

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 045.0080121

Product Name: VAL DTM ACRY GLS EN TNTBS

Product Use: Paint product.
Print date: 05/Feb/2014
Revision Date: 04/Feb/2014

Company Identification

The Valspar Corporation - Architectural Coatings Division 1191 Wheeling Road Wheeling, IL 60090

Manufacturer's Phone: 1-847-520-8580

24-Hour Medical Emergency 1-888-345-5732

Phone:

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation Ingestion Skin absorption

Eye Contact:

· Moderate eye irritation

Skin Contact:

- · Causes skin irritation.
- · May cause defatting of the skin.
- · Harmful if absorbed through skin.
- Can be absorbed through skin.

Ingestion:

· Harmful if swallowed.

Inhalation:

- · May cause irritation of respiratory tract.
- · Harmful by inhalation.

Target Organ and Other Health Effects:

- Causes headache, drowsiness or other effects to the central nervous system.
- Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.
- Kidney injury may occur.
- · Liver injury may occur.
- Spleen damage may occur.

This product contains ingredients that may contribute to the following potential chronic health effects:

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain
and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be
harmful or fatal.

Carcinogens:

• Possible cancer hazard. Contains material which may cause cancer based on animal data.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
TITANIUM DIOXIDE 13463-67-7	15 - 20	Titanium dioxide
DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8	1 - 5	Dipropylene glycol monomethyl ether
PROPYLENE GLYCOL N- BUTYL ETHER 5131-66-8	1 - 5	1-Butoxy-2-propanol
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	2-Butoxyethanol

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES

Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Never give anything by mouth to an unconscious person. Only induce vomiting at the instruction of medical personnel. Get medical attention.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit): 201 Flash point (Celsius): 94

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

Sensitivity to impact:

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

Hazardous combustion products: See Section 10.

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Other Personel Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
TITANIUM DIOXIDE 13463-67-7	15 - 20	15 mg/m ³ TWA dust total		
DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8	1 - 5	100 ppm TWA 600 mg/m³ TWA		prevent or reduce skin absorption
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	240 mg/m³ TWA 50 ppm TWA		prevent or reduce skin absorption

ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
TITANIUM DIOXIDE 13463-67-7	15 - 20	10 mg/m ³ TWA			
DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8	1 - 5	100 ppm TWA	150 ppm STEL		CAN BE ABSORBED THROUGH THE SKIN
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	20 ppm TWA			

9. PHYSICAL PROPERTIES

Odor: Normal for this product type.

Physical State: liquid

pH: not determined

Vapor pressure: 24 mmHg @ 77°F (25°C)

Vapor density (air = 1.0): 5.11

Boiling point: 212°F (100°C)
Solubility in water: not determined
Coefficient of water/oil distribution: not determined

Density (lbs per US gallon):

Specific Gravity:

Evaporation rate (butyl acetate = 1.0):

Flash point (Fahrenheit):

Flash point (Celsius):

94

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: None known.

Incompatibility: Strong oxidizing agents

Hazardous Polymerization: None anticipated.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide. Metal oxide fumes.

10. STABILITY AND REACTIVITY

Sensitivity to static discharge:

Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
TITANIUM DIOXIDE 13463-67-7	15 - 20	> 10000 mg/kg Oral LD50 Rat
DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8	1 - 5	= 5230 mg/kg Oral LD50 Rat = 9500 mg/kg Dermal LD50 Rabbit
PROPYLENE GLYCOL N- BUTYL ETHER 5131-66-8	1 - 5	= 3100 mg/kg Dermal LD50 Rabbit = 5660 μL/kg Oral LD50 Rat
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	= 2.21 mg/L Inhalation LC50 Rat 4 h = 220 mg/kg Dermal LD50 Rabbit = 2270 mg/kg Dermal LD50 Rat = 450 ppm Inhalation LC50 Rat 4 h = 470 mg/kg Oral LD50 Rat

Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

3	Approx.	IARC Group 1 - Human	IARC Group 2A - Limited	IARC Group 2B -
	Weight %	Evidence	Human Data	Sufficient Animal Data
TITANIUM DIOXIDE 13463-67-7	15 - 20			Monograph 47 [1989]

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 13463-67-7	15 - 20	Present		
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5			A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

14. TRANSPORTATION INFORMATION

Proper Shipping Name: NOT REGULATED

U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

Proper shipping name: NOT REGULATED

International Maritime Organization (IMO):

Proper shipping name: NOT REGULATED

Marine Pollutant No

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

Ingredient Name	Approx.	SARA 302	SARA 313	CERCLA RQ in lbs.	
CAS-No.	Weight %				
ETHYLENE GLYCOL	1 - 5		YES		
MONOBUTYL ETHER					
111-76-2					

SARA 311/312 Hazard Class:

Acute: yes
Chronic: yes
Flammability: no
Reactivity: no
Sudden Pressure: no

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317

Pennsylvania Right To Know:

ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2
PROPYLENE GLYCOL N-BUTYL ETHER 5131-66-8
DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8

TITANIUM DIOXIDE 13463-67-7

Additional Non-Hazardous Materials

WATER 7732-18-5

PROPRIETARY RESIN Trade Secret

Rule 66 status of product Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

Not all components in this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

HMIS Codes

Health: 1 Flammability: 0 Reactivity: 0

PPE: X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By: Regulatory Affairs Department

Print date: 05/Feb/2014 Revision Date: 05/Feb/2014