

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

1. Identification

Product Identification

Product Identifier: ETR
Recommended Use: Epoxy Paste-Over Material for Crack Repair
Use Restrictions: None Known.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

ETR is a two part system. The two parts of this product have been assessed according to GHS and are classified below. The final hardened material is considered nonhazardous. Some hazards apply upon grinding or cutting through hardened product.

Part A (white side) GHS Classification

Classification according to HazCom 2012 (GHS)

Physical Hazards:	Not Classified.	
Health Hazards	Skin Corrosion/Irritation	Category 2
	Serious Eye Damage/Irritation	Category 2A
	Sensitization, Skin	Category 1
	Germ Cell Mutagenicity	Category 2
	STOT, Single Exposure	Category 2 (narcotic effects)
Environmental Hazards:	Acute Aquatic Environmental Hazard	Category 2
	Chronic Aquatic Environmental Hazard	Category 2

GHS Label Elements



Signal Word: **WARNING!**

Hazard Statements: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid release to the environment.
Response:	If exposed or concerned: Call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before re-use. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect Spillage.
Storage:	Store locked up. Store in a well-ventilated place. Store between 45-90°F (7-32°C).
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

Part B (black side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Flammable Liquid	Category 4
Health Hazards:	Skin Corrosion/Irritation	Category 1C
	Serious Eye Damage/Irritation	Category 1
	Sensitization, Skin	Category 1
	STOT, Single Exposure	Category 2 (narcotic effects)
Environmental Hazards:	Not Classified.	

GHS Label Elements



Signal Word:	DANGER!
Hazard Statements:	Combustible liquid. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Precautionary Statements:	
Prevention:	Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray.
Response:	If swallowed: Rinse mouth. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before re-use.
Storage:	Store locked up. Store in a well-ventilated place. Store between 45-90°F (7-32°C).
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured components of ETR. Upon combination with the components of ETR form an innocuous solid which does not present any immediate hazards. Upon grinding or cutting the cured product, the following hazards may apply.



Health Hazards:	Carcinogenicity	Category 2
Hazard Statements:	Suspected of causing cancer.	
Precautionary Statements:	Do not breathe dust.	

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

Part A (white side)

Chemical Name	CAS Number	Weight %
Bisphenol A/Epichlorohydrin	25068-38-6	40-60
Wollastonite	13983-17-0	20-30
Limestone	1317-65-3	10-20
o-Cresyl Glycidyl Ether	2210-79-9	1-10
Titanium Dioxide	13463-67-7	1-5

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

Part B (black side)

Chemical Name	CAS Number	Weight %
Wollastonite	13983-17-0	35-50
Polymercaptan	N/A	15-30
Diethylenetriamine	111-40-0	1-10
Limestone	1317-65-3	1-10
Terpene Hydrocarbon	8002-09-3	1-10

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

- Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician.**
- Skin Contact:** Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. If skin irritation persists **consult a physician.**
- Ingestion:** Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. **Consult a physician.**
- Inhalation:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

Most Important Symptoms

Symptoms include itching, burning, redness and tearing. Sensitization. Rash. Drowsiness and dizziness. Headaches, nausea and vomiting. Corrosive effects. Permanent eye damage including blindness could result.

5. Fire-Fighting Measures

- Suitable Extinguishing Media:** Extinguish with foam, carbon dioxide, dry powder, or water fog.
- Additional Information:** None known.
- Hazards during Fire-Fighting:** Hazardous decomposition products may occur when materials polymerize at temperatures above 500 °F (260°C). Irritating and toxic gases/fumes may be released during a fire. Do not allow run-off from fire-fighting to enter drains or water courses.
- Fire-Fighting Procedures:** Use standard firefighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Clean-Up Methods

- Small spills:** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.
- Large spills:** Stop the flow of material, if this is without risk. Dike far ahead of spill. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas.

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

7. Handling and Storage

Handling

Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Avoid contact with eyes, skin, and clothing. Observe good industrial hygiene practices.

Storage

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a dry place out of direct sunlight. Keep out of the reach of children. Store between 45-90°F (7-32°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Store locked up.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure:	Wear appropriate personal protective equipment.
Eye Protection:	Wear chemical splash goggles or safety glasses with side shield.
Hand Protection:	Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection:	Wear long sleeve shirt/long pants and other clothing as required to minimize contact.
Respirator Protection:	The use of a respirator is not required during normal use of this product. If grinding or cutting cured product the use of a respirator is recommended.
General Hygiene:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

When using indoors good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Titanium dioxide (CAS 13463-67-7)	15 mg/m ³ (Total dust)	10 mg/m ³	N/E
Limestone (CAS 1317-65-3)	5 mg/m ³ (Respirable) 15 mg/m ³ (Total dust)	N/E	5 mg/m ³ (Respirable) 10 mg/m ³ (Total dust)
Diethylenetriamine (CAS 111-40-0)	N/E	1 ppm (TWA)	4 mg/m ³ (REL, TWA) 1 ppm (REL, TWA)

Additional Information

After Cure: Product forms an innocuous solid. Processing after cure (grinding or cutting) may produce dust containing compounds that present an inhalation hazard.

9. Physical and Chemical Properties

<u>Property</u>	<u>Part A</u>	<u>Part B</u>
Physical State:	Liquid, Paste	Liquid, Paste
Color:	White	Black
Odor:	No Significant Odor	Strong, skunk like
pH:	8.4	10.2
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	>1 torr (356°F, 180°C)	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Appreciable
Freezing/Melting Point:	No data	No data

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

Boiling Point:	> 392 °F (>200 °C)	No data
Flash Point:	>300 °F (>149 °C) Closed Cup	172 °F (78 °C) Closed Cup
Evaporation Rate:	No data	No data
Decomposition Temperature:	No data	No data
Specific Gravity:	1.56 at 72°F (22°C)	1.55 at 72°F (22°C)
VOC (after cure):	7 g/L	7 g/L
Kow:	No data	No data
Viscosity:	No data	No data

10. Stability and Reactivity

Part A (white side)

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Strong oxidizing agents. Acids. Amines. Bases, alkalis (organic).
Hazardous Reactions:	Hazardous polymerization does not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

Part B (black side)

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Strong oxidizing agents. Strong acids.
Hazardous Reactions:	Hazardous polymerization will not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	Causes digestive tract burns. Ingestion may cause irritation to the gastrointestinal tract.
Inhalation:	Causes respiratory tract burns. If this material is heated or misted, coughing and mild, temporary irritation may occur.
Skin contact:	Causes skin irritation. Causes severe skin burns. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation. Causes serious eye burns.

Information on Toxicological Effects

Acute toxicity:	Occupational exposure to the substance or mixture may cause adverse effects.
------------------------	--

Product	Species	Test Result
o-Cresyl Glycidyl Ether (2210-79-9)		
Acute, Dermal, LD50	Rat	>2000 mg/kg
Acute, Inhalation, LC50	Rat	>6.1 mg/l, 4 hours
Acute, Oral, LD50	Rat	>5000 mg/kg

Skin corrosion/irritation:	Causes skin irritation.
Eye damage/eye irritation:	Causes serious eye irritation. Causes serious eye damage.
Respiratory sensitization:	No data available.
Skin sensitization:	May cause an allergic skin reaction.
Germ cell mutagenicity:	Contains a component that is suspected of causing genetic defects.
Carcinogenicity:	Titanium Dioxide is considered a carcinogen only in its inhalable form. Exposure is likely only when grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure. IARC Monographs. Overall Evaluation of Carcinogenicity Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans Wollastonite (CAS 13983-17-0) 3 Not classifiable as to carcinogenicity
Reproductive toxicity:	No data available.
Aspiration hazard:	No data available.
Specific target organ toxicity:	
Single exposure	May cause drowsiness or dizziness.
Repeated exposure	No data available.

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and similar products. Part A is classified as toxic to aquatic life with long lasting effects. Part B is not classified as environmentally hazardous. Avoid release to the environment.

Supporting Data

Component	Species	Test Result
Bisphenol A/Epichlorohydrin (25068-38-6)		
Fish, LC50	Salmo Gairdneri	1.5 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia Magna	2.7 mg/l, 48 hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic , Crustacea, EC50	Daphnia	>1000 mg/l, 48 hours
Aquatic , Fish, LC50	Mummichog	>1000 mg/l, 96 hours

Persistence and degradability: This product is not suspected to be readily biodegradable.

Bioaccumulative potential: No data available for this product.

Mobility in soil: No data available.

Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Consideration

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Grind or chip off surface. Solid material does not need special disposal considerations.

14. Transportation Information

Resin (white side)

UN number: UN3082

UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant

Precautions: Marine Pollutant

Required Labels: 9

ERG Code (IATA): 9L

EmS (IMDG): F-A, S-F

Hardener (black side)

UN number: UN3259

UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (Diethylenetriamine), 8, III

Precautions: Corrosive

Required Labels: 8

ERG Code (IATA): 8L

EmS (IMDG): F-A, S-B

Additional Information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not intended to be transported in bulk.

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA 302 Extremely hazardous substance: No
SARA 311/312 Hazardous chemical: Yes
SARA 313 (TRI reporting): Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:	Immediate	Delayed	Fire	Pressure	Reactivity
Part A	Yes	Yes	No	No	No
Part B	Yes	Yes	Yes	No	No

US State Right-To-Know Lists

Chemical	Massachusetts RTK	New Jersey Work and Community RTK Act	Pennsylvania Worker and Community RTK Law	Rhode Island RTK
Diethylenetriamine (CAS 111-40-0)	Listed	Listed	Listed	Not on List
Limestone (CAS 1317-65-3)	Listed		Listed	
Titanium dioxide (CAS 13463-67-7)	Listed		Listed	

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or reproductive harm.

Component	Regulation	% In Blend (approx.)	Remark
Titanium dioxide (CAS 13463-67-7)	ACGIH	1-10	Carcinogenic

Canada

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.

WHMIS Classification

		
Class E: Corrosive	Class B-3: Combustible Liquid	Class D-2B: Material Causing other toxic effects

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

SIMPSON

Strong-Tie

International

International Inventories


Country or Region	Inventory	On Inventory? (Yes/No)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

16. Other Information

Date Prepared or Revised: September 2014
Supersedes: August 2012

Additional Part A (white side) Classifications

NFPA Ratings




HMIS Rating

HEALTH HAZARD	2
FLAMMABILITY HAZARD	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

Additional Part B (black side) Classifications

NFPA Ratings



HMIS Rating

HEALTH HAZARD	3
FLAMMABILITY HAZARD	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
CPR:	Controlled Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
EPA:	Environmental Protection Agency (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HEPA:	High-Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code

ETR Crack Injection Paste-Over Adhesive

SAFETY DATA SHEET

LPP:	Limité Permissible Ponderado (Chile)
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
SDS:	Safety Data Sheet
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
U.S.:	United States
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2014 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY

ETR Part A: XCOM3B – 50% Cartridge

ETR Part B: XCOM3A – 50% Cartridge
XCORR – 50% Cartridge