

Material Safety Data Sheet



Zep, Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-I-BUY-ZEP (428-9937)
www.zep.com

Section 1. Chemical Product and Company Identification

Product name ML LUBRICANT
Product use Aerosol Lubricant
Product code 7313
Date of issue 08/05/09 **Supersedes** 03/09/06

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

Printing date: 08/05/09

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

DANGER !

1 3 0

FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire. Do not smoke. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Inhalation.

Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin

Causes skin irritation. Product may be dermal absorbed. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation

Over-exposure by inhalation may cause respiratory irritation. Inhalation causes headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Can cause central nervous system (CNS) depression.

Ingestion

Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Contains material which may cause damage to the following organs: central nervous system (CNS).

Carcinogenicity

No known significant effects or critical hazards.

Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

CAS number

% by Weight

BLEND OF ISOBUTANE & PROPANE

74-98-6; 75-28-5

10 - 20

PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate

64742-52-5

10 - 20

ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)

64741-73-7

5 - 15

Section 4. First Aid Measures

Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact

Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

Inhalation


Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Not available.
Flammable Limits	Not determined.
Flammability	FLAMMABLE. (CSMA method)
Fire hazard	CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed. May emit toxic fumes under fire conditions.
Fire-Fighting Procedures	Use an extinguishing agent suitable for the surrounding fire.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wash thoroughly after handling. Empty containers retain product residue and can be hazardous.
Storage	CONTENTS UNDER PRESSURE. Do not puncture, incinerate, store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

BLEND OF ISOBUTANE & PROPANE

PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate

ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)

Exposure limits**ACGIH TLV (United States).**

TWA: 800 ppm 8 hour(s).

OSHA PEL (United States).

TWA: 1000 ppm 8 hour(s).

OSHA PEL (United States).TWA: 5 mg/m³ 8 hour(s). Form: Mist**ACGIH TLV (United States).**TWA: 5 mg/m³ 8 hour(s). Form: Mist**NIOSH REL (United States).**TWA: 1200 mg/m³ Form: Vapor**Personal Protective Equipment (PPE)**

Eyes	Safety glasses.
Body	Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Nitrile gloves.
Respiratory	Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

Section 9. Physical and Chemical Properties

Physical State	Liquid. [Aerosol. Viscous liquid. Oily liquid.]	Color	Black.
pH	Not available.	Odor	Solvent-like.
Boiling Point	>200°C (>392°F)	Vapor Pressure	Not determined.
Specific Gravity	0.905	Vapor Density	Not determined.
Solubility	Insoluble in the following materials: cold water and hot water.	Evaporation Rate	Not determined.
		VOC (Consumer)	339.69 (g/l). 2.83 lbs/gal (37.60%)

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Incompatibility	Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.
Hazardous Polymerization	Will not occur.
Hazardous Decomposition Products	carbon oxides (CO, CO ₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Isoparaffinic Solvent; Hydrotreated light distillate (petroleum)	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Section 12. Ecological Information**Aquatic Ecotoxicity**

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D001
Classification: - [Hazardous waste.]
Origin: - [RCRA waste.]

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Consumer commodity	ORM-D	-	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

[All Components of this product are listed or exempt from listing on TSCA Inventory.](#)

State Regulations

California Prop 65 No products were found.

Section 16. Other Information

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.
Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.