



SAFETY DATA SHEET

SeaShield 550 Epoxy Grout Part A (Resin)

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name SeaShield 550 Epoxy Grout Part A (Resin)

Product number 7071073R

Recommended use of the chemical and restrictions on use

Application Part of a corrosion protection system.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier See Manufacturer

Manufacturer Denso North America
9710 Telge Road
Houston, TX 77095
1 (281) 821-3355
1 (281) 821-0304
info@densona.com

Emergency telephone number

Emergency telephone 1-801-629-0667

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Hazard symbols



Signal word Warning

Hazard statements H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

SeaShield 550 Epoxy Grout Part A (Resin)

Precautionary statements

P102 Keep out of reach of children.
 P202 Do not handle until all safety precautions have been read and understood.
 P234 Keep only in original container.
 P261 Avoid breathing vapor/ spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P284 In case of inadequate ventilation wear respiratory protection.
 P301+P312 If swallowed: Call a poison center/ doctor if you feel unwell.
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
 P302+P352 If on skin: Wash with plenty of water.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 If exposed or concerned: Get medical advice/ attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P391 Collect spillage.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Proprietary Resin A, Proprietary Resin B, Proprietary Resin C, Proprietary Resin D, Proprietary Resin E

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Proprietary Resin A	60-100%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	

SeaShield 550 Epoxy Grout Part A (Resin)

Proprietary Resin B	10-30%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
Proprietary Resin C	10-30%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	
Proprietary Resin D	10-30%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
Proprietary Resin E	<1%
CAS number: Proprietary	
Classification	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information	Get medical advice/attention if you feel unwell. Show this Safety Data Sheet to the medical personnel. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Never give anything by mouth to an unconscious person. Get medical attention if symptoms are severe or persist.

SeaShield 550 Epoxy Grout Part A (Resin)

Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Skin Contact	It is important to remove the substance from the skin immediately. Remove contaminated clothing immediately and wash skin with soap and water. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contamination with soap and water or recognized skin cleansing agent. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if symptoms are severe or persist after washing. Following contact with hot product, immediately immerse affected area in, or flush with, large amounts of cold water to dissipate heat and cover with clean cotton sheeting or gauze. Get medical attention. In the event of any sensitization symptoms developing, ensure further exposure is avoided.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention promptly if symptoms occur after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation. Symptoms following overexposure may include the following: Nausea, vomiting. Diarrhea.
Skin contact	Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: Eczema/contact dermatitis. May cause skin sensitization or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Profuse watering of the eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.
-----------------------------	--

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

SeaShield 550 Epoxy Grout Part A (Resin)

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances:
Harmful gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Regular protection may not be safe. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Do not touch or walk into spilled material. Avoid inhalation of vapors and contact with skin and eyes. Use suitable respiratory protection if ventilation is inadequate. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place.

Environmental precautions

Environmental precautions The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Stop leak if safe to do so. If leakage cannot be stopped, evacuate area. Provide adequate ventilation. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

SeaShield 550 Epoxy Grout Part A (Resin)

Usage precautions

Read and follow manufacturer's recommendations. Do not handle until all safety precautions have been read and understood. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid breathing gas, fume, vapours or spray. Avoid contact with skin, eyes and clothing. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid discharge to the aquatic environment. Do not handle broken packages without protective equipment. Do not reuse empty containers. Use only outdoors or in a well-ventilated area.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class

Miscellaneous hazardous material storage.

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

SeaShield 550 Epoxy Grout Part A (Resin)

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Persons susceptible to allergic reactions should not handle this product. Take off immediately all contaminated clothing and wash it before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Amber.
Odor	Characteristic.
Odor threshold	No specific test data are available.
pH	pH (concentrated solution): near 7
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	> 93°C/200°F Closed cup.
Evaporation rate	No specific test data are available.
Evaporation factor	No specific test data are available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Other flammability	No specific test data are available.

SeaShield 550 Epoxy Grout Part A (Resin)

Vapor pressure	No specific test data are available.
Vapor density	> 1
Relative density	1.2 @ 23°C/75°F
Bulk density	No specific test data are available.
Solubility(ies)	No specific test data are available.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	400 cP @ 23°C/75°F
Explosive properties	No specific test data are available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidizing properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidizing.

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Amines. Strong acids. Strong alkalis. Strong oxidizing agents.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Containers can burst violently or explode when heated, due to excessive pressure build-up.
Materials to avoid	Amines. Strong acids. Strong alkalis. Strong oxidizing agents.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Toxicological effects	When mixed with Part B, the mixture cures and forms an inert solid and is not considered hazardous.
<u>Acute toxicity - oral</u> Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u> Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - inhalation</u> Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u> Animal data	Irritating.

SeaShield 550 Epoxy Grout Part A (Resin)

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization May cause skin sensitization or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause sensitization or allergic reactions in sensitive individuals. May cause irritation.

Skin Contact

May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin.

Eye contact

Irritating to eyes.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target Organs

No specific target organs known.

Medical considerations

Skin disorders and allergies.

12. Ecological information

Ecotoxicity

The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. It is unlikely that the substance will dissolve in water in amounts big enough to have a toxic effect on fish and daphnia. However, large or frequent spills may have hazardous effects on the environment. When mixed with Part B, the mixture cures and forms an inert solid and is not considered hazardous.

Toxicity

Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Persistence and degradability

SeaShield 550 Epoxy Grout Part A (Resin)

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

UN Number

UN No. (TDG) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (DOT) UN3082

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin), 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin), 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin), 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Reaction product: bisphenol-A-(epichlorhydrin), 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

Transport hazard class(es)

DOT hazard class 9

DOT hazard label 9

SeaShield 550 Epoxy Grout Part A (Resin)

TDG class	9
TDG label(s)	9
IMDG Class	9
ICAO class/division	9

Transport labels



DOT transport labels



Packing group

TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

None of the ingredients are listed or exempt.

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

SeaShield 550 Epoxy Grout Part A (Resin)

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

Massachusetts "Right To Know" List

None of the ingredients are listed or exempt.

Rhode Island "Right To Know" List

None of the ingredients are listed or exempt.

Minnesota "Right To Know" List

None of the ingredients are listed or exempt.

New Jersey "Right To Know" List

None of the ingredients are listed or exempt.

Pennsylvania "Right To Know" List

None of the ingredients are listed or exempt.

Inventories

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

SeaShield 550 Epoxy Grout Part A (Resin)

Abbreviations and acronyms used in the safety data sheet	<p>TDG: The transport of dangerous goods act</p> <p>IATA: International air transport association.</p> <p>ICAO: Technical instructions for the safe transport of dangerous goods by air.</p> <p>IMDG: International maritime dangerous goods.</p> <p>CAS: Chemical abstracts service.</p> <p>ATE: Acute toxicity estimate.</p> <p>LC₅₀: Lethal concentration to 50 % of a test population.</p> <p>LD₅₀: Lethal dose to 50% of a test population (median lethal dose).</p> <p>EC₅₀: 50% of maximal effective concentration.</p> <p>PBT: Persistent, bioaccumulative and toxic substance.</p> <p>vPvB: Very persistent and very bioaccumulative.</p>
Classification abbreviations and acronyms	<p>Eye Irrit. = Eye irritation</p> <p>Skin Irrit. = Skin irritation</p> <p>Skin Sens. = Skin sensitisation</p> <p>Aquatic Chronic = Hazardous to the aquatic environment (chronic)</p>
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Issued by	HS&E Manager.
Revision date	7/31/2020
Revision	2
Supersedes date	4/21/2017
SDS No.	5035
Hazard statements in full	<p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.