



## SAFETY DATA SHEET

### SeaShield 550 Epoxy Grout Part C (Aggregate)

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

##### Product identifier

**Product name** SeaShield 550 Epoxy Grout Part C (Aggregate)

**Product number** 7071078

##### Recommended use of the chemical and restrictions on use

**Application** Part of a corrosion protection system.

**Uses advised against** No specific uses advised against are identified.

##### Details of the supplier of the safety data sheet

**Supplier** See Manufacturer

**Manufacturer** Denso North America  
9710 Telge Road  
Houston, TX 77095  
1 (281) 821-3355  
1 (281) 821-0304  
info@densona.com

##### Emergency telephone number

**Emergency telephone** 1-801-629-0667

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 1B - H350 STOT SE 3 - H335 STOT RE 1 - H372

**Environmental hazards** Not Classified

##### Label elements

##### Hazard symbols



**Signal word**

Danger

##### Hazard statements

H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H350 May cause cancer.  
H335 May cause respiratory irritation.  
H372 Causes damage to organs through prolonged or repeated exposure.

## SeaShield 550 Epoxy Grout Part C (Aggregate)

### Precautionary statements

P102 Keep out of reach of children.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P234 Keep only in original container.  
 P261 Avoid breathing dust.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P284 In case of inadequate ventilation wear respiratory protection.  
 P301+P310 If swallowed: Immediately call a poison center/ doctor.  
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.  
 P302+P352 If on skin: Wash with plenty of water.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 If exposed or concerned: Get medical advice/ attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P391 Collect spillage.  
 P402 Store in a dry place.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

Proprietary Solid A, Proprietary Solid B, Proprietary Solid C, Proprietary Solid D

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Proprietary Solid A</b> CAS number: Proprietary	<b>60-100%</b>
<b>Classification</b> Carc. 1B - H350 STOT RE 1 - H372	
<b>Proprietary Solid B</b> CAS number: Proprietary	<b>30-60%</b>
<b>Classification</b> Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1B - H317 STOT SE 3 - H335	

## SeaShield 550 Epoxy Grout Part C (Aggregate)

<b>Proprietary Solid C</b>	<b>1-5%</b>
CAS number: Proprietary	
<b>Classification</b>	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
<b>Proprietary Solid D</b>	<b>1-5%</b>
CAS number: Proprietary	
<b>Classification</b>	
Met. Corr. 1 - H290	
Skin Corr. 1A - H314	
Eye Dam. 1 - H318	

The full text for all hazard statements is displayed in Section 16.

**Composition comments**            The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

#### 4. First-aid measures

##### Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Do not induce vomiting unless under the direction of medical personnel. Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention if symptoms are severe or persist.
<b>Skin Contact</b>	It is important to remove the substance from the skin immediately. In the event of any sensitization symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognized skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

##### Most important symptoms and effects, both acute and delayed

**General information**            The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

## SeaShield 550 Epoxy Grout Part C (Aggregate)

<b>Inhalation</b>	A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
<b>Ingestion</b>	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
<b>Skin contact</b>	May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
<b>Eye contact</b>	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

### Indication of immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.
-----------------------------	--

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

**Specific hazards** None known.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

#### Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Avoid inhalation of dust. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place.

#### Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

#### Methods and material for containment and cleaning up

## SeaShield 550 Epoxy Grout Part C (Aggregate)

<b>Methods for cleaning up</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### 7. Handling and storage

#### Precautions for safe handling

<b>Usage precautions</b>	Read and follow manufacturer's recommendations. Do not handle until all safety precautions have been read and understood. Wear protective clothing as described in Section 8 of this safety data sheet. Good personal hygiene procedures should be implemented. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. Keep container dry. Do not handle broken packages without protective equipment. Do not reuse empty containers. Use only in well-ventilated areas. Do not use in confined spaces without adequate ventilation and/or respirator. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. Do not get in eyes, on skin, or on clothing. Do not breathe dust. May cause cancer.
--------------------------	--

<b>Advice on general occupational hygiene</b>	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.
---	--

#### Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Store away from incompatible materials (see Section 10). Store locked up. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Store in a dry place.
----------------------------	--

<b>Storage class</b>	Chemical storage.
----------------------	-------------------

#### Specific end uses(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.
----------------------------	---

### 8. Exposure controls/Personal protection

#### Control parameters

#### Occupational exposure limits

##### **Proprietary Solid A**

Long-term exposure limit (8-hour TWA): OSHA 0.05 mg/m<sup>3</sup> respirable dust  
 Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m<sup>3</sup> respirable fraction  
 A2

##### **Proprietary Solid B**

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> total dust  
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m<sup>3</sup> respirable fraction  
 Long-term exposure limit (8-hour TWA): ACGIH 1 mg/m<sup>3</sup> respirable fraction  
 A4

##### **Proprietary Solid C**

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m<sup>3</sup>  
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m<sup>3</sup>

## SeaShield 550 Epoxy Grout Part C (Aggregate)

OSHA = Occupational Safety and Health Administration.  
 ACGIH = American Conference of Governmental Industrial Hygienists.  
 A2 = Suspected Human Carcinogen.  
 A4 = Not Classifiable as a Human Carcinogen.

### Proprietary Solid A

**Immediate danger to life and health** 25 mg/m<sup>3</sup> 50 mg/m<sup>3</sup>

### Proprietary Solid B

**Immediate danger to life and health** 5000 mg/m<sup>3</sup>

### Proprietary Solid C

**Immediate danger to life and health** 25 mg/m<sup>3</sup>

### Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Use mechanical ventilation if there is a risk of handling causing formation of airborne dust. Ensure that the direction of airflow is clearly away from the worker. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure operatives are trained to minimize exposure.

#### Eye/face protection

Not normally required. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133.

#### Hand protection

Wear protective gloves. It is recommended that gloves are made of the following material: Leather.

#### Other skin and body protection

Not normally required. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

#### Hygiene measures

Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

#### Respiratory protection

The use of a respirator is normally not required for outdoor application and areas with adequate ventilation. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. If dust is generated: Wear a suitable dust mask.

#### Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

## SeaShield 550 Epoxy Grout Part C (Aggregate)

<b>Appearance</b>	Dusty powder.
<b>Color</b>	Grey.
<b>Odor</b>	Odorless.
<b>Relative density</b>	> 2
<b>Solubility(ies)</b>	Slightly soluble in water.

### 10. Stability and reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE oral (mg/kg)</b>	12,500.0

##### Acute toxicity - dermal

<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
---------------------------------------	--

##### Acute toxicity - inhalation

<b>Notes (inhalation LC<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
---	--

##### Skin corrosion/irritation

<b>Animal data</b>	Irritating.
--------------------	-------------

##### Serious eye damage/irritation

<b>Serious eye damage/irritation</b>	Eye Dam. 1 - H318 Causes serious eye damage.
--------------------------------------	--

##### Respiratory sensitization

<b>Respiratory sensitization</b>	Based on available data the classification criteria are not met.
----------------------------------	--

##### Skin sensitization

<b>Skin sensitization</b>	May cause skin sensitization or allergic reactions in sensitive individuals.
---------------------------	--

##### Germ cell mutagenicity

<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
--------------------------------	--

##### Carcinogenicity

<b>Carcinogenicity</b>	May cause cancer.
------------------------	-------------------

## SeaShield 550 Epoxy Grout Part C (Aggregate)

<b>IARC carcinogenicity</b>	Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	STOT SE 3 - H335 May cause respiratory irritation.
<b>Target organs</b>	Respiratory system, lungs
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	STOT RE 1 - H372
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Not relevant. Solid.
<b>General information</b>	
	May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing.
<b>Ingestion</b>	May cause sensitization or allergic reactions in sensitive individuals. May cause irritation.
<b>Skin Contact</b>	May cause skin sensitization or allergic reactions in sensitive individuals. Redness. Irritating to skin.
<b>Eye contact</b>	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	Respiratory system, lungs
<b>Medical considerations</b>	Skin disorders and allergies.
<b>12. Ecological information</b>	
<b>Ecotoxicity</b>	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
<b>Toxicity</b>	Based on available data the classification criteria are not met.
<b><u>Persistence and degradability</u></b>	
<b>Persistence and degradability</b>	The degradability of the product is not known.
<b><u>Bioaccumulative potential</u></b>	
<b>Bio-Accumulative Potential</b>	No data available on bioaccumulation.
<b><u>Mobility in soil</u></b>	
<b>Mobility</b>	No data available.
<b><u>Other adverse effects</u></b>	
<b>Other adverse effects</b>	None known.



## SeaShield 550 Epoxy Grout Part C (Aggregate)

### 13. Disposal considerations

#### Waste treatment methods

##### **General information**

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

##### **Disposal methods**

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

### 14. Transport information

##### **General**

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

##### UN Number

**UN No. (International)** Not applicable.

**UN No. (DOT)** Not applicable.

##### UN proper shipping name

**Proper shipping name (International)** Not applicable.

**Proper shipping name (DOT)** Not applicable.

##### Transport hazard class(es)

**Transport Labels (International)** No transport warning sign required.

##### **DOT transport labels**

No transport warning sign required.

##### Packing group

**Packing group (International)** Not applicable.

**DOT packing group** Not applicable.

##### Environmental hazards

##### **Environmentally Hazardous Substance**

No.

##### Special precautions for user

Not applicable.

**DOT reportable quantity** Not applicable.

**DOT TIH Zone** Not applicable.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## SeaShield 550 Epoxy Grout Part C (Aggregate)

### 15. Regulatory information

#### US Federal Regulations

##### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

##### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

*Proprietary Solid D*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

##### **SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

##### **SARA 313 Emission Reporting**

None of the ingredients are listed or exempt.

##### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

##### **FDA - Essential Chemical**

None of the ingredients are listed or exempt.

##### **FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

##### **SARA (311/312) Hazard Categories**

None of the ingredients are listed or exempt.

##### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

#### US State Regulations

##### **California Proposition 65 Carcinogens and Reproductive Toxins**

None of the ingredients are listed or exempt.

##### **California Air Toxics "Hot Spots" (A-I)**

None of the ingredients are listed or exempt.

##### **California Air Toxics "Hot Spots" (A-II)**

None of the ingredients are listed or exempt.

##### **California Directors List of Hazardous Substances**

The following ingredients are listed or exempt:

*Proprietary Solid C*

*Proprietary Solid D*

##### **Massachusetts "Right To Know" List**

All the ingredients are listed or exempt.

##### **Rhode Island "Right To Know" List**

The following ingredients are listed or exempt:

*Proprietary Solid C*

*Proprietary Solid A*

## SeaShield 550 Epoxy Grout Part C (Aggregate)

*Proprietary Solid B*

### Minnesota "Right To Know" List

The following ingredients are listed or exempt:

*Proprietary Solid C*

*Proprietary Solid A*

*Proprietary Solid B*

### New Jersey "Right To Know" List

All the ingredients are listed or exempt.

### Pennsylvania "Right To Know" List

All the ingredients are listed or exempt.

### Inventories

#### US - TSCA

All the ingredients are listed or exempt.

#### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### 16. Other information

#### Abbreviations and acronyms used in the safety data sheet

TDG: The transport of dangerous goods act

IATA: International air transport association.

ICAO: Technical instructions for the safe transport of dangerous goods by air.

IMDG: International maritime dangerous goods.

CAS: Chemical abstracts service.

ATE: Acute toxicity estimate.

LC<sub>50</sub>: Lethal concentration to 50 % of a test population.

LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).

EC<sub>50</sub>: 50% of maximal effective concentration.

PBT: Persistent, bioaccumulative and toxic substance.

vPvB: Very persistent and very bioaccumulative.

#### Classification abbreviations and acronyms

Carc. = Carcinogenicity

Eye Dam. = Serious eye damage

Skin Irrit. = Skin irritation

Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure

STOT SE = Specific target organ toxicity-single exposure

#### Training advice

Only trained personnel should use this material.

#### Issued by

HS&E Manager.

#### Revision date

7/31/2020

#### Revision

2

#### Supersedes date

7/26/2019

#### SDS No.

5258

## SeaShield 550 Epoxy Grout Part C (Aggregate)

### Hazard statements in full

H290 May be corrosive to metals.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H372 Causes damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.