

# **Hazardous Substance, NON-Dangerous Goods**

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

# Product Identifier: Selleys Cracks Gone Outside Powder Filler

**Synonyms:** Product Code Bar Code Cracks Gone Outside Powder Filler, 1kg - 9300697127044

Relevant identified uses of the substance or mixture and uses advised against: Cement based, exterior filler. No information for uses advised against.

Details of the supplier of the safety data sheet:

Supplier/Distributor: Selleys Australia Craig and Rose Ltd

Street Address: 1 Gow Street, Unit 8, Halbeath Industrial Estate,

Padstow NSW 2211 Crossgates Road, Halbeath,

Australia Dunfermline, Fife, KY11 7EG

Scotland

**Telephone:** 0800 085 6278 **Web Address:** www.selleys.com

**E:Mail** selleys.sds@selleys.co.uk

24hr UK Emergency telephone number: 0800 085 6522

#### 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture: This material is classified as hazardous according to the criteria of Regulation (EC) No. 1272/2008 (CLP).

Skin Corrosion/Irritation – Category 2 Serious Eye Damage/Irritation – Category 1 Specific Target Organ Toxicity (Single Exposure) – Category 3

## Label elements/pictogram:



# Signal word:

Danger

#### **Hazard statements:**

H315 Causes skin irritation
H318 Causes serious eye damage
H335 May cause respiratory irritation

## **Precautionary statements:**

P102 Keep out of reach of children P103 Read label before use P261 Avoid breathing dust

P264 Wash hands, face and all exposed skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective clothing, gloves, eye/face protection and suitable dust mask as required

P101 If medical advice is needed, have product container or label at hand

P302+352 IF ON SKIN: Wash with soap and water

P362 Take off contaminated clothing and wash before reuse P332+313 If skin irritation occurs: Get medical advice/attention

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 1 of 8



P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do – continue rinsing

P310 Immediately call a POISON CENTRE or doctor/physician

P405 Store locked up

P403+233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents/container in accordance with local, regional, national and international

regulations

### Supplemental hazard information

This product does not contain more than 0.0002% soluble chromium (VI) of the total dry weight of the cement.

Other hazards: Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS No.	EC No.	REACH Reg. No.	Proportion (% w/w)	Classification
Portland cement	65997-15-1	266-043-4	02-2119682167-31	20 - 25	H315, H318, H335
Calcium diformate	544-17-2	208-863-7	01-2119486476-24	1.0 - 1.5	H318
Non-Hazardous	-	-	=	Balance	-

Classification in accordance to Regulation (EC) No. 1272/2008 (CLP).

#### 4. FIRST AID MEASURES

**Description of first aid measures:** If poisoning occurs, contact a doctor or the National Poisons Information Service (Phone 111) or Ambulance (Phone 999).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

**Skin contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

**Eye contact:** Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

**Ingestion:** Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

**Self-protection for the first aider:** Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If dust exists, wear dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Most important symptoms and effects, both acute and delayed:** Refer to Section 11 for Toxicological Information.

**Indication of any immediate medical attention and special treatment needed**: Treat symptomatically. Can cause corneal burns.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 2 of 8



### 5. FIRE-FIGHTING MEASURES

Hazchem code: Not applicable.

**Extinguishing media:** Not combustible, however, if material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder). Do not use water jets.

Specific hazards arising from the substance or mixture: Non-combustible material.

**Advice for firefighters:** On decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust.

**Environmental precautions:** Do not let product enter drains. If contamination of sewers or waterways has occurred advise local emergency services.

### Methods and material for containment and cleaning up

**Small spills:** Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

**Large spills:** Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

Reference to other sections: Refer to Section 13 for Disposal Considerations.

## 7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and inhalation of dust.

**Conditions for safety storage, including any incompatibilities**: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

**Specific end use**: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Ensure that eyewash stations and safety showers are close to the workstation location.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 3 of 8



### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

**Occupational exposure limits:** No Workplace Exposure Standard values have been assigned for this specific material by the Health and Safety Executive (HSE).

However, for:

	WES ppm	-TWA mg/m3	WES- ppm	STEL mg/m3	CARCINOGEN CATEGORY	NOTICES
Portland cement (Inhalable aerosol) Portland cement	-	10	-	-	-	-
(Respirable aerosol)	-	4	-	-	-	-

Assigned by United Kingdom.

As published by GESTIS International Limit Values (http://limitvalue.ifa.dguv.de/WebForm\_gw2.aspx).

WES-TWA (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

WES-STEL (Workplace Exposure Standard - Short-Term Exposure Limit). The 15-minute average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue changes, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological monitoring: No biological monitoring required.

#### **Exposure Controls**

**Engineering Controls:** Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards.

**Personal Protection Equipment:** VIOLET: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.

Personal protective equipment should be used only when other control measure (eg. elimination, substitution, isolation and engineering controls) have been found to be impractical or in conjunction with one or more control measures.

**Manufacturing, Packing and Transport:** Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If dust exists, wear dust mask/respirator meeting the requirements of HSE Respiratory Protective Equipment at Work HSGE53.

**Recommendations for consumer use:** Wear safety glasses and gloves. Avoid inhaling dust. Wash hands after use.

Environmental Exposure Controls: Keep containers closed when not in use.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 4 of 8



### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

**Appearance and odour:** Practically odourless, white to off-white powder.

**Solubility:** Practically insoluble in water.

**Bulk Density (20 ℃):** 1,300 kg/m<sup>3</sup>

Relative Vapour Density (air=1): >1 Vapour Pressure (20 ℃): N Av **Oxidising Properties:** N App Flash Point (℃): N App Flammability Limits (%): N App Autoignition Temperature (℃): N App **Explosive Properties:** N App Initial Boiling Point/Range (℃): N Av **Decomposition Point (℃):** N Av Melting Point/Freezing Point (℃): N Av

pH: 12 (5% Aqueous solution)

Viscosity:

Partition Coefficient:

Evaporation Rate (n-Butyl acetate=1):

N Av

Total VOC (g/Litre):

N Av

<

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

### 10. STABILITY AND REACTIVITY

Reactivity: Product cures on contact with water, releasing methanol and ethanol.

Chemical stability: This material is thermally stable when stored and used as directed.

**Possibility of hazardous reactions:** No known hazardous reactions.

Conditions to avoid: Elevated temperatures.

**Incompatible materials:** Incompatible with oxidising agents and acids.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

## Information on Toxicological Effects

**Inhalation:** Material is an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin will result in irritation. May cause skin sensitisation in sensitive individuals.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 5 of 8



#### **Acute toxicity**

**Inhalation:** Based on available data the classification criteria have not been met. This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >20 mg/L

**Skin contact:** Based on available data the classification criteria have not been met. This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Ingestion:** Based on available data the classification criteria have not been met. This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Corrosion/Irritancy:** Eye: Based on available data this material has been classified as a Category 1 Hazard (irreversible effects to eyes).

Skin: Based on available data this material has been classified as a Category 2 Hazard (irritant to skin).

**Sensitisation:** Inhalation: Based on available data this material has been classified as not a respiratory sensitiser.

Skin: Based on available data this material has been classified as not a skin sensitiser.

Aspiration hazard: Based on conclusive data this material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** Based on available data this material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

#### **Chronic Toxicity**

Mutagenicity: Based on available data this material has been classified as non-hazardous.

Carcinogenicity: Based on available data this material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): Based on available data this material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** Based on available data this material has been classified as non-hazardous.

#### 12. ECOLOGICAL INFORMATION

#### **Toxicity**

Acute: No information is available to complete an assessment.

**Chronic:** No information is available to complete an assessment.

**Persistence and degradability:** Controlled releases of minimal concentrations to adapted biological sewage plants, will not disturb the biodegradability of activated sludge.<sup>1</sup>

Bio-accumulative potential: No information available.

Mobility in soil: Low mobility in soil. Product cures on contact with air/water.

Results of PBT and vPvB assessment: A PBT/vPvB assessment is not required for this material.

Other adverse effects: No information available.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 6 of 8



## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods:** Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose of in accordance with the countries' Environmental Protection Authority.

#### 14. TRANSPORT INFORMATION

#### **Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of "The European Agreement Concerning the International Carriage of Dangerous Goods by Road (ADR)", "The Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID)" and "The European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways (ADN)".

## **Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

#### **Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Special Precautions for User: Not applicable.

Transport in Bulk according to Annex II MARPOL 73/78 and the IBC Code: Not applicable.

#### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture: This Safety Data Sheet has been written in accordance with Regulation (EC) No. 1272/2008 (CLP) and ECHA corresponding Guidance on the Classification, Labelling and Packaging of Substances and Mixtures (2015, Version 4,1)

All the constituents of this material are listed on the European Chemicals Agency C&L Inventory.

This material is not subject to the following international agreements

- Montreal Protocol (Ozone depleting substances)
- The Stockholm Convention (Persistent Organic Pollutants)
- The Rotterdam Convention (Prior Informed Consent)
- Basel Convention (Hazardous Waste)
- International Convention for the Prevention of Pollution from Ships (MARPOL)

**Chemical safety assessment:** No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 7 of 8



### **16. OTHER INFORMATION**

1. Supplier Safety Data Sheet. Proprietary Information, 2016.

Indications of changes: First Issue

#### Literatures sources and abbreviations

CLP Classification, Labelling and Packaging

EC European Commission

EC No. EINECS Number

ECHA European Chemicals Agency HSE Health and Safety Executive

H315 Causes skin irritation

H318 Causes serious eye damageH335 May cause respiratory irritation

PVT Persistent, Bioaccumulative and Toxic vPVB Very Persistent and very Bioaccumulative

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Craig and Rose Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

End of SDS.

Product name: Selleys Cracks Gone Outside Powder Filler SDS No: SELGBREN000578

Issued: 26 October 2018 Version: 1.0 Page: 8 of 8