

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: SELLEYS KITCHEN & BATHROOM NEUTRAL SILICONE SEALANT (CHINA)

Recommended Use: Silicone sealant.

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street,
Padstow, NSW 2211
Australia
Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825
Emergency Telephone: **1 800 033 111 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Risk Phrases: May cause sensitisation by skin contact.

Safety Phrases: Avoid contact with skin. Wear suitable protective clothing and gloves.

Poisons Schedule: None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS Number | Proportion | Risk Phrases |
|--|------------|------------|--------------|
| Oxime silane | 22984-54-9 | <10% | R36/38 R43 |
| Titanium dioxide | 13463-67-7 | <10% | - |
| Vinyltri (methylethylketoxime) silane | 2224-33-1 | <1% | - |
| Ingredients determined not to be hazardous | - | to 100% | - |

4. FIRST AID MEASURES

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact:

Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin). Remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Safety Data Sheet

**Ingestion:**

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.

Medical attention and special treatment:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Combustible paste. On burning will emit toxic fumes, including those of oxides of carbon and oxides of nitrogen .

Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

SMALL SPILLS: Wipe up with rag or absorbent paper. Any residual material can be cleaned up with mineral turpentine or similar hydrocarbon solvent, or acetone based nail polish remover.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

7. HANDLING AND STORAGE

Conditions for safe storage:

Keep containers closed when not in use - check regularly for leaks.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for substance liberated during application and cure:

Methyl ethyl ketoxime 8 hr TWA = 3 ppm; STEL = 10 ppm *

Safety Data Sheet



TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

*Supplier recommended.

Engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated areas. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been removed from fingertips, nails and cuticles. Always wash hands before smoking, eating, drinking or using the toilet. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

FOR CONSUMER USE: Avoid contact with eyes and skin. Use with adequate ventilation. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical state: | Paste |
| Colour: | Coloured / Translucent |
| Odour: | Mild |
| Solubility: | Insoluble in water. Uncured material is soluble in organic solvents. No solvent known for cured sealant. |
| Specific Gravity: | 1.04 @ 20°C |
| Relative Vapour Density (air=1): | Not available |
| Vapour Pressure (20 °C): | Not available |
| Flash Point (°C): | >63 |
| Flammability Limits (%): | Not available |
| Autoignition Temperature (°C): | 450 |
| % Volatile by Volume: | Not available |
| Solubility in water (g/L): | Insoluble |
| Melting Point/Range (°C): | Not applicable |
| Boiling Point/Range (°C): | Not available |
| Decomposition Point (°C): | Not available |
| pH: | Not applicable |
| Viscosity: | Not available |
| Evaporation Rate: | Not available |

Product Name: SELLEYS KITCHEN & BATHROOM NEUTRAL
SILICONE SEALANT (CHINA)
Substance No: 000000022875

Issued: 24/11/2011

Version: 1

10. STABILITY AND REACTIVITY

| | |
|--|---|
| Chemical stability: | Stable under normal conditions of use. |
| Conditions to avoid: | Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame. |
| Incompatible materials: | Incompatible with oxidising agents. |
| Hazardous decomposition products: | Oxides of carbon. Oxides of nitrogen. |
| Hazardous reactions: | Hazardous polymerisation will not occur. |

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

| | |
|---------------------------|--|
| Ingestion: | Swallowing may result in irritation to the mouth and throat. No adverse effects expected after swallowing cured (solvent free) sealant. |
| Eye contact: | May be an eye irritant. |
| Skin contact: | Repeated or prolonged skin contact may lead to irritation. Methyl ethyl ketoxime (liberated during application and setting) is a skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis in sensitive individuals. Cured sealant (solvent free) is not expected to be a skin irritant. |
| Inhalation: | Methyl ethyl ketoxime is liberated during application and setting. Material may be irritant to the mucous membranes of the respiratory tract (airways). |
| Long Term Effects: | No information available for the product. |

Toxicological Data: No LD50 data available for the product.

For methyl ethyl ketoxime:

Negative in IN VITRO and IN VIVO genotoxicity assays. Animal studies have shown that this chemical does not cause reproductive or developmental toxicity. Four week inhalation studies in the rat produced a NOEL (for CNS effects) of 714 ppm and NOEL (for blood effects) of 283 ppm. Lifetime inhalation studies in rats and mice have observed changes to liver and nasal tissue (degeneration of olfactory epithelium). Nasal tissue changes were concentration dependant.

12. ECOLOGICAL INFORMATION

| | |
|--------------------|--------------------------------|
| Ecotoxicity | Avoid contaminating waterways. |
|--------------------|--------------------------------|

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Normally suitable for disposal at approved land waste site.

Safety Data Sheet



14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

| | |
|--------------------------|---|
| Classification: | This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE. |
| Hazard Category: | Xi: Irritant |
| Risk Phrase(s): | R43: May cause sensitisation by skin contact. |
| Safety Phrase(s): | S24: Avoid contact with skin. S36/37: Wear suitable protective clothing and gloves. |
| Poisons Schedule: | None allocated. |

16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 0800 735 539 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

First Issue Primary SDS

Safety Data Sheet



This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.