

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: SELLEYS WALL PUTTY (SEA)

Recommended use of the chemical

Wall repair compound.

and restrictions on use:

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd

**ABN:** 67 000 049 427 **Street Address:** 1 Gow Street,

Padstow, NSW 2211

Australia

**Telephone Number:** +61 2 9781 8777 **Facsimile:** +61 2 9781 8825

Emergency Telephone: 1 800 033 111 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail: NON-DANGEROUS GOODS.

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule (SUSMP): None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Calcium carbonate	1317-65-3	10-60%	-
Synthetic polymer(s)	-	10-60%	-
Water	7732-18-5	10-60%	-
Ingredients determined not to be hazardous	-	to 100%	-

# 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

#### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

#### **Skin Contact:**

Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin). If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

#### **Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

#### Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

#### Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

Product Name: SELLEYS WALL PUTTY (SEA)

Substance No: 000000023724

Issued: 04/06/2013 Version: 1



## 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

### Specific hazards arising from the substance or mixture:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes, including those of oxides of carbon.

## Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Wash area down with excess water. Cured material can only be removed by cutting or abrasion.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling:

Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact.

#### Conditions for safe storage, including any incompatibilities:

Store in cool place and out of direct sunlight. Store away from incompatible materials described in Section 10. Protect from freezing. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia.

## Appropriate engineering controls:

Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green







Product Name: SELLEYS WALL PUTTY (SEA)

Substance No: 000000023724

Issued: 04/06/2013 Version: 1

Page 2 of 5



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: No special personal protective equipment required. Wash hands after use. Rubber gloves are recommended if handling often.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Colour: Off-white Odour: Characteristic Solubility: Dispersible in water. **Specific Gravity:** 1.5-1.8 @ 20°C Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): 3.2 kPa Flash Point (°C): Not applicable Flammability Limits (%): Not applicable Autoignition Temperature (°C): Not applicable

% Volatile by Weight: <55

Solubility in water (g/L):

Melting Point/Range (°C):

Boiling Point/Range (°C):

Decomposition Point (°C):

PH:

Viscosity:

Not available

Not available

Not available

Not available

Not available

## 10. STABILITY AND REACTIVITY

**Reactivity:** No information available.

**Chemical stability:** Stable under normal conditions of use.

**Possibility of hazardous reactions:** Reacts with acids liberating carbon dioxide.

Conditions to avoid: Avoid contact with acids .

**Incompatible materials:** Incompatible with acids and oxidising agents .

**Hazardous decomposition** 

Substance No: 000000023724

products:

Oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:**No adverse effects expected, however, large amounts may cause nausea and vomiting.

Swallowing calcium carbonate can result in the generation of uncomfortable quantities

of carbon dioxide gas in the stomach.

**Eye contact:** May be an eye irritant.

**Skin contact:** Repeated or prolonged skin contact may lead to irritation.

Product Name: SELLEYS WALL PUTTY (SEA) Issued: 04/06/2013

Version: 1



**Inhalation:** Not expected to cause respiratory irritation.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

#### Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

## 14. TRANSPORT INFORMATION

#### Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

#### **Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

#### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

#### Classification:

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule (SUSMP): None allocated.

## **16. OTHER INFORMATION**

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 0800 735 539 (New Zealand)
Fax: 0800 804 583 (New Zealand)

## Reason(s) for Issue:

First Issue Primary SDS

Product Name: SELLEYS WALL PUTTY (SEA) Issued: 04/06/2013

Substance No: 00000023724 Version: 1



This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Dulux Group owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.

Product Name: SELLEYS WALL PUTTY (SEA)

Substance No: 000000023724

Issued: 04/06/2013 Version: 1