

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/10/2015 Supersedes: 10/13/2015 Version: 2.1

### **SECTION 1: Identification**

1.1. Identification

Product name : Cheff-4
Product code : SG-1001-04180
Other means of identification : Hydrofluoroalkane

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

1.3. Details of the supplier of the safety data sheet

Air Liquide 9811 Katy Freeway, Suite 100 Houston, TX 77024 - USA T 1-800-819-1704 www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Liquefied gas H280 - Contains gas under pressure; may explode if heated

Full text of H-phrases: see section 16

#### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS04

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

OSHA-H01 - May displace oxygen and cause rapid suffocation

CGA-HG01 - May cause frostbite

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection, face protection, protective gloves, protective clothing

P302 - IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area, Get

immediate medical advice/attention

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P403 - Store in a well-ventilated place

P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-PG05 - Use a back flow preventive device in the piping CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure

CGA-PG14 - Approach suspected leak area with caution

CGA-PG21 - Open valve slowly

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

11/10/2015 EN (English US) Page 1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical

advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact : May cause frostbite.

Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite. Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous : Not known.

administration

Chronic symptoms : Adverse effects not expected from this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

### SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : The product is not flammable.

Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire

and increasing risk of burns and injuries.

Reactivity : None known.

#### 5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray

or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent

premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep

upwind.

### 6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area.

11/10/2015 EN (English US) 2/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.2. Environmental precautions

Try to stop release if safe to do so.

#### 6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

#### 6.4. Reference to other sections

See also Sections 8 and 13.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder

pressure. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or

in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in

use. Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products : None known.

Incompatible materials : Strong oxidizing agents.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Cheff-4		
ACGIH	ACGIH TWA (ppm)	1000 ppm Workplace Environmental Exposure Level (AIHA)

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local

exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit

system e.g. for maintenance activities.

Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : None necessary during normal and routine operations. See Sections 5 & 6.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Color : Colorless
Odor : Ethereal.

Odor threshold : No data available pH : No data available

Melting point : -103 °C

Freezing point : No data available

Boiling point : -1.4 °C Critical temperature : 124.9 °C

Flash point : Not applicable - not flammable

11/10/2015 EN (English US) 3/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : See Section 2.1 and 2.2
Explosion limits : Not applicable - not flammable
Explosive properties : Not applicable - not flammable.

Oxidizing properties : None.

Vapor pressure : 1956 mm Hg at 25 C : No data available Relative density Relative vapor density at 20 °C : No data available Specific gravity / density : 1.37 g/ml Molecular mass : Proprietary Relative gas density : Heavier than air Solubility : Water: 724 mg/l Log Pow No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

9.2. Other information

Gas group : Liquefied gas

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

None known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reacts exothermically with (some) metals. Potassium. Calcium. Magnesium. Powdered Aluminum. zinc.

### 10.4. Conditions to avoid

alkali metals. Alkaline earth metals. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

### 10.5. Incompatible materials

Strong oxidizing agents. Alkali metals. Alkaline metals.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Cheff-4	neff-4	
LC50 inhalation rat (ppm)	> 457000 ppm/4h	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: Not classified	
Specific target organ toxicity (repeated exposure)	: Not classified	
11/10/2015	EN (English US)	4/7

11/10/2015 EN (English US) 4/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact : May cause frostbite.

Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite. Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous : Not known.

administration

Chronic symptoms : Adverse effects not expected from this product.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Cheff-4		
LC50 fish 1	292 mg/l zebra fish - 96 hr	
LC50 other aquatic organisms 1	> 186 mg/l freshwater algae - 96 hr	
LC50 other aquatic organisms 2	299 mg/l daphnia magna - 48 hr	

#### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Cheff-4		
	Bioaccumulative potential	Bioaccumulation unlikely.

### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone depletion factor [R11=1] : 0

Effect on the global warming : Product is a greenhouse gas, and may contribute to global warming.

Global Warming Potential (CO2 = 1.0): 9.650

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its

accumulation could be dangerous. Ensure that the emission levels from local regulations or

operating permits are not exceeded.

Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more

guidance on suitable disposal methods.

### **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN3163 Liquefied gas, n.o.s. (Hydrofluoroalkane), 2.2

UN-No.(DOT) : UN3163

Proper Shipping Name (DOT) : Liquefied gas, n.o.s.

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

11/10/2015 EN (English US) 5/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** 

passenger vessel.

Other information : No supplementary information available.

**TDG** 

Transport document description : UN3163 Liquefied gas, n.o.s., 2.2

UN-No. (TDG) : UN3163

: Liquefied gas, n.o.s. TDG Proper Shipping Name

TDG Primary Hazard Classes : 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gas.

Transport by sea

UN-No. (IMDG) : UN3163

Proper Shipping Name (IMDG) : Liquefied gas, n.o.s.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : UN3163

: Liquefied gas, n.o.s Proper Shipping Name (IATA)

Class (IATA) : 2.2 - Gases : Non-flammable, non-toxic

#### SECTION 15: Regulatory information

### 15.1. US Federal regulations

No additional information available

### 15.2. International regulations

### **CANADA**

No additional information available

# **EU-Regulations**

No additional information available

### **National regulations**

No additional information available

#### 15.3. US State regulations

No additional information available

# **SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation

promulgated March 26, 2012.

Other information This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29

CFR, 1910.1200. Other government regulations must be reviewed for applicability to this

product.

#### Full text of H-phrases:

Liquefied gas	Gases under pressure Liquefied gas
H280	Contains gas under pressure; may explode if heated

SDS US (GHS HazCom 2012)

11/10/2015 EN (English US) 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

11/10/2015 EN (English US) 7/7