

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 08/07/2014 Date of issue: 08/07/2014

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

<u>Product Identifier</u> <u>Product Form:</u> Mixture

Product Name: Focus 0.5% Acid Alcohol

Product Code: SL88-1
Synonyms: Acid Rinse
Intended Use of the Product

Histology/Cytology General Use reagent. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

StatLab Medical Products 2090 Commerce Drive McKinney, TX 75069 800-442-3573

www.statlab.com

Emergency Telephone Number

Emergency number: CHEMTREC 800-424-9300 (USA & Canada)

CHEMTREC 703-527-3887 (International) Non-transport 800-225-8867 (USA)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flammable Liquid 2 H225 Eye Irritation 2A H319 Specific Target Organ Toxicity Single Exposure 1 H370

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)







Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation H370 - Causes damage to organs

Precautionary Statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe mist, spray, vapors.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

 $\ensuremath{\mathsf{P270}}$ - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, protective clothing, protective gloves.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

08/07/2014 EN (English US) 1/17

Version: 1.0

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO_2) for extinction.

P403+P235+P405 - Store in a well-ventilated place. Keep cool. Store locked up.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 2

H401 - Toxic to aquatic life

P273 - Avoid release to the environment

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Ethyl alcohol	(CAS No) 64-17-5	60	Flammable Liquid 2, H225
			Eye Irritation 2A, H319
			Aquatic Acute 2, H401
Isopropyl alcohol	(CAS No) 67-63-0	3	Flammable Liquid 2, H225
			Eye Irritation 2A, H319
			Specific Target Organ Toxicity Single Exposure 3, H336
Methyl alcohol	(CAS No) 67-56-1	3	Flammable Liquid 2, H225
			Acute Toxicity 3 (Oral), H301
			Acute Toxicity 3 (Dermal), H311
			Acute Toxicity 3 (Inhalation:vapor), H331
			Specific Target Organ Toxicity Single Exposure 1, H370
Hydrogen chloride	(CAS No) 7647-01-0	0.5	Corrosive to Metal 1, H290
			Acute Toxicity 3 (Inhalation:gas), H331
			Skin Corrosion 1A, H314
			Eye Damage 1, H318
			Specific Target Organ Toxicity Single Exposure 3, H335

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Assure fresh air breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes damage to organs. Causes serious eye irritation.

Inhalation: High concentration of vapors may induce: headache, dizziness, drowsiness, nausea and vomiting.

Skin Contact: Absorption through the skin may occur from direct contact.

Eye Contact: Causes serious eye irritation.

Ingestion: This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

08/07/2014 EN (English US) 2/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Powder, alcohol-resistant foam, water spray, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts violently with oxidants causing fire and explosion hazard.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or mist.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Histology/Cytology General Use reagent. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Methyl alcohol (67-56-1)		
Mexico	OEL TWA (mg/m³)	260 mg/m³
Mexico	OEL TWA (ppm)	200 ppm
Mexico	OEL STEL (mg/m³)	310 mg/m³
Mexico	OEL STEL (ppm)	250 ppm

08/07/2014 EN (English US) 3/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	250 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³	
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³	
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm	
USA IDLH	US IDLH (ppm)	6000 ppm	
Alberta	OEL STEL (mg/m³)	328 mg/m³	
Alberta	OEL STEL (ppm)	250 ppm	
Alberta	OEL TWA (mg/m³)	262 mg/m³	
Alberta	OEL TWA (ppm)	200 ppm	
British Columbia	OEL STEL (ppm)	250 ppm	
British Columbia	OEL TWA (ppm)	200 ppm	
Manitoba	OEL STEL (ppm)	250 ppm	
Manitoba	OEL TWA (ppm)	200 ppm	
New Brunswick	OEL STEL (mg/m³)	328 mg/m³	
New Brunswick	OEL STEL (ppm)	250 ppm	
New Brunswick	OEL TWA (mg/m³)	262 mg/m³	
New Brunswick	OEL TWA (ppm)	200 ppm	
Newfoundland & Labrador	OEL STEL (ppm)	250 ppm	
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm	
Nova Scotia	OEL STEL (ppm)	250 ppm	
Nova Scotia	OEL TWA (ppm)	200 ppm	
Nunavut	OEL STEL (mg/m³)	328 mg/m³	
Nunavut	OEL STEL (ppm)	250 ppm	
Nunavut	OEL TWA (mg/m³)	262 mg/m³	
Nunavut	OEL TWA (ppm)	200 ppm	
Northwest Territories	OEL STEL (mg/m³)	328 mg/m³	
Northwest Territories	OEL STEL (ppm)	250 ppm	
Northwest Territories	OEL TWA (mg/m³)	262 mg/m³	
Northwest Territories	OEL TWA (ppm)	200 ppm	
Ontario	OEL STEL (ppm)	250 ppm	
Ontario	OEL TWA (ppm)	200 ppm	
Prince Edward Island	OEL STEL (ppm)	250 ppm	
Prince Edward Island	OEL TWA (ppm)	200 ppm	
Québec	VECD (mg/m³)	328 mg/m³	
Québec	VECD (ppm)	250 ppm	
Québec	VEMP (mg/m³)	262 mg/m³	
Québec	VEMP (ppm)	200 ppm	
Saskatchewan	OEL STEL (ppm)	250 ppm	
Saskatchewan	OEL TWA (ppm)	200 ppm	
Yukon	OEL STEL (mg/m³)	310 mg/m ³	
Yukon	OEL STEL (ppm)	250 ppm	
Yukon	OEL TWA (mg/m³)	260 mg/m³	
Yukon	OEL TWA (mg/m /	200 ppm	
Ethyl alcohol (64-17-5)	· · · · · /bk· · · ·	1 kk,	
Mexico			
Mexico	OEL TWA (IIIg/III) OEL TWA (ppm)	1000 ppm	
IVICALCO	OLL IVVA (PPIII)	τοσο μλιιι	

08/07/2014 EN (English US) 4/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
USA NIOSH	NIOSH REL (TWA) (Hig/Hi) NIOSH REL (TWA) (ppm)	1000 mg/m 1000 ppm
USA IDLH	, , , , ,	3300 ppm (10% LEL)
Alberta	US IDLH (ppm) OEL TWA (mg/m³)	1880 mg/m³
Alberta		1000 mg/m 1000 ppm
	OEL TWA (ppm) OEL STEL (ppm)	• •
British Columbia	11.1 /	1000 ppm
Manitoba	OEL STEL (ppm)	1000 ppm
New Brunswick	OEL TWA (mg/m³)	1880 mg/m³
New Brunswick	OEL TWA (ppm)	1000 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm
Nova Scotia	OEL STEL (ppm)	1000 ppm
Nunavut	OEL STEL (mg/m³)	2355 mg/m³
Nunavut	OEL STEL (ppm)	1250 ppm
Nunavut	OEL TWA (mg/m³)	1884 mg/m³
Nunavut	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (mg/m³)	2355 mg/m³
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (mg/m³)	1884 mg/m³
Northwest Territories	OEL TWA (ppm)	1000 ppm
Ontario	OEL STEL (ppm)	1000 ppm
Prince Edward Island	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m³)	1880 mg/m³
Québec	VEMP (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Yukon	OEL STEL (mg/m³)	1900 mg/m³
Yukon	OEL STEL (ppm)	1000 ppm
Yukon	OEL TWA (mg/m³)	1900 mg/m³
Yukon	OEL TWA (ppm)	1000 ppm
Isopropyl alcohol (67-63-0)		
Mexico	OEL TWA (mg/m³)	980 mg/m³
Mexico	OEL TWA (ppm)	400 ppm
Mexico	OEL STEL (mg/m³)	1225 mg/m³
Mexico	OEL STEL (ppm)	500 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Alberta	OEL STEL (mg/m³)	984 mg/m³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m³)	492 mg/m³
Alberta	OEL TWA (mg/m)	200 ppm
Alberta	OLL IVVA (PPIII)	200 ppm

08/07/2014 EN (English US) 5/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	7, 140. 30 / 141011ddy, 141d1c11 20, 2012 / 14d1c3 d11d 11cg	
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	1230 mg/m³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (mg/m³)	983 mg/m³
New Brunswick	OEL TWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m³)	1228 mg/m³
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (mg/m³)	983 mg/m³
Nunavut	OEL TWA (ppm)	400 ppm
Northwest Territories	OEL STEL (mg/m³)	1228 mg/m³
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OEL TWA (mg/m³)	983 mg/m³
Northwest Territories	OEL TWA (ppm)	400 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m³)	1230 mg/m³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m³)	985 mg/m³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m³)	1225 mg/m³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m³)	980 mg/m³
Yukon	OEL TWA (ppm)	400 ppm
Hydrogen chloride (7647-01		100 pp.m
Mexico	OEL Ceiling (mg/m³)	7 mg/m³
Mexico	OEL Ceiling (mg/m)	<u> </u>
USA ACGIH	ACGIH Ceiling (ppm)	5 ppm 2 ppm
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	7 mg/m ³
USA OSHA	OSHA PEL (Ceiling) (Ing/In-)	5 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	7 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m²) NIOSH REL (ceiling) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Alberta	OEL Ceiling (mg/m³)	3 mg/m ³
Alberta	OEL Coiling (ppm)	2 ppm
British Columbia	OEL Ceiling (ppm)	2 ppm
Manitoba	OEL Ceiling (ppm)	2 ppm
New Brunswick	OEL Ceiling (mg/m³)	7.5 mg/m³
New Brunswick	OEL Ceiling (ppm)	5 ppm
Newfoundland & Labrador	OEL Ceiling (ppm)	2 ppm
Nova Scotia	OEL Ceiling (ppm)	2 ppm

08/07/2014 EN (English US) 6/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nunavut	OEL Ceiling (mg/m³)	7.5 mg/m³	
Nunavut	OEL Ceiling (ppm)	5 ppm	
Northwest Territories	OEL Ceiling (mg/m³)	7.5 mg/m ³	
Northwest Territories	OEL Ceiling (ppm)	5 ppm	
Ontario	OEL Ceiling (ppm)	2 ppm	
Prince Edward Island	OEL Ceiling (ppm)	2 ppm	
Québec	PLAFOND (mg/m³)	7.5 mg/m ³	
Québec	PLAFOND (ppm)	5 ppm	
Saskatchewan	OEL Ceiling (ppm)	2 ppm	
Yukon	OEL Ceiling (mg/m³)	7 mg/m³	
Yukon	OEL Ceiling (ppm)	5 ppm	

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

Personal Protective Equipment: Full protective flameproof clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist

are expected to exceed exposure limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance : Clear, colorless liquid

Odor Threshold : Pungent : Not available

pH : 1.5 - 2

Relative Evaporation Rate (butylacetate=1) Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** 79 °C (174.2 °F) **Flash Point** 20 °C (68 °F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Not available Flammability (solid, gas) **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available Relative Vapor Density at 20 °C Not available

Relative Density: 0.8 - 0.9 (water = 1)Specific Gravity: Not availableSolubility: Soluble in water.

08/07/2014 EN (English US) 7/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Pow:Not availableLog Kow:Not availableViscosity, Kinematic:Not availableViscosity, Dynamic:Not availableExplosion Data – Sensitivity to Mechanical Impact:Not availableExplosion Data – Sensitivity to Static Discharge:Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts violently with oxidants causing fire and explosion hazard.

Chemical Stability: Flammable liquid and vapor.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Ignition sources.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. **Hazardous Decomposition Products:** Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Causes damage to organs.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: High concentration of vapors may induce: headache, dizziness, drowsiness, nausea and

vomiting.

Symptoms/Injuries After Skin Contact: Absorption through the skin may occur from direct contact.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity

ranging from diminished visual capacity to complete blindness, and possible death.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Methyl alcohol (67-56-1)		
ATE (oral)	100.000 mg/kg body weight	
ATE (dermal)	300.000 mg/kg body weight	
ATE (vapors)	3.000 mg/l/4h	
Ethyl alcohol (64-17-5)		
LC50 Inhalation Rat (mg/l)	124.7 mg/l/4h	
ATE (dust, mist)	124.700 mg/l/4h	
Isopropyl alcohol (67-63-0)		
LD50 Oral Rat	4396 mg/kg	
LD50 Dermal Rabbit	12800 mg/kg	
LC50 Inhalation Rat (ppm)	16000 ppm (Exposure time: 8 h)	
ATE (oral)	4396.000 mg/kg body weight	
ATE (dermal)	12800.000 mg/kg body weight	

08/07/2014 EN (English US) 8/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen chloride (7647-01-0)		
LD50 Oral Rat	700 mg/kg	
LD50 Dermal Rabbit	> 5010 mg/kg	
LC50 Inhalation Rat (ppm)	781 ppm/4h (reported as 3124 ppm/1 h)	
ATE (oral)	700.000 mg/kg body weight	
ATE (gases)	781.000 ppmV/4h	
Isopropyl alcohol (67-63-0)		
IARC Group	3	
Hydrogen chloride (7647-01-0)		
IARC Group	3	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - Water: Readily bioldegrades. Evaporates to moderate extent. Does not bioaccumulate.

Methyl alcohol (67-56-1)		
LC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
Ethyl alcohol (64-17-5)		
LC50 Fish 1	9.468 (9.468 - 12.624) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) converted from ml/l	
EC50 Daphnia 1	9268 (9268 - 14221) mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC 50 Fish 2	100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
Isopropyl alcohol (67-63-0)		
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)	
LC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	

Persistence and Degradability

r crosscence and begradability	
Focus 0.5% Acid Alcohol	
Persistence and Degradability	The substance is biodegradable. Unlikely to persist.
Ethyl alcohol (64-17-5)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Focus 0.5% Acid Alcohol		
Bioaccumulative Potential	Not expected to bioaccumulate.	
Methyl alcohol (67-56-1)		
BCF fish 1	< 10	
Log Pow	-0.77	
Ethyl alcohol (64-17-5)		
Log Pow	-0.32	
Bioaccumulative Potential	Not established.	
Isopropyl alcohol (67-63-0)		
Log Pow	0.05 (at 25 °C)	

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

08/07/2014 EN (English US) 9/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number
UN-No.(DOT): 1987
DOT NA no.: UN1987

UN Proper Shipping Name

DOT Proper Shipping Name : Alcohols, n.o.s.

Transport Document Description : UN1987 Alcohols, n.o.s., 3, II

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard Labels (DOT) : 3 - Flammable liquid



Packing Group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 172 - This entry includes alcohol mixtures containing up to 5% petroleum

products.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than $0 \, \text{C}$ (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

Additional Information

Emergency Response Guide (ERG) Number : 127

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on

a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in

paragraph (k)(2)(i) of this section is exceeded.

MFAG-No : 127

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : 60 L

08/07/2014 EN (English US) 10/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: REGULATORY INFORMATION				
US Federal Regulations				
Focus 0.5% Acid Alcohol				
SARA Section 311/312 Hazard Classes Fire hazard				
·	Immediate (acute) health hazard			
Methyl alcohol (67-56-1)				
Listed on the United States TSCA (Toxic S	ubstances Control Act)	inventory		
Listed on SARA Section 313 (Specific toxic				
SARA Section 311/312 Hazard Classes	Delayed (chronic) hea	olth hazard		
, , , , , , , , , , , , , , , , , , , ,	Immediate (acute) he			
	Fire hazard			
SARA Section 313 - Emission Reporting	1.0 %			
Ethyl alcohol (64-17-5)				
Listed on the United States TSCA (Toxic S	ubstances Control Act)	inventory		
Isopropyl alcohol (67-63-0)	<u> </u>	,		
Listed on the United States TSCA (Toxic S	ubstances Control Act)	inventory		
Listed on SARA Section 313 (Specific toxic		,		
EPA TSCA Regulatory Flag	T .	stance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting		ctured by the strong acid process, no supplier notification)		
Hydrogen chloride (7647-01-0)	, ,	, 3 1 , 11		
Listed on the United States TSCA (Toxic S	uhstances Control Δct)	inventory		
Listed on SARA Section 302 (Specific toxic		inventory		
Listed on SARA Section 313 (Specific toxic				
SARA Section 302 Threshold Planning Qu		500 (gas only)		
SARA Section 313 - Emission Reporting	auticity (11 Q)	1.0 % (acid aerosols including mists, vapors, gas, fog, and other		
		airborne forms of any particle size)		
US State Regulations		, , , , ,		
Methyl alcohol (67-56-1)				
U.S California - Proposition 65 - Develo	opmental Toxicity	WARNING: This product contains chemicals known to the State of		
	.,	California to cause birth defects.		
Ethyl alcohol (64-17-5)				
U.S California - Proposition 65 - Carcin	WARNING: This product contains chemicals known to the State of			
	- 6	California to cause cancer.		
U.S California - Proposition 65 - Develo	pmental Toxicity	WARNING: This product contains chemicals known to the State of		
·		California to cause birth defects.		
Methyl alcohol (67-56-1)				
U.S California - Proposition 65 - Maximo	um Allowable Dose Lev	els (MADL)		
U.S California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute				
U.S California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic				
U.S California - Toxic Air Contaminant List (AB 1807, AB 2728)				
U.S Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues				
U.S Connecticut - Hazardous Air Pollutants - HLVs (30 min)				
U.S Connecticut - Hazardous Air Pollutants - HLVs (8 hr)				
U.S Connecticut - Volatile Substances				
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities				
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations				
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)				
U.S Idaho - Occupational Exposure Limits - TWAs				
	U.S Illinois - Toxic Air Contaminants			
U.S Louisiana - Reportable Quantity List for Pollutants				

08/07/2014 EN (English US) 11/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Maine Air Pollutants Hazardous Air Pollutants
- U.S. Maine Chemicals of High Concern
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Skin Designations
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Groundwater Health Risk Limits
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Skin Designations
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey Water Quality Ground Water Quality Criteria
- U.S. New Jersey Water Quality Practical Quantitation Levels (PQLs)
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. North Dakota Hazardous Wastes Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits Skin Designations
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Skin Designations
- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Dangerous Waste Discarded Chemical Products List
- U.S. Washington Permissible Exposure Limits Skin Designations
- U.S. Washington Permissible Exposure Limits STELs

08/07/2014 EN (English US) 12/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Washington - Permissible Exposure Limits - TWAs

Ethyl alcohol (64-17-5)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Maine Chemicals of High Concern
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Isopropyl alcohol (67-63-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Connecticut Volatile Substances
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs

08/07/2014 EN (English US) 13/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

Hydrogen chloride (7647-01-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Accidental Release Prevention Regulations Sufficient Quantities
- U.S. Delaware Accidental Release Prevention Regulations Threshold Quantities
- U.S. Delaware Accidental Release Prevention Regulations Toxic Endpoints
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Florida Essential Chemicals List
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits Ceilings
- U.S. Illinois Toxic Air Contaminants
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Maine Air Pollutants Hazardous Air Pollutants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Ceilings
- U.S. Michigan Polluting Materials List
- U.S. Michigan Process Safety Management Highly Hazardous Chemicals

08/07/2014 EN (English US) 14/17


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Ceilings
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey TCPA Extraordinarily Hazardous Substances (EHS)
- U.S. New York Occupational Exposure Limits Ceilings
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Carolina Control of Toxic Air Pollutants
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Ohio Accidental Release Prevention Threshold Quantities
- U.S. Ohio Extremely Hazardous Substances Threshold Quantities
- U.S. Oregon Permissible Exposure Limits Ceilings
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits Ceilings
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Ceilings
- U.S. Washington Permissible Exposure Limits Ceilings
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet
- U.S. Wyoming Process Safety Management Highly Hazardous Chemicals

Canadian Regulations

WHMIS Classification Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification Class B Division 2 - Flammable Liquid

Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

08/07/2014 EN (English US) 15/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on the Canadian Ingredient Disclosure List		
WHMIS Classification	Class B Division 2 - Flammable Liquid	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Isopropyl alcohol (67-63-0)		
Listed on the Canadian DSL	(Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List		
WHMIS Classification	Class B Division 2 - Flammable Liquid	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Hydrogen chloride (7647-0	L-O)	
Listed on the Canadian DSL (Domestic Substances List) inventory.		
Listed on the Canadian Ingr	edient Disclosure List	
WHMIS Classification	Class A - Compressed Gas	
	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects	
	Class E - Corrosive Material	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Revision date : 08/07/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Toxicity 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Toxicity 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Toxicity 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Toxicity 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Eye Damage 1	Serious eye damage/eye irritation Category 1
Eye Irritation 2A	Serious eye damage/eye irritation Category 2A
Flammable Liquid 2	Flammable liquids Category 2
Corrosive to Metal 1	Corrosive to metals Category 1
Skin Corrosion 1A	Skin corrosion/irritation Category 1A
Specific Target Organ Toxicity Single Exposure 1	Specific target organ toxicity (single exposure) Category 1
Specific Target Organ Toxicity Single Exposure 3	Specific target organ toxicity (single exposure) Category 3
Specific Target Organ Toxicity Single Exposure 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H290	May be corrosive to metals
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H401	Toxic to aquatic life

08/07/2014 EN (English US) 16/17

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA Health Hazard

NFPA Fire Hazard : 3 - Liquids and solids that can be ignited under almost all ambient

conditions.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not

reactive with water.

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur


Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard



StatLab Medical Products Phone Number: 800-442-3573

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS



08/07/2014 EN (English US) 17/17