

## 20 MINUTE ACRYLIC LIQUID

### Section I - Product and Company Identification

**Product Name:** SLEDGEHAMMER 20 MINUTE DENTAL ACRYLIC MONOMER  
**Chemical Name:** NA

**Family:** Monomer

**Manufacturer:** KEYSTONE RESEARCH & PHARMACEUTICAL  
 616 Hollywood Avenue  
 Cherry Hill, NJ 08002

**Product Use:** Dental Monomer  
**Formula:** Proprietary Formulation

**Emergency Phone Numbers:** ( 800 ) 535 - 5053  
**Information Contacts:** ( 856 ) 663 - 4700

### Section II - Hazardous Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL		
Methyl Methacrylate	80-62-6	201-297-1	N/E	100ppm	100ppm	3/none/none	90-95
Ethylene Glycol Dimethacrylate Esters	97-90-5	202-617-2	Glycol HEMA-Methacrylate	N/E	N/E	Not Listed	5-10
N,N-Dimethyl-p-toluidine	99-97-8	202-805-4	Dimethyltolylamine	N/E	N/E	Not Listed	0-1
Inhibitor (MEHQ)	150-76-5	205-769-8	p-Hydroxyanisole	5 mg/m3	5 mg/m3	Not Listed	0-0.5
N/E - None Established	N/DA - No Data Available						
N/R - Not Reviewed	N/A - Not Applicable						

### Section III - Hazards Identification

#### EMERGENCY OVERVIEW

- May cause allergic skin reaction and eye irritation.
- Flammable liquid and vapor.
- Hazardous polymerization may occur.
- May cause respiratory irritation.

#### Potential Health Effects, Signs and Symptoms of Exposure:

**Primary Route of Entry:** Inhalation, eyes & skin.  
**Eye:** Vapor concentration may cause irritation of eyes. Liquid contact with eyes can cause irritation and possible corneal damage.  
**Skin:** Liquid concentration may cause moderate skin irritation. Repeated or prolonged contact may cause allergic skin rashes, itching and swelling  
**Ingestion:** Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.  
**Inhalation:** High vapor concentrations may irritate the respiratory system. Prolonged exposure can lead to headaches, nausea, drowsiness and unconsciousness.  
**Sub-Chronic Effects:** Prolonged and / or repeated exposure may lead to kidney, lung, liver and heart damage. Unlikely to present a cancer hazard to man.

NOTE: Refer to Section 11, Toxicological Information for Details

### Section IV - First Aid Measures

**First Aid for Eye:** Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.  
**First Aid for Skin:** Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.  
**First Aid for Inhalation:** Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give artificial respiration. Get medical help if discomfort persists.  
**First Aid for Ingestion:** If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Seek medical attention if symptoms persist.

## 20 MINUTE ACRYLIC LIQUID

### Section V - Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
TAG Closed: 68 F	LEL : 2% ; UEL : 12.5%	421 deg C

Method:

- Extinguishing Media: Foam, carbon dioxide, dry chemical or carbon tetrachloride.
- Fire Fighting Instructions: Wear self-contained breathing apparatus and full protective gear. Water may be ineffective unless used as a fine spray or fog. Use water spray to cool the exposed containers of methyl methacrylate.
- Unusual Hazards: Vapors may travel to source ignition or excessive temperatures. Heat can induce polymerization with rapid release of energy. Closed containers may rupture explosively. Spontaneous polymerization may occur on prolonged aging. Explosive mixtures may occur at temperatures at or above the flashpoint.

### Section VI - Accidental Release Measures

- Spill or Release Procedures -
- Evacuate area and eliminate all possible sources of ignition. Use self contained breathing apparatus and protective clothing. Dike and absorb with inert materials (sand, soda, ash, vermiculite, etc) and then transfer to proper containers for disposal, using non-sparking tools. Keep spills out of sewers and open bodies of water. Remove saturated clothing and wash affected skin areas with soap and water.

### Section VII - Handling and Storage

- Handling
- Keep away from heat, sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. Ground all metal containers when transferring and use explosion-proof equipment. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.
- Storage
- Store in a cool dry place, at ambient temperatures out of direct sunlight. Keep containers closed and away from heat.
- Explosion Hazard
- Keep away from sparks and open flame. Closed containers may rupture explosively. Spontaneous polymerization may occur on prolonged aging.

### Section VIII - Exposure Controls / Personal Protective Equipment

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation with a minimum capture velocity of 100 ft/min at the point of monomer release. Refer to "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygiene.

Personal Protective Equipment  
General

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection

Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying material.

Skin Protection

Use impermeable gloves to minimize skin contact.

Respiratory Protection

Use self-contained breathing apparatus when needed. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

## 20 MINUTE ACRYLIC LIQUID

### Section IX - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	% Volatile
Clear, colorless liquid	Characteristic strong, acrid odor	NA	(H2O=1): 0.94	NA	W/W%: 99+

  

Boiling / Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water
214°F	NA	Log Po/w NA	(mm of Hg) 29 @ 25°C	(Air=1) 3.45	(Bu Ac=1) 1.5	NA	(20°C) 1% to 10%

### Section X - Stability and Reactivity

**Stability:**

Stable under normal storage conditions.

**Hazardous Decomposition Products:**

Acid fumes, CO and carbon dioxide

**Conditions to Avoid:**

Elevated temperatures, ignition sources, aging and contamination.

**Incompatibility (Materials to Avoid):**

Reducing/ oxidizing agents and UV light

**Hazardous Polymerization:**

May occur

### Section XI - Toxicological Information

**Acute Oral Toxicity**

Oral(Rat) LD50: 7872 mg/kg

**Acute Dermal Toxicity**

Dermal (Rabbit) LD50: 9400mg/kg

**Acute Inhalation Toxicity**

Inhalation (Rat) LC50 3750ppm

**Irritation - skin**

skin irritant

**Irritation - Eye**

moderate eye irritant

**Sensitization**

skin sensitizer in animals

**Mutagenicity**

N/DA

**Sub-chronic Toxicity**

N/DA

### Section XII - Ecological Information

**Ecotoxicological Information**

**Acute Toxicity to Fish**

96 hour LC50:  
fathead minnows: 150 ppm  
bluegill sunfish; 232 ppm

**Acute Toxicity to Invertebrates**

N/DA

**Acute Toxicity to Algae**

N/DA

**Bioconcentration**

N/DA

**Toxicity to Sewage Bacteria**

N/DA

**Chemical Fate Information**

**Biodegradability**

**Chemical Oxygen Demand**

Partially biodegradable in water.

(BOD 5 day) : 0.14g/g - 0.90g/g ; Theoretical Oxygen Demand : 1.92g/g

### Section XIII - Disposable Concentrations

- After the addition of excess inhibitor, incinerate the liquid and diking materials in accordance with federal, state and local regulations. Do not incinerate in closed containers. Biodegradation is also possible. Empty containers must be handled with care due to product residue. DO NOT HEAT OR CUT THE EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.

### Section XIV - Transport Information

- DOT/UN Shipping Name: Flammable Liquid, n.o.s., Class 3, UN 1993
- RQ (Lbs): 1000

### Section XV - Regulatory Information

**US Federal Regulations**

Clean Air Act: HAP

Clean Air Act: ODS

This product contains hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act . Methyl Methacrylate CASRN : 80626

This product neither contains, nor was manufactured with a Class I or Class II ozone depleting substance(ODS).

## 20 MINUTE ACRYLIC LIQUID

### Section XV - Regulatory Information Continued

#### US Federal Regulations:

Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the USA Clean Water Act Priority Pollutant List.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/ or other applications as an indirect food additive.
Occupational Safety and Health Act RCRA	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazard are: Immediate (acute) health hazard, Fire hazard, Reactive hazard This product is considered to be a hazardous waste under RCRA ( 40 CFR 261 ) : RCRA Code : U162
SARA Title III: Section 302	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification (" CERCLA " List) : Methyl Methacrylate CASRN : 80 - 62 - 6 RQ (Lbs) : 1000
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazard are : Immediate ( acute ) health hazard, Fire hazard, Reactive hazard
SARA Title III: Section 313:	This product contains chemicals regulated as Toxic Chemical under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 : Methyl Methacrylate : CASRN : 80 - 62 - 6
TSCA Section 8(b): Inventory:	This product or its components are listed in or exempt from the TSCA inventory requirements.
TSCA Section 12(b): Export Notification:	This product contains no substances subject to export notification under Section 12 (b) of TSCA.

#### State Regulations

CA Proposition 65	Chemical Name: This product contains no hazardous substances known to the State of California to cause cancer and adverse reproductive effects. CASRN: N/A % Composition: N/A
MA Right-to-Know Law:	Chemical Name: This product contains the following substance on the Massachusetts Substance List : Methyl Methacrylate CASRN: 80 - 62 - 6 % Composition
NJ Right-to-Know Law:	Chemical Name: This product contains the following substance on the New Jersey Substance List : Methyl Methacrylate CASRN: 80 - 62 - 6 % Composition
PA Right-to-Know Law:	Chemical Name: This product contains no hazardous substances on the Pennsylvania Substance List. CASRN: N/A % Composition: N/A

#### International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	MEHQ CAS #150-76-5 is on the DSL list. WHMIS = n/da MMA CAS # is on the DSL list. WHMIS = B2, D2B N,N,-Dimethyl-p-toluidine: DSL regulatory status: Included, WHMIS: None
EINECS: European Inventory:	Chemical Name: Methyl Methacrylate CASRN: 80-62-6
MITI: Japanese Inventory:	Chemical Name: CASRN:

### Section XVI - Other Information

Hazard Rating System	NFPA: Health = 2/Flammability = 3/Reactivity = 2 HMIS: Health = 2/Flammability/ = 3/Reactivity = 2
Product Number - Revised Sections since Last Version:	Section 2 and 15 revised on 07/07/06

Approval Date: 07/07/06  
Supersedes Date:

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800)535-5053.