

 Product name:
 SPECIFIX RESIN
 Page:
 1/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name: SPECIFIX RESIN

Cat. No. 40200051, 40200048, 40200049

Container size: 1 l

Relevant identified uses of the substance or mixture and uses advised against

Application: For embedding and impregnation of materialographic specimens

Details of the supplier of the safety data sheet

Supplier: Struers A/S

Pederstrupvej 84 DK-2750 Ballerup Tel:+45 44 600 800

Responsible for material Responsible for material safety data sheet authoring: DHI

safety data sheet authoring: Any questions to the contents of this material safety data sheet should be sent to:

Chemical.info@struers.dk

Emergency telephone number

Emergency telephone: Infotrac:

1-800-535-5053 Struers US: 1-440-871-0071

 Product name:
 SPECIFIX RESIN
 Page:
 2/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

## **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

The product is classified:

67/548/EEC / 1999/45/EC: R43 Xi;R36/38 N;R51/53

GHS: Skin Irrit. 2;H315 - Eye Irrit. 2;H319 - Skin Sens. 1;H317 - Aquatic Chronic 2;H411

**Label elements** 



Warning

<u>Contains:</u> Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average

molecular weight <= 700)

Reaction product: bisphenol-F-glycidyl ether, Epoxy resin (number average

molecular weight < 700) 1,6-Hexandiol-diglycidylether

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

P273 Avoid release to the environment.

P280 Wear protective clothing, gloves, eye and face protection.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

NFPA Rating: Health:2 Fire:1 Reactivity:0 Other:-

Other hazards

PBT/vPvB: Not relevant.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### **Mixtures**

The product contains: epoxy resin and additives.

 Product name:
 SPECIFIX RESIN
 Page:
 3/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

^-	,,,,,	0		-	
nı	1/54	ᅜᄶ	_	⊢(.	

67/548/EEC:							
	<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
	30-60	25068-38-6	500-033-5	01-2119456619- 26-xxxx	Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight <= 700)	R43 Xi;R36/38 N;R51-53	
	10-30	28064-14-4	-	-	Reaction product: bisphenol-F-glycidyl ether, Epoxy resin (number average molecular weight < 700)	R43 Xi;R36/38 N;R51-53	
	10-30	16096-31-4	240-260-4	-	1,6-Hexandiol-diglycidylether	R43 Xi;R36/38 R52-53	
	0,1-<1	4420-74-0	224-588-5	-	3-Trimethoxysilylpropane-1 -thiol	Xn;R21/22 N;R51-53	
	GHS:						
	<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
	30-60	25068-38-6	500-033-5	01-2119456619- 26-xxxx	Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight <= 700)	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	
	10-30	28064-14-4	-	-	Reaction product: bisphenol-F-glycidyl ether, Epoxy resin (number average molecular weight < 700)	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	
	10-30	16096-31-4	240-260-4	-	1,6-Hexandiol-diglycidylether	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 3;H412	
	0,1-<1	4420-74-0	224-588-5	-	3-Trimethoxysilylpropane-1 -thiol	Acute Tox. 4;H312 Acute Tox. 4;H302	

References: The full text for all R-phrases and hazard statements are displayed in section 16.

Aquatic Chronic 2;H411

 Product name:
 SPECIFIX RESIN
 Page:
 4/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

#### **SECTION 4: FIRST AID MEASURES**

#### **Description of first aid measures**

Inhalation: Move injured person into fresh air and keep person calm under observation. If

uncomfortable: Seek hospital and bring these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water.

In case of eczema or other skin disorders: Seek medical attention and bring

these instructions.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact

lenses and open eyelids widely. If irritation persists: Continue flushing during

transport to hospital. Bring along these instructions.

Immediately rinse mouth and drink plenty of water. Keep person under

observation. If person becomes uncomfortable seek hospital and bring these

instructions. Do not induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

#### Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Not known.

## **SECTION 5: FIREFIGHTING MEASURES**

#### Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog.

## Special hazards arising from the substance or mixture

<u>Specific hazards:</u> When heated and in case of fire, irritating vapors/gases may be formed.

**Advice for firefighters** 

Protective equipment for Selection of respiratory protection for fire fighting: follow the general fire

<u>fire-fighters:</u> precautions indicated in the workplace.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

<u>Personal precautions:</u> Avoid contact with skin and eyes.

**Environmental precautions** 

<u>Environmental</u> Do not discharge into drains, water courses or onto the ground.

precautions:

#### Methods and material for containment and cleaning up

<u>Spill Cleanup Methods:</u> Absorb spillage with suitable absorbent material.

Reference to other sections

References: For personal protection, see section 8. For waste disposal, see section 13.

 Product name:
 SPECIFIX RESIN
 Page:
 5/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

#### **SECTION 7: HANDLING AND STORAGE**

#### Precautions for safe handling

Safe handling advice: Avoid contact with skin and eyes. Good personal hygiene is necessary. Wash

hands and contaminated areas with water and soap before leaving the work site.

Observe good chemical hygiene practices.

<u>Technical measures:</u> Work practice should minimize contact. Technical aids: Use disposable

equipment (rags, brushes, spatulas, putty knives, etc.), if possible.

<u>Technical precautions:</u> First-aid equipment, including eye wash bottle, must be available at the work site.

## Conditions for safe storage, including any incompatibilities

<u>Technical measures for safe</u> No special precautions.

storage:

Storage conditions: Store in closed original container in a dry place. Avoid contact with oxidizing

agents.

Specific end use(s)

Specific use(s): Not relevant.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

No occupational exposure limit assigned.

#### Exposure controls

Engineering measures: Mix and prepare in a place with efficient exhaust ventilation. An eye wash

bottle must be available at the work site.

<u>Personal protection:</u> Personal protection equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment.

Respiratory equipment: In case of inadequate ventilation, use air-supplied full-mask.

<u>Hand protection:</u> Wear protective gloves. Neoprene gloves are recommended. The most

suitable glove must be chosen in consultation with the gloves supplier, who

can inform about the breakthrough time of the glove material.

Eye protection: Wear goggles/face shield.

Skin protection: Wear apron or protective clothing in case of contact.

<u>Hygiene measures:</u> Remove contaminated clothing and wash the skin thoroughly with soap and

water after work. When using do not eat, drink or smoke.

**Environmental Exposure** 

Controls:

Not available.

 Product name:
 SPECIFIX RESIN
 Page:
 6/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

<u>Appearance:</u> Colorless-pale yellow liquid.

Odor:slight odorpH:Not available.Boiling point:Not available.

Flash point: 149°C

Explosion limits: Not available.

Vapor pressure: <0,01 Pa

Relative density: 1,15

Solubility: Not available.

Other information

Other data: Volatile Organic Compound (VOC): 0 g/l

#### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity

Reactivity: None known.

**Chemical stability** 

Stable under normal temperature conditions.

Curing time:

SPECIFIX-20: 8 hours

SPECIFIX-40: 3.5 hours (40-60 °C)

Possibility of hazardous reactions

<u>Hazardous Reactions:</u> None known.

Conditions to avoid

<u>Conditions/materials to avoid:</u> Heating. Strong oxidizing substances, strong acids and strong bases.

Incompatible materials

<u>Incompatible materials:</u> None known.

**Hazardous decomposition products** 

<u>Hazardous decomposition</u> When heated and in case of fire, irritating vapors/gases may be formed.

products:

 Product name:
 SPECIFIX RESIN
 Page:
 7/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### Information on toxicological effects

Inhalation: Not relevant at normal room temperatures. When heated, irritating vapors may be

formed.

Skin contact: Irritating and may cause redness, itching and small vesicles. Risk of sensitization

to epoxy compounds.

Eye contact: Causes serious eye irritation.

<u>Ingestion:</u> Irritating. May cause nausea, stomach pain and vomiting.

<u>Specific effects:</u> Risk of sensitization to epoxy compounds.

Carcinogenicity:

National Toxicology Program (NTP): No.

I.A.R.C. Monographs: No.

OSHA: No.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### **Toxicity**

Ecotoxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

### Persistence and degradability

<u>Degradability:</u> This product is expected to be heavily biodegradable.

Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

Mobility in soil

Mobility: No data available.

#### Results of PBT and vPvB assessment

PBT/vPvB: Not relevant.

Other adverse effects

Other adverse effects: None known.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## Waste treatment methods

Dispose of collected dust according to agreement with local authorities. Waste is classified as hazardous waste. Note that fully cured material is not considered as hazardous waste.

Waste from residues: 16 05 08

 Product name:
 SPECIFIX RESIN
 Page:
 8/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

## **SECTION 14: TRANSPORT INFORMATION**

**UN number** 

<u>UN-No:</u> 3082

UN proper shipping name

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy Resin)

Additional IMDG information:

EmS: F-A, S-F MFAG: 1

Transport hazard class(es)

Class: 9

Packing group

PG:

**Environmental hazards** 

Marine pollutant: Yes.
Environmentally Hazardous Yes.

substance:

Special precautions for user

Special precautions: None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

<u>Transport in bulk:</u> Not relevant.

## **SECTION 15: REGULATORY INFORMATION**

## Safety, health and environmental regulations/legislation specific for the substance or mixture

<u>Special provisions:</u> TSCA: Listed.

As a general rule, persons under 18 years of age are not allowed to work with this product. Users must be carefully instructed in the proper work procedure, the dangerous properties of the product and the necessary safety instructions.

National regulation: Europe/USA:

This Material Safety Data Sheet has been prepared according to the

EU-regulation.

**Chemical Safety Assessment** 

CSA status: Not relevant.

 Product name:
 SPECIFIX RESIN
 Page:
 9/9

 Revision Date:
 2015-01-07
 Print date:
 2015-01-07

 Document No.:
 M0073
 SDS-ID:
 US-EN/15.0

#### **SECTION 16: OTHER INFORMATION**

For restrictions on use see section 15.

The following sections contain revisions or new statements: -

The (\*) indicates the changes made with respect to the previous version.

Approved by DHI.

Allan Vorue

Additional information: Classification according to Regulation (EC) No. 1272/2008:

Calculation method.

Wording of H-statements:

R21/22 Harmful in contact with skin and if swallowed.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.