

Buckeye International, Inc.

2700 Wagner Place Maryland Heights, MO 63043 314/291-1900

N. F. P. A.


4 = Extreme

3 = High

2 = Moderate

1 = Slight

0 = Insignificant



Material Safety Data Sheet

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call: 651-632-8956. 24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call: 352-323-3500.

SECTIO	ON I - IDEN	TIFICATIO	N			
PRODUCT NAME				DATE PREPARED		
BUCKEYE SANICARE II						December 27, 2011
CHEMICA	L FAMILY					CODE
		Aerosol Disir	nfectant Deodoran	ıt		5501
PROPER D	O.T.					•
SHIPPING	NAME	Consumer Co	ommodity, ORM-	D		
D.O.T. HAZ	ZARD		•			
CLASSIFIC	CATION	ORM-D				
SECTIO	N II - INGI	REDIENTS A	AND IDENTITY	INFORMA	TION	
% By WGT		MATERIAL		PEL	T.L.V.	C.A.S. NO.
44.25	Ethanol			1000 ppm	1000 ppm	64-17-5
21.79	Isobutane/Propa	ne Blend		1000 ppm	1000 ppm	75-28-5; 74-98-6
2.20	Methanol*			200ppm	200ppm	67-56-1
0.30	Sodium Nitrite			NE	NE	7632-00-0
0.25	O-Phenylphenol	 *		NE	NE	90-43-7
0.15	Ammonium Hy	droxide		35 ppm	25 ppm	1336-21-6
ITEMS M	IARKED * ARE SA	ARA TITLE III SI	EC 313 REPORTABLE	S. ALL INGRE	DIENTS ARE ON	TSCA INVENTORY.
SECTIO	ON III - PHY	SICAL DAT	' A			
BOILING F	POINT °F		NA	pH (CONC.)		NE
SOLUBILITY IN WATER		Infinite		pH (USE DILUTION)		NE
% VOLATI	LE BY WEIGHT	98.0		EVAPORATION RATE (Water=1)		NE
SPECIFIC (GRAVITY	Concentrate 0.880		PRODUCT FORM		Aerosol
APPEARAI	NCE AND ODOR	Clear	Colorless Spray; Flora	al Fragrance		
SECTIO	ON IV - FIR	E AND EXP	LOSION DATA			
FLASH PO	INT(Test Method)	No Flame 1	Extention ASTM D30	65	FLAMMABL	E LIMITS
EXTINGUISHING MEDIA CO ₂ , Foam, Dry Che		Dry Chemical, Water	UPPER LIMIT: NE		LOWER LIMIT: NE	
SPECIAL F	FIRE FIGHTING P	ROCEDURES	S	elf-contained b	reathing apparatu	IS.
	EIDE AND EVEL	OCIONIII ZA DE		.	1. 4. 4	1200Γ
UNUSUAL	FIRE AND EXPL	OSION HAZARL				atures above 130°F,
				r containers ma	bustion. Oxides	of coult on
CECTIO		CTIVITY D		roducts of com	ioustion. Oxides	oi cardon.
	ON V - REA					
STABILITY Stable						
	DITIONS TO AVOID Open flame, welding area, heat and sparks.					
	NCOMPATIBILITY Oxidants, reducing agents, ammonia salts.				1	
				de, Carbon Dioxi	de	
HAZAKDU	OUS POLYMERIZA	ATION	<u> </u>	Vill not occur.		

BUCKEYE SANICARE II CODE: 5501

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? Yes SKIN? Yes INGESTION? No

HEALTH HAZARDS (Acute and Chronic)

Causes mild eye and skin irritation. For Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

For Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. Chronic effects: (Effects due to excessive exposure to the raw materials of this mixture) Overexposure may cause kidney damage, liver abnormalities, brain damage.

CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

SIGNS AND SYMPTOMS OF OVEREXPOSURE

For Eyes: Redness or burning sensation. For Skin: Redness of skin or a warming sensation.

For Inhalation: Dizziness, headache.

MEDICAL CONDITIONS

GENERALLY AGGRAVATED BY EXPOSURE

May aggravate existing eye, skin or upper respiratory conditions.

EMERGENCY AND FIRST AID PROCEDURES

Call a poison control center or doctor immediately for treatment advice. For Eyes and Skin: Remove contaminated clothing. Immediately flush eyes or skin with plenty of water for 15 - 20 minutes. For Inhalation: Move person to fresh air. If person is not breathing, call 911 or an ambulance and then give artificial respiration. For Ingestion: Give two large glasses of water. DO NOT induce vomiting. Never give anything by mouth to an unconscious person.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.

SECTION VII - SPILL OR LEAK PROCEDURES

SPILL RESPONSE

Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations.

WASTE DISPOSAL

METHOD

Send to sanitary landfill following local, state and federal regulations.

Aerosol cans when vented to atmospheric pressure through normal use, pose no hazard.

SECTION VIII - SPECIAL PROTECTION INFORMATION

EYE PROTECTION		VENTILATION	ON Adequate ventilation to	
Safe	ty glasses recommended.		keep vapor concentration below TLV.	
SKIN	Latex gloves if	RESPIRATORY	If vapor concentration exceeds TLV, use NIOSH	
PROTECTION	skin is easily irritated.	PROTECTION	approved respirator in positive pressure mode.	
OTHER				

SECTION IX - S	SPECIAL PRECAUTIONS
	Remove and wash all contaminated clothing before reuse.
PROTECTION	Wash thoroughly with soap and water after handling.

PRECAUTIONS IN	KEEP OUT	OF REACH O	F CHILDREN!
	_		

HANDLING AND	Do not puncture or incinerate containers.	Remove ignition sources.
STORAGE	Do not store at temperatures above 130°F.	Avoid breathing vapors.
	Avoid contamination of food and food utensils.	

Do not use on polished wood furniture or rayon fabrics. OTHER If more than 10,000 lbs. is stored in a single day, product may require reporting under PRECAUTIONS SARA Title III, Section 311/312 as a sudden release of pressure hazard. NFPA Code

NA = Not Applicable30B Level 2 Aerosol.

NE = Not Established

PREPARED BY: Scott Maag, Vice President of Operations

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept 1985.