U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I	*					
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.					
National Laboratories, Lehn & Fink Products	(201) 573-5700					
ADDRESS (Number, Street, City, State, and ZIP Code) 225 Summit Avenue, Montvale, New Jersey 07645						
CHEMICAL NAME AND SYNONYMS TRADE N	AME AND SYNONYMS					
	window, glass and multi					
Multi-use aerosol cleaner FORMULA purpo	se cleaner.					

		SECTION	11 -	, ,	RDOUS INGREDIENTS			
PAINTS, PRESERVATIVES, & SOLVENTS		%	TLV (Units)	ALLOYS AND METALLIC COATINGS		%	TLV (Units)	
PIGMENTS	Not Ap	plicabl	е		BASE METAL Not Appl	icable		
CATALYST	11	11			ALLOYS "	n. ^ · · ·		
VEHICLE	11	11		7 -	METALLIC COATINGS 11	11		
SOLVENTS	"	11			FILLER METAL PLUS COATING OR CORE FLUX	11		
ADDITIVES	11				OTHERS II	"		
OTHERS								ı
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES						%	TLV (Units)	
Isobutane	Propella	nt			,	5	10	
					31 ·			
								0
2					3			

SECTION III - PHYSICAL DATA									
BOILING POINT (°F.)			N A	SPECIFIC G	RAVITY (H ₂ O=1)	NA			
VAPOR PRESSURE (mm Hg.) '			N A	PERCENT, V		100			
VAPOR DENSITY (AIR=1)			N A	EVAPORAT	ION RATE =1)				
SOLUBILITY IN WATER	1		N A						
APPEARANCE AND ODOR	19 0	Ζ.	aerosol	containe	r				

SECTION IV - FIRE AND EXPLOSION HAZARD DATA								
FLASH POINT (Method used) Nonflammable - ASTM 3065 Flame Extension Test	Lei	Uel						
EXTINGUISHING MEDIA								
SPECIAL FIRE FIGHTING PROCEDURES Pressurized container								
UNUSUAL FIRE AND EXPLOSION HAZARDS Expose to temperatures above 120	For	in sun						
or discarding can in incinerator may cause bursting.								

	SECTION V - HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	Not Applicable	
EFFECTS OF OVEREXPOSURE	Non toxic	
EMERGENCY AND FIRST AID P	PROCEDURES Avoid spraying in eyes.	
	CECTION VI DEACTIVITY DATA	

			SECTION	ON VI - RI	EACTIVITY DATA			
STABILITY	UNS	JNSTABLE		CONDITIONS TO AVOID				
	STAE	BLE	Х					
INCOMPATABILIT	Y (Mater	ials to avoid)						
HAZARDOUS DEC	OMPOSI	TION PRODUC	TS .					
POLYMERIZATION		MAY OCCUR			CONDITIONS TO AVOID			
		WILL NOT OCCUR		Х				
		l						

SECTION VII - SPILL OR LEAK PROCEDURES
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Wipe up with rags or paper towels.
waste Disposal Metiopose in trash.

	SECTION VIII -	SPECIAL	PROTECTION INFORMATION
RESPIRATORY PE	ROTECTION (Specify type) Not Appl	icable	
VENTILATION	LOCAL EXHAUST	11	SPECIAL
	MECHANICAL (General)	11	OTHER
PROTECTIVE GLOVES Not Applicable			EYE PROTECTION Not Applicable
	ot Applicable		

SECTION IX - SPECIAL PRECAUTIONS								
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING CAUTION: Contents under pressure. Avoid spraying in eyes. Do not								
puncture. Do not use near heat or open flame. Exposure to temperatuother precautions	re							
above 120°F or in sun or discarding can in fire or incinerator may								
cause bursting. Keep out of reach of children.								

Form OSHA-20 Rev. May 72