



Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-0684-7	Version Number:	17.01
Issue Date:	05/02/14	Supersedes Date:	04/07/14

SECTION 1: Identification

1.1. Product identifier

SCOTCHKOTE 323 Patch, Brush, and Spray Grades, Part A

Product Identification Numbers

80-6116-1152-8, 80-6300-0059-6, 80-6300-0061-2, 80-6300-0247-7

1.2. Recommended use and restrictions on use

Recommended use

Coating, Part A of 2 Part Liquid Epoxy Coating System

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Electrical Markets Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

Causes eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	25068-38-6	60 - 70 Trade Secret *
HYDROUS MAGNESIUM SILICATE	14807-96-6	20 - 30 Trade Secret *
TITANIUM DIOXIDE	13463-67-7	1 - 5 Trade Secret *
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	64742-95-6	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Aldehydes
Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Irritant Vapors or Gases
Ammonia
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of vapors created during cure cycle. Avoid skin contact with hot material. For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TITANIUM DIOXIDE	13463-67-7	Amer Conf of Gov. Indust. Hyg.	TWA:10 mg/m ³	
TITANIUM DIOXIDE	13463-67-7	Chemical Manufacturer Rec Guid	TWA(as respirable dust):5 mg/m ³	
TITANIUM DIOXIDE	13463-67-7	US Dept of Labor - OSHA	TWA(as total dust):15 mg/m ³	
HYDROUS MAGNESIUM SILICATE	14807-96-6	Amer Conf of Gov. Indust. Hyg.	TWA(respirable fraction):2 mg/m ³	
HYDROUS MAGNESIUM SILICATE	14807-96-6	Chemical Manufacturer Rec Guid	TWA(as respirable dust):0.5 mg/m ³	
HYDROUS MAGNESIUM SILICATE	14807-96-6	US Dept of Labor - OSHA	TWA concentration(as total dust):0.3 mg/m ³ ;TWA concentration(respirable):0.1 mg/m ³ (2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	

LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	64742-95-6	Chemical Manufacturer Rec Guid	TWA:50 ppm(245 mg/m3)	
---	------------	--------------------------------------	-----------------------	--

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid : Chemical Manufacturer's Recommended Guidelines

US Dept of Labor - OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Provide local exhaust ventilation at transfer points.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Wear eye/face protection. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear protective gloves.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Viscous
Odor, Color, Grade:	Viscous, White
Odor threshold	No Data Available
pH	Not Applicable

Melting point	<i>No Data Available</i>
Boiling Point	> 200 °F
Flash Point	> 200 °F [Test Method: Tagliabue Closed Cup]
Evaporation rate	< 1 [Ref Std: BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	0.01 mmHg [Test Method: Calculated] [Details: at 25C, Raoult's Law]
Vapor Density	> 1 [Ref Std: AIR=1]
Density	1.425 g/cm3
Specific Gravity	1.425 [Ref Std: WATER=1]
Solubility In Water	<i>No Data Available</i>
Solubility- non-water	<i>No Data Available</i>
Solubility- non-water	Nil
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	120,000 - 280,000 centipoise [@ 72 °C] [Test Method: Brookfield]
Volatile Organic Compounds	12 g/l [Details: For coating mixture of Parts A and B]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Target Organ Effects:

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

<u>Name</u>	<u>Route</u>	<u>Species</u>	<u>Value</u>
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Ingestion	Rat	LD50 > 1,000 mg/kg
HYDROUS MAGNESIUM SILICATE	Dermal		LD50 Not available
HYDROUS MAGNESIUM SILICATE	Ingestion		LD50 Not available
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l

TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Dermal	Rabbit	LD50 > 2,000 mg/kg
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Rabbit	Mild irritant
HYDROUS MAGNESIUM SILICATE	Rabbit	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Rabbit	Moderate irritant
HYDROUS MAGNESIUM SILICATE	Rabbit	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Human and animal	Sensitizing
TITANIUM DIOXIDE	Human and animal	Not sensitizing
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Guinea pig	Not sensitizing

Respiratory Sensitization

Name	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Human	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	Human	Not sensitizing

Germ Cell Mutagenicity

Name	Route	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	In vivo	Not mutagenic
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	In Vitro	Not mutagenic
HYDROUS MAGNESIUM SILICATE	In vivo	Not mutagenic
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
HYDROUS MAGNESIUM SILICATE	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
TITANIUM DIOXIDE	Ingestion	Multiple animal species	Not carcinogenic
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Ingestion	Not toxic to female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Ingestion	Not toxic to male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Dermal	Not toxic to development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Ingestion	Not toxic to development	Rat	NOAEL 750 mg/kg/day	2 generation
HYDROUS MAGNESIUM SILICATE	Ingestion	Not toxic to development	Rat	NOAEL 1,600 mg/kg	during organogenesis
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	Not toxic to female reproduction	Rat	NOAEL 1,500 ppm	2 generation
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	Not toxic to male reproduction	Rat	NOAEL 1,500 ppm	2 generation
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 500 ppm	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Dermal	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
HYDROUS MAGNESIUM SILICATE	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
HYDROUS MAGNESIUM SILICATE	Inhalation	pulmonary fibrosis respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 18 mg/m3	113 weeks
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL	2 years

			data are not sufficient for classification		0.010 mg/l	
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *2 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	16-0684-7	Version Number:	17.01
Issue Date:	05/02/14	Supersedes Date:	04/07/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com