Page 1/4

#### 1 Identification of the substance and manufacturer Trade name: FLUORESCENT YELLOW Product code: 0000161619 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Manufacturer/Supplier: Seymour of Sycamore Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com www.seymourpaint.com 1-800-255-3924 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Additional information: GHS Hazard pictograms GHS02 GHS04 GHS07 GHS08 Signal word Danger Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. **Precautionary statements** Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

# 3 Composition/information on ingredients

Chemical characterization: Mixtures This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description: Dangerous components: 15-25% 74-98-6 propane 64742-47-8 Mineral Spirits 10-15% 1317-65-3 Calcium Carbonate 10-15% 106-97-8 n-butane 10-15% 110-19-0 Isobutyl Acetate 5-10% 64742-94-5 Naphtha, heavy aromatic 1-5% 64742-89-8 VM&P Naphtha 1-5% 68410-97-9 Low boiling point naphtha 1-5%

4 First-aid measures After inhalation: After skin contact: After eye contact: After swallowing:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse out mouth and then drink plenty of water.	
Most important symptoms and effects: Indication of any immediate medical attention needed:	Rinse mouth with water. Do not <sup>'</sup> induce vomiting. Dizziness No further relevant information available.	
5 Fire-fighting measures		
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.	(Contd on page 2)

Revised On 01/09/2023

	(Contd. of page
Protective equipment for firefighters:	A respiratory protective device may be necessary.
Accidental release measures	
Personal precautions, protective	
equipment and emergency procedures:	Wear protective equipment. Keep unprotected persons away.
procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Ensure adequate ventilation.
Handling and storage	
Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
	action .
Exposure controls/personal prot Components with limit values that r	
74-98-6 propane	oquito montoring at the workplace.
PEL (USA) Long-term value: 1800 mg	a/m <sup>3</sup> , 1000 ppm
REL (USA) Long-term value: 1800 mg	
TLV (USA) see Appendix F Minimal of	
106-97-8 n-butane	
REL (USA) Long-term value: 1900 mg	j/m <sup>3</sup> , 800 ppm
TLV (USA) Short-term value: 1000 pp	
(EX)	
110-19-0 Isobutyl Acetate	
PEL (USA) Long-term value: 700 mg/	
REL (USA) Long-term value: 700 mg/	m³, 150 ppm
TLV (USA) Short-term value: 150 ppm	n
Long-term value: 50 ppm	
Hygienic protection:	Wash hands after use. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas.
Breathing equipment.	cases where short and/or long term overexposure exists, a charcoal filter respirator should be wo
	If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Nitrile gloves.
	The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles
Physical and chemical properties	S
Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Auto igining.	
	In use, may form flammable/explosive vapour-air mixture.
Danger of explosion: Lower Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 0.5 Vol % 10 0 Vol %
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	0.5 Vol % 10.9 Vol %
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure:	0.5 Vol % 10.9 Vol % Not determined.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density:	0.5 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00)
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density	0.5 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate	0.5 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/wate	0.5 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. r: Not determined.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate	0.5 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable.

	Safety Data Sheet
Printing date 01/09/2023	Revised On 01/09/2023
Trade name: FLUORESCENT YELLOW	
	(Contd. of page 2)
10 Stability and reactivity	
Reactivity: Conditions to avoid: Chemical stability: Possibility of hazardous reactions:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated. No dangerous reactions known.
Incompatible materials: Hazardous decomposition: 11 Toxicological information	No further relevant information available. No dangerous decomposition products known.
LD/LC50 values that are relevant for	classification:
110-19-0 Isobutyl Acetate	
Oral LD50 4,763 mg/kg (rbt)	
	. No data available
Information on toxicological effects	No data available.
Information on toxicological effects Skin effects: Eye effects:	No irritant effect. No irritating effect.

12 Ecological information	
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.

#### **13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

### 14 Transport information

+ mansport mormation	
UN-Number	UN1950
DOT	UN1950
	UN1950
DOT	Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1 Gases
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-Ŭ
Packaging Group:	
UN "Model Regulation":	UN1950, Aerosols, 2.1

## **15 Regulatory information**

SARA Section 355 (extremely hazardous substances):		
None of the ingredients in this product are listed.		
SARA Section 313 (Specific toxic chemical listings):		
None of the ingredients is listed.		
Toxic Substances Control Act		
(TSCA):	All hazardous ingredients are found on the inventory list of substances.	
Canadian Domestic Substances Lis	t	
(DSL):	All ingredients are listed or exempted.	
Consumer Product Safety		
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals known to cause cancer:		
100-41-4 ethyl benzene		
Prop 65 chemicals known to cause birth defects or reproductive harm:		
None of the ingredients is listed.		
	(Contd. on page 4)	

Revised On 01/09/2023

Page 4/4

Trade name: FLUORESCENT	YELLOW	
		(Contd. of page 3)
EPA:		
110-19-0 Isobutyl Acetate	9	D
16 Other information		
Contact:	Regulatory Affairs	