```
FOR COATINGS, RESINS AND RELATED MATERIALS
**************************
                          SECTION I
******************************
Manufacturers Name SHEFFIELD BRONZE PAINT CORP Emergency Phone No.
Street Address 17814 S.WATERLOO RD.
                                      (216) 481-8330
City, State, Zip CLEVELAND, OHIO 44119 TRANSPORTATION EMERGENCIES: CHEMTREC
PRODUCT NUMBER: 2-740
                                (800) 424-9300 CONTINENTAL U.S.
PRODUCT NAME: BRIGHT GOLD ENAMEL
                                (202) 483-7616 (COLLECT) FROM
PRODUCT CLASS: INTERIOR/EXTERIOR PAINT
                                      ALASKA & HAWAII
*******************************
                SECTION II - HAZARDOUS INGREDIENTS
**************************
                * CAS NUMBER*PERCENT* TLV
TNGREDIENT
                                               VAPOR PRESSURE
                * * PPM MG/M3* LEL * MM/HG
****************************
                        :27.04 : : 0.8 :
*MEDIUM OIL ALKYD :
                                            : 7@ 100°F.
*MINERAL SPIRITS :64742-48-9 :51.72 :100 : :
                        :17.10 : :
BRONZE POWDER
*COPPER
              :7440-50-8
                        :
                              :
:<2.0 :
ADDITIVES
                                   : :
                         :
                              :
All INGREDIENTS ARE LISTED ON THE EPA/TSCA INVENTORY
SARA TITLE III SECTION 313 REPORTING FOR SUPERFUND AMENDMENTS
******************************
                  SECTION III - PHYSICAL DATA
****************************
Boiling Range 300-390°F
                                   Vapor Density: HEAVIER than AIR
Evaporation Rate SLOWER THAN ETHER
Percent Volatile by Weight - 54.6 Vercent Volatile by Volume - 69.6
                            V.O.C.: 4.71#/Gallon; 565 Grams/Liter
                                 WEIGHT per GALLON- 8.61 LBS.
**************************
                SECTION IV - FIRE and EXPLOSION DATA
******************************
DOT CATEGORY -COMBUSTIBLE LIQUID
                                   FLASH POINT-104°F
EXTINGUISHING MEDIA CO-2, DRY CHEMICAL, FOAM, FOG. DO NOT use direct stream of water.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
: VAPORS ARE HEAVIER THAN AIR AND MAY ACCUMULATE IN LOW OR UNVENTILATED AREAS.
: THEY MAY FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER
SPECIAL FIRE FIGHTING PROCEDURES-DO NOT ENTER CONFINED FIRE SPACE WITHOUT
: PROPER PROTECTIVE EQUIPMENT INCLUDING a N.I.O.S.H. APPROVED BREATHING APPARATUS.
***************************
                SECTION V - HEALTH HAZARD DATA
*****************************
THRESHOLD LIMIT VALUE- 100ppm
EFFECTS OF OVEREXPOSURE- DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS. EYE AND
: SKIN IRRITATION. REMOVE TO FRESH AIR. SECURE MEDICAL ATTENTION. GIVE MOUTH
: TO MOUTH RESUSCITATION. DO NOT INDUCE VOMITING. FLUSS EYES AND SKIN WITH
```

MATERIAL SAFETY DATA SHEETS

DATE: August 2011

: LARGE AMOUNTS OF WATER.

PAGE 2 of 2: #2-740 SUPER BRIGHT GOLD ENAMEL \* SECTION VI - REACTIVITY DATA \* STABILITY-STABLE CONDITIONS TO AVOID INCOMPATABILITY: THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES AND SELECTED AMINES. HAZARDOUS DECOMPOSITION PRODUCTS- FUMES, SMOKE, HYDROGEN CHLORIDE AND CARBON MONOXIDE, : IN THE CASE OF COMPLETE COMBUSTION. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID: OPEN FLAME, EXTREME HEAT \* SECTION VII - SPILL OR LEAK PROCEDURES \* STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate, avoid breathing vapors SEE SECTION X Remove with INERT ABSORBENT (sand, earth, sawdust etc.) WASTE DISPOSAL METHOD: : DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, and LOCAL REGULATIONS REGARDING : POLLUTION. IF DISCARDED THIS PRODUCT MAY BECOME AN IGNITABLE, HAZARDOUS WASTE. \* SECTION VIII - SPECIAL PROTECTION INFORMATION \* RESPIRATORY PROTECTION- USE HYDROCARBON VAPOR CANISTER OR AIR RESPIRATOR : IN CONFINED OR ENCLOSED SPACES, IF NEEDED. VENTILATION- LOCAL EXHAUST FACE VELOCITY > 60 fpm; USE ONLY WITH : ADEQUATE VENTILATION, USE EXPLOSION PROOF EQUIPMENT. NO SMOKING OR OPEN LIGHTS. PROTECTIVE GLOVES: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT EYE PROTECTION: SAFETY GLASSES WITH UNPERFORATED SIDESHIELDS OTHER PROTECTIVE EQUIPMENT- USE CHEMICAL RESISTANT APRON OR CLOTHING, AVOID REPEATED OR PROLONGED SKIN CONTACT. \* SECTION IX - SPECIAL PRECAUTIONS \* PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: USE ADEQUATE VENTILATION EQUIVALENT TO THE OUTDOORS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS. STORE IN COOL, DRY PLACE. OTHER PRECAUTIONS- DO NOT TAKE INTERNALLY. DO NOT STORE IN UNLABELED CONTAINERS. WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER CONTACT. \* SECTION X - HAZARDOUS MATERIAL IDENTIFICATION \* LISTED IN THIS SECTION IS NPCA-HMIS CLASSIFICATION FOR THIS PRODUCT Health : 1 : Flammability : 2 Reactivity : 0 Personal Protection: B \*

The information contained herein is believed to be accurate and complete to the best of Sheffield Bronze's knowledge at the time of issuance. Sheffield Bronze does not warranty the accuracy of this data and shall not be liable for any loss or damage arising from the use thereof. Information above pertains to this product as currently formulated. Addition of other additives may alter the Composition and Hazards WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED AND ASSUME NO LIABILITY WITH USE OF THIS INFORMATION.