

MATERIAL SAFETY DATA SHEET

Date Issued: 7/8/2003 Supercedes: 7/15/2002

I. Identification of the Substance/Preparation and the of the Company/Undertaking

Identification of the product

Product Name:

Shimmerize Nail & Polish Enhancement UV Gel

Company/undertaking identification:

Star Nail International
29120 Avenue Paine
Valencia, CA 91355 USA

Phone 661-257-7827

Emergency Contact Information
813-248-0573 or 800-255-3924

II. Composition on Ingredients

Synonyms: Acrylated urethane / epoxy blend

	CAS #	WT% OSHA TWA ppm	OSHA STEL ppm	ACGIH TWA ppm	ACGIH
STEL ppm					
Urethane Diacrylate	***	60-63	---	---	---
Urethane Triacrylate	***	30-32	---	---	---
Epoxy diacrylate	***	10	---	---	---
Photoinitiator	947-19-3	1-5	---	---	---
Silica	67762-90-7	0-5	---	---	---
Titanium Dioxide	***	0-0.3	---	---	---
Various Pigments	***	0-0.5	---	---	---

--- Not established

*** The specific chemical identity and/or weight percent is being withheld as a trade secret

III. Hazard Identification

Irritating to eyes. Repeated exposure may cause skin dryness, cracking or rash.

IV. First Aid Measures

Eye Contact: Flush with plenty of water for at least 15 minutes and seek medical attention.

Skin Contact: Remove contaminated clothing and wash contact area with soap and water for 15 minutes. Particular attention should be paid to hair, nose, ears and other areas not easily cleaned. See section VIII. Note to physician: effects can be delayed 24-48 hours.

Ingestion: If appreciable quantities are swallowed, seek medical attention.

Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention

V. Fire-Fighting Measures

Extinguishing Media:

Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires

Unusual Fire and Explosion Hazards:

High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and and the violent rupture of storage vessels and containers. Avoid the use of a stream of water to control fires since frothing can occur.

Special Fire Fighting Procedure:

Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined area where potential for exposure to vapors or products of combustion exists.

VI. Accidental Release Measures

Steps to Be Taken in Case Material is Released or Spilled:

Spontaneous polymerization can occur. Eliminate ignition & heat sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb with inert material and dispose. Flush area with water; prevent washings from entering waterways. Spills or releases to the environment may be reportable to the National Response Center (800- 424-8802) and to state and local agencies.

Waste Disposal Method:

For large spills: incinerate or use biological treatment in accordance with federal, state and local regulations. For small spills: cure using UV light or peroxide and dispose in accordance with federal, state and local regulations.

VI. Handling & Storage

Stability: Normally Stable

Conditions to Avoid:

Storage >100F, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

Materials to Avoid:

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.

Hazardous Decomposition Products:

Fumes produces when heated to decomposition may include: carbon monoxide, carbon dioxide, oxides of nitrogen.

VIII. Exposure Controls/Personal Protection

Respiratory Protection:

When exposed to aerosols or vapors, use full-face respirator with organic vapor cartridges that utilize a particulate pre-filter. In emergency situations, or when used in confined spaces, use self-contained breathing apparatus or other air-supplied full face respirator.

Ventilation:

Local exhaust - recommended to control exposure which may result from operations generating
Mechanical - Not recommended to control exposure for operations generating aerosols or vapors.

Protective Gloves:

Impervious gloves (neoprene). A combination of barrier cream, applied before exposure, and gloves is recommended. Do not apply cream after exposure.

Eye Protection:

Chemical splash goggles or safety glasses when handling large quantities.

Other Protective Equipment:

None

IX. Physical and Chemical Properties:

Manufacturer's ID:	LE Colorz	Form:	liquid
Product Class:	Acrylated urethane / epoxy blend	Color:	colorless
Boiling Range:	n.a.	Percent Volatile by Volume:	0
Vapor Density:	n.a.		
VOC:	0.0	Weight Per Gallon:	9.1 lbs
Evaporation Rate:	n.a.	Vapor Pressure at 20C:	n.a.
Appearance and Odor:	Clear liquid with mild odor	Solubility in Water:	insoluble
Flashpoint:	> 212 F Setafash		
Explosion Limits:	LEL: n.a. UEL: n.a.		

X. Stability and Reactivity

Stability: Normally Stable
Hazardous Polymerization:
May occur – uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.
Conditions to Avoid:
Storage >100F, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.
Materials to Avoid:
Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.
Hazardous Decomposition Products:
Fumes produces when heated to decomposition may include: carbon monoxide, carbon dioxide, oxides of nitrogen.

XI. Toxicological Information

Health Hazards: See section V
Ingestion: n.a.
Inhalation: n.a.
Skin Contact: n.a.
Allergy Sensitization: Mild skin and eye sensitization may be observed upon continued overexposure
Carcinogenicity: Category E (evidence of non-carcinogenicity for humans)
Mutagenicity: Negative in all tests

XII. ECOLOGICAL INFORMATION

Biologic Degredation: Biodegradation: n.a
Behavior in environmental compartments: Distribution: log p(o/w): n.a. no bioaccumulation to be expected
Ecotoxic effects:
Biological effects:
Fish toxicity: L. macrochirus LC₅₀: n.a
Daphnia toxicity: Daphnia magna EC₅₀:n.a.
Maximum permissible toxic concentrations:
Algeal toxicity: Sc. Quadricauda IC₅: n.a.
Bacterial toxicity: M. aeruginosa EC₅: n.a.
Protozoa: E. sulcatum EC₅: n.a.
Further ecological data:
Degradability:
BOD₅: n.a.
COD: n.a.
TOD: n.a.

XIII. DISPOSAL INFORMATION

Product: Chemicals must be disposed of in compliance with federal, state and local regulations.
Container: Container must be disposed of in accordance with federal, state and local regulations.

XIV. Transportation Information

D.O.T. Shipping Name: polyurethane resin
D.O.T. Hazard Class: none
D.O.T. Label(s): none
D.O.T. UN/NA Number: none

XV. Regulatory Information

In The EU:
Classification and Labeling (according to 88/379/EEV as amended): None
Threshold Limit Value: **OSHA PEL** **ACGIH TLV** **MAK** **HGV** **Others**
(USA) (USA) (Germany) (Denmark)
n.a. n.a. n.a. n.a. ---
Product Name: See section I
Active Ingredient: urethane acrylate
EPA Reg. No. n.a.

XVI. Other Information

All of the components of this product are included on the TSCA inventory
INVENTORY STATUS:
Australia (AICS): Included on inventory
Canada (DSL): Included on inventory
European Economic Community (EINECS): Included on inventory
Japan (MITI): Included on inventory
Korea (MOE): Included on inventory