

Safety Data Sheet

acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

1 Identification

Trade name: Solid Lead (Pb) Alloy Solder Wire**Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

Kester Inc.

800 West Thorndale Avenue

Itasca, IL 60143 USA

Tel (630) 616-4000

Tel International 00 1 630 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd.

Heng Qiao Road

Wujiang Economic Development Zone

Suzhou, Jiangsu 215200 China

Tel +86 512 82060808

Kester GmbH

Ganghofer Strasse 45

D-82216 Gernlinden Germany

Tel +49 (0) 8142 4785 0

Information department: Product Compliance: EHS_Kester@kester.com**Emergency telephone number:**

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

2 Hazard(s) identification

Classification of the substance or mixture

Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1 H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS07

GHS08

Signal word Danger

(Contd. on page 2)

US

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 1)

Hazard-determining components of labeling:

LEAD (Pb)

Hazard statements

- H302+H332 Harmful if swallowed or if inhaled.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P314 Get medical advice/attention if you feel unwell.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)





Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients

Description: Mixture of the substances listed below with nonhazardous additions.

| CAS No. | Description | % Range |
|----------------|--|---------|
| CAS: 7439-92-1 | LEAD (Pb) | 20-100% |
| |   | |
| CAS: 7440-31-5 | TIN (Sn) | 0-80% |
| CAS: 7440-22-4 | SILVER (Ag) | 0-5% |

4 First-aid measures

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Follow general first aid procedures.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 2)

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Seek immediate medical advice.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture In case of fire, the following can be released:

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Environmental precautions: No special measures required.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

| | | |
|----------------|--------------|------------------------|
| CAS: 7439-92-1 | LEAD (Pb) | 0.15 mg/m ³ |
| CAS: 7440-31-5 | TIN (Sn) | 6 mg/m ³ |
| CAS: 7440-22-4 | SILVER (Ag) | 0.3 mg/m ³ |
| CAS: 7440-69-9 | BISMUTH (Bi) | 15 mg/m ³ |

PAC-2:

| | | |
|----------------|--------------|-----------------------|
| CAS: 7439-92-1 | LEAD (Pb) | 120 mg/m ³ |
| CAS: 7440-31-5 | TIN (Sn) | 67 mg/m ³ |
| CAS: 7440-22-4 | SILVER (Ag) | 170 mg/m ³ |
| CAS: 7440-69-9 | BISMUTH (Bi) | 170 mg/m ³ |

PAC-3:

| | | |
|----------------|--------------|-----------------------|
| CAS: 7439-92-1 | LEAD (Pb) | 700 mg/m ³ |
| CAS: 7440-31-5 | TIN (Sn) | 400 mg/m ³ |
| CAS: 7440-22-4 | SILVER (Ag) | 990 mg/m ³ |
| CAS: 7440-69-9 | BISMUTH (Bi) | 990 mg/m ³ |

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 3)

7 Handling and storage

Handling:

Precautions for safe handling Thorough dedusting.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

CAS: 7439-92-1 LEAD (Pb)

| | |
|-----|--|
| PEL | Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 |
| REL | Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C |
| TLV | Long-term value: 0.05* mg/m ³ *and inorganic compounds, as Pb; BEI |

CAS: 7440-31-5 TIN (Sn)

| | |
|-----|---|
| PEL | Long-term value: 2 mg/m ³ metal |
| REL | Long-term value: 2 mg/m ³ |
| TLV | Long-term value: 2 mg/m ³ metal |

CAS: 7440-22-4 SILVER (Ag)

| | |
|-----|--|
| PEL | Long-term value: 0.01 mg/m ³ |
| REL | Long-term value: 0.01 mg/m ³ |
| TLV | Long-term value: 0.1 mg/m ³ metal: dust and fume |

Additional information:

PEL = Permissible Exposure Limit (OSHA)

TLV= Threshold Limit Value (ACGIH)

OSHA= Occupational Safety and Health Administration

ACGIH= American Conference of Governmental Industrial Hygienists

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 4)

Protection of hands:



Protective gloves

Material of gloves:

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

| | |
|---------------|-------------|
| Form: | Solid |
| Color: | Silver grey |
| Odor: | Mild |

pH-value: Not applicable.

Change in condition

Melting point/Melting range: Undetermined.

Flash point: Not applicable.

Flammability (solid, gaseous): Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Vapor pressure at 970 °C (1,778 °F): 1.3 hPa (1 mm Hg)

Density at 20 °C (68 °F): 9.45 g/cm³ (78.86 lbs/gal)

Vapor density: Not applicable.

Solubility in / Miscibility with

Water: Insoluble.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 5)

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

CAS: 7439-92-1 LEAD (Pb)

| | | |
|------------|----------|-----------------|
| Oral | LD50 | 500 mg/kg (ATE) |
| Inhalative | LC50/4 h | 1.5 mg/l (ATE) |

Primary irritant effect:

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization: Sensitization possible through inhalation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

Carcinogenic categories

IARC (International Agency for Research on Cancer)

| | | |
|----------------|-----------|----|
| CAS: 7439-92-1 | LEAD (Pb) | 2B |
|----------------|-----------|----|

NTP (National Toxicology Program)

| | | |
|----------------|-----------|---|
| CAS: 7439-92-1 | LEAD (Pb) | R |
|----------------|-----------|---|

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 6)

14 Transport information

| | |
|--|-----------------|
| UN-Number | Not applicable |
| DOT, ADR, ADN, IMDG, IATA | Not applicable |
| UN proper shipping name | Not applicable |
| DOT, ADR, ADN, IMDG, IATA | Not applicable |
| Transport hazard class(es) | |
| DOT, ADR, ADN, IMDG, IATA | |
| Class | Not applicable |
| Packing group | |
| DOT, IMDG, IATA | Not applicable |
| Special precautions for user | Not applicable. |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| UN "Model Regulation": | Not applicable |

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are listed on the following Government Inventories:

- China: Inventory of Existing Chemical Substances in China (IECSC)
- Korea: Korea Existing Chemicals List (ECL)
- Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)
- Japan: Inventory of Existing and New Chemical Substances (ENCS)
- Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

CAS: 7439-92-1 | LEAD (Pb)

CAS: 7440-22-4 | SILVER (Ag)

California Proposition 65

Chemicals known to cause cancer:

LEAD (Pb)

Chemicals known to cause reproductive toxicity:

LEAD (Pb)

Carcinogenic categories

EPA (Environmental Protection Agency)

CAS: 7439-92-1 | LEAD (Pb) B2

CAS: 7440-22-4 | SILVER (Ag) D

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 7)

CANADA:

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

LEAD (Pb)

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing Safety Data Sheet (SDS): Product Compliance / EHS Department

Contact: EHS_Kester@kester.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS 29CFR1910.1200

Printing Date 11/01/2017

Version number 3

Reviewed on 11/01/2017

Trade name: Solid Lead (Pb) Alloy Solder Wire

(Contd. of page 8)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Carc. 2: Carcinogenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 1: Reproductive toxicity – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
*** Data compared to the previous version altered.**

US