



SHEET #365

ZBU487320
BU487320

MATERIAL SAFETY DATA SHEET

Speedball GLASS Glass and Surface
CleanerDate Prepared: 04/02/1998
Date Revised: 05/26/1998

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name/Use: Speedball GLASS Glass and Surface Cleaner

MANUFACTURER

The Butcher Company

67 Forest Street

Marlborough, MA 01752-3012

Butcher Telephone Number: 800-225-9475

Emergency Telephone (24 hours): 800-228-5635 Ext 118

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS NO.	% BY WEIGHT
Isopropyl alcohol	67-63-0	3 - 5
Propylene glycol n-propyl ether	1569-01-3	1 - 3
Ammonium hydroxide	1336-21-6	0.25 - <1.0

See Section 8 for Exposure Limits

NA - Not Applicable

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear, Blue Liquid. Soapy, ammonia Odor. May Cause Eye Irritation. Combustible.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(S) OF EXPOSURE: ☒ Eye ☒ Skin Contact ☐ Skin Absorption
☒ Inhalation ☒ Ingestion

EFFECTS OF ACUTE EXPOSURE

EYES:

May cause eye irritation. Symptoms may include redness and pain.

SKIN:

May cause mild skin irritation. Symptoms may include redness.

INITIATION:

High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing, wheezing and shortness of breath. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

INGESTION:

May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

MSDS No: 4287

Page: 1 of 1

Speedball GLASS Glass and Surface
CleanerDate Prepared: 04/02/1998
Date Revised: 05/26/1998

EFFECTS OF CHRONIC EXPOSURE:

Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

MEDICAL CONDITIONS AGGRAVATED:

May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES:

Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN:

Flush with water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops.

INITIATION:

Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION:

Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 115°F 46.1°C TCC

FLAMMABLE LIMITS

UPPER EXPLOSIVE LIMIT: 12.7% (2-propanol)

LOWER EXPLOSIVE LIMIT: 2% (2-propanol)

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA:

Use water fog, dry chemical, CO₂, or foam.

HAZARDOUS COMBUSTION PRODUCTS:

Normal products of combustion (carbon monoxide and carbon dioxide).

FIRE AND EXPLOSION HAZARDS:

Class II combustible liquid. This product is combustible and may be ignited by heat, sparks, flame, and other ignition sources. Vapors can travel to a source of ignition and flash back.

MSDS No: 4287

Page: 1 of 1

FIRE FIGHTING INSTRUCTIONS:

Evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Remove ignition sources and ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent and non-sparking tools to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING:

Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse.

STORAGE:

Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Store away from direct sunlight. Keep away from heat, sparks and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE: Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN:

Where prolonged or repeated contact is possible, chemical-resistant clothing (e.g., gloves) is recommended.

RESPIRATORY:

No respiratory protection is required if ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits may be exceeded, use appropriate respiratory protection (NIOSH/MSHA-approved) to prevent overexposure.

ENGINEERING CONTROLS:

General room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

EXPOSURE LIMITS:

INGREDIENT(S)

	OSHA PEL/STEL	ACGIH TLV/STEL
Isopropyl alcohol	400 ppm (980 mg/m ³) / 500 ppm (1225 mg/m ³) NE	400 ppm (98.1 mg/m ³) / 500 ppm (12.30 mg/m ³) NE
Propylene glycol n-propyl ether	50 ppm (35 mg/m ³) / (NII)	25 ppm (17 mg/m ³) / 35 ppm (24 mg/m ³) (NII)
Ammonium hydroxide		

NE - Not Established

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Soapy, ammonia

APPEARANCE: Clear, Blue

pH: 10.5 to 11.5

PERCENT VOLATILE BY WEIGHT: 99.5

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: Not Determined

FREEZING/MELTING POINT: Not Determined

SOLUBILITY IN WATER: Complete

EVAPORATION RATE: Not Determined

SPECIFIC GRAVITY: 0.991

VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Determined

ODOR THRESHOLD: Not Determined

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID):

Stable.

POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION:

None.

INCOMPATIBLE MATERIALS:

Oxidizers (e.g., bleach) and strong bases (e.g., sodium hydroxide).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA:

Based on testing of this similar product, this product may cause eye irritation; it is not considered to be toxic by inhalation. The following data are available for product ingredients.

PRODUCT/INGREDIENT	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Isopropyl alcohol	5840 mg/kg	13000 mg/kg	12000 ppm (8-hr)
Propylene glycol n-propyl ether	2000-4350 mg/kg	3800-4290 mg/kg	Not Available
Ammonium hydroxide	350 mg/kg	Not Available	Not Available

SENSITIZATION DATA:
No data available.

CHRONIC DATA:

Prolonged overexposure to isopropyl alcohol by ingestion and inhalation has caused central nervous system effects in humans and laboratory animals; overexposure by ingestion has also caused liver effects in animals. Prolonged overexposure to high concentrations of propylene glycol n-propyl ether by skin absorption, ingestion and inhalation may cause liver, kidney, and central nervous system effects.

REPRODUCTIVE/TERATOGENIC DATA:

Ingestion of isopropyl alcohol has caused slight fetotoxic and reproductive effects in laboratory animals.

CARCINOGENIC/MUTAGENIC DATA:

Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS:

No data available.

12. ECOLOGICAL INFORMATION

This product is made with all biodegradable detergents. No other data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA hazardous waste (Ignitable-D001) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/IDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated when in a container of 119 gallons (454 liters) or less.

15. REGULATORY INFORMATION

Not meant to be all-inclusive—selected regulations represented.

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)
311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories.
Immediate, Delayed, Fire.

313 REPORTABLE INGREDIENTS: Ingredients in this product are not currently subject to notification.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)
CERCLA REGULATORY: Not reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
Isopropyl alcohol	67-63-0	MA, NJ, PA
Propylene glycol n-propyl ether	1569-01-3	Not Listed

NA - Not Applicable

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):

Class B-Division 3, combustible liquid; Class D-Division 2B, eye irritant. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.


16. OTHER INFORMATION

HMIS RATING

HEALTH	*	1
FLAMMABILITY		2
REACTIVITY		0
PERSONAL PROTECTION		-

NFPA RATING

FIRE



SPECIAL.

MSDS STATUS

Revision #: 1

This MSDS replaces the May 05, 1998 MSDS. Any changes in information are as follows:

**Speedball GLASS Glass and Surface
Cleaner**

Date Prepared: 04/02/1998
Date Revised: 05/20/1998

APPROVAL DATE: 05/20/1998

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.