RESENE STAINLOCK

RESENE PAINTS LTD

Version No: **1.2**Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 2

Issue Date: 30/10/2014 Print Date: 30/10/2014 Initial Date: 30/10/2014 S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RESENE STAINLOCK
Chemical Name	Not Applicable
Synonyms	9428
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
Relevant identified uses	Use according to manufacturer's direction

Details of the manufacturer/importer

Registered company name	RESENE PAINTS LTD 32-50 VOGEL STREET, LOWER HUTT New Zealand			
Address				
Telephone	+64 4 577 0500			
Fax	+64 4 577 3327			
Website	www.resene.co.nz			
Email Not Available				

Emergency telephone number

	Association / Organisation	Not Available
	Emergency telephone numbers	0800737363
	Other emergency telephone numbers	0800737363

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2	
+800 2436 2255	+612 9186 1132	Not Available	

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

GHS Classification	Not Applicable		
Determined by Chemwatch using GHS/HSNO criteria	Not Available		
Label elements			
GHS label elements	Not Applicable		
SIGNAL WORD	NOT APPLICABLE		

Hazard statement(s)

Not Applicable

Precautionary statement(s): Prevention

Not Applicable

Version No: **1.2** Page **2** of **6** Issue Date: **30/10/2014**

RESENE STAINLOCK

Precautionary statement(s): Response

Not Applicable

Precautionary statement(s): Storage

Not Applicable

Precautionary statement(s): Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
Not Available	70-85	non hazardous materials	
7732-18-5	15-30	water	

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 764 766 | NZ Emergency Services: 111 - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

▶ There is no restriction on the type of extinguisher which may be used.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Advice for firefighters

Fire Fighting • Alert Fire Brigade and tell them location and nature of hazard		
Fire/Explosion Hazard ► Non combustible.		▶ Non combustible.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	► Clean up all spills immediately.	
Major Spills Moderate hazard.		
Personal Protective Equipment advice is contained in Section 8 of the MSDS.		

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Frecautions for safe nationing		
	Safe handling	 ▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Avoid all personal contact, including inhalation.
Other information		

Print Date: 30/10/2014

RESENE STAINLOCK

Suitable container

Polyethylene or polypropylene container.

Barium sulfate (barytes)

• reacts violently with dimethyl sulfoxide, sodium acetylide, finely divided carbon, aluminium, magnesium, zirconium, and possibly other active metals, especially at elevated temperatures

• is incompatibility

Titanium dioxide

• reacts with strong acids, strong oxidisers

• reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures

• these reactions involves reduction of the oxide and are accompanied by incandescence

• dust or powders can ignite and then explode in a carbon dioxide atmosphere

None known

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

TEEL-0

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

Ingredient

EMERGENCY LIMITS

ingrodient	ILLE 0	1 1	1222	ILLE O
RESENE STAINLOCK	Not Available	Not Available	Not Available	Not Available
Ingredient			Revised IDLH	
non hazardous materials			Not Available	
water			Not Available	

TEFI -1

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.	
Personal protection		
Eye and face protection	► Safety glasses with side shields.	
Skin protection	See Hand protection below	
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC.	
Body protection	See Other protection below	
Other protection	▶ Overalls.	
Thermal hazards	Not Available	

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the $\ \textit{computer-generated}$ selection:

RESENE STAINLOCK

Material	СРІ
BUTYL	A
NEOPRENE	A
NATURAL RUBBER	С
NITRILE	С
PVA	С
PVC	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AX Filter of sufficient capacity.

TFFI -2

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

TEFI -3

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	AX-AUS / Class 1	-	AX-PAPR-AUS / Class 1
up to 25 x ES	Air-line*	AX-2	AX-PAPR-2
up to 50 x ES	-	AX-3	-
50+ x ES	-	Air-line**	-

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Print Date: 30/10/2014

^{^ -} Full-face

Version No: 1.2 Page 4 of 6

RESENE STAINLOCK

Issue Date: **30/10/2014**Print Date: **30/10/2014**

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

A	Note that all of the monopropylene glycol ethers may exist in two isomeric forms, alpha or beta.
Appearance	Off white liquid

	Oil writte liquid		
Physical state	Liquid	Relative density (Water = 1)	1.4
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	0.001 BuAC = 1	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	60
Vapour pressure (kPa)	0.002	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	15

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	▶ Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).
Ingestion	All cases of acute oral barium poisoning in adults exhibit gastrointestinal disturbances as the initial symptoms.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

RESENE STAINLOCK	TOXICITY	IRRITATION
	Not Available	Not Available
water	TOXICITY	IRRITATION
water	Not Available	Not Available

RESENE STAINLOCK	for propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM).
WATER	No significant acute toxicological data identified in literature search.

Version No: 1.2 Page 5 of 6 Issue Date: 30/10/2014 Print Date: 30/10/2014

RESENE STAINLOCK

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

✓ – Data required to make classification available

X - Data available but does not fill the criteria for classification

Data Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

for propylene glycol ethers:

Environmental fate:

Most are liquids at room temperature and all are water-soluble.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
non hazardous materials	HIGH	HIGH
water	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
non hazardous materials	LOW (BCF = 40.49)
water	LOW (BCF = 3.162)

Mobility in soil

Ingredient	Mobility
non hazardous materials	LOW (KOC = 22.28)
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging
disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

Insure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source Ingredient **Pollution Category**

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard Not Available

HSR Number	Group Standard

water(7732-18-5) is found on the following regulatory lists

"New Zealand Inventory of Chemicals (NZIoC)"

Version No: 1.2 Page 6 of 6 Issue Date: 30/10/2014 Print Date: 30/10/2014

RESENE STAINLOCK

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.