

SDS Revision Date: 04/25/2014

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity Standard Arterial

Alternate Names Arterial Embalming Chemical, Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name The Dodge Company, Inc

9 Progress Road Billerica, MA 01821

Emergency

CHEMTREC (USA) (800) 424-9300

Customer Service

The Dodge Company, Inc (800) 443-6343, (978) 600-2099

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

Acute Tox. 4;H302 Harmful if swallowed.

Acute Tox. 3;H311 Toxic in contact with skin.

Acute Tox. 2;H330 Fatal if inhaled.

Skin Corr. 1B;H314 Causes severe skin burns and eye damage.

Eye Dam. 1;H318 Causes serious eye damage.

Skin Sens. 1;H317 May cause an allergic skin reaction.

Muta. 2;H341 Suspected of causing genetic defects.

Carc. 1B;H350 May cause cancer.

STOT SE 2;H371 May cause damage to organs.

Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

SDS Revision Date:

04/25/2014



2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.











Danger

- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H341 Suspected of causing genetic defects.
- H350 May cause cancer.
- H371b May cause damage to organs if inhaled or swallowed.
- H371h May cause damage to organs in contact with skin.
- H411 Toxic to aquatic life with long lasting effects.

[Prevention]:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat / sparks / open flames / hot surfaces No smoking.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P284 Wear respiratory protection.

SDS Revision Date:

04/25/2014



[Response]:

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P309+311 IF exposed or you feel unwell Call a POISON CENTER or doctor / physician.

P310 Immediately call a POISON CENTER or doctor / physician.

P320 Specific treatment is urgent (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

P391 Collect spillage.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Formaldehyde CAS Number: 0000050-00-0	25 - 50	Carc. 1B;H350 Muta. 2;H341 Acute Tox. 3;H301 Acute Tox. 3;H311 Acute Tox. 3;H331 Skin Corr. 1B;H314 Skin Sens. 1;H317	[1][2]
Methanol CAS Number: 0000067-56-1	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370	[1][2]

^[1] Substance classified with a health or environmental hazard.



SDS Revision Date: 04/25/2014

- [2] Substance with a workplace exposure limit.
- [3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General Move victim to fresh air.

Call 911 or emergency medical service if deemed necessary.

Give artificial respiration if victim is not breathing.

Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Administer oxygen if breathing is difficult.

Remove and isolate contaminated clothing and shoes.

In case of contact with substance, immediately flush skin or eyes with running water for at

least 20 minutes.

In case of burns, immediately cool affected skin for as long as possible with cold water. Do

not remove clothing if adhering to skin.

Keep victim warm and quiet.

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Ensure that medical personnel are aware of the material(s) involved and take precautions

to protect themselves.

Inhalation Move victim to fresh air. Call emergency medical care. Apply artificial respiration if victim is

not breathing. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Administer oxygen if breathing is

difficult.

Eyes Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart

and seek medical attention.

Skin Remove and isolate contaminated clothing and shoes. In case of contact with substance,

immediately flush skin or eyes with running water for at least 20 minutes. Shower and wash

with soap and water. Keep victim warm and quiet.

Ingestion DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting

occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get

medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Reproductive or genetic defect hazard. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include



SDS Revision Date: 04/25/2014

headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation Fatal if inhaled. May cause damage to organs.

Eyes Causes serious eye damage.

Skin Toxic in contact with skin. May cause an allergic skin reaction. Causes severe skin burns

and eye damage.

Ingestion Harmful if swallowed.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, foam, carbon dioxide and water fog.

5.2. Special hazards arising from the substance or mixture

May form formaldehyde gas, carbon oxides, hydrogen, formic acid and various hydrocarbons. Incomplete combustion may also produce irritating smoke and toxic and/or irritating gases or fumes.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Flammable/combustible material.

May be ignited by heat, sparks or flames.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Vapor explosion hazard indoors, outdoors or in sewers.

Runoff to sewer may create fire or explosion hazard.

Containers may explode when heated.

Many liquids are lighter than water.

SDS Revision Date:

04/25/2014



May cause toxic effects if inhaled or ingested/swallowed.
Contact with substance may cause severe burns to skin and eyes.
Fire will produce irritating, corrosive and/or toxic gases.
Vapors may cause dizziness or suffocation.
Runoff from fire control or dilution water may cause pollution.

ERG Guide No. 132

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback.

Neutralize residual product in the spill area using sodium carbonate or sodium bicarbonate.

DO NOT USE COMBUSTIBLE MATERIALS.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Avoid contact with strong oxidizers, strong alkalies, strong mineral acids, phenol and urea. See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.



SDS Revision Date: 04/25/2014

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingestion	Source	Value
0000050-00-0	0000050-00-0 Formaldehyde		TWA 0.75 ppmSTEL 2 ppm
	ACGIH	STEL: 0.3 ppm Ceiling: 1 ppmS, A2, 1	
	NIOSH	Ca TWA 0.016 ppm C 0.1 ppm [15-minute]	
	Supplier	No Established Limit	
0000067-56-1 Methanol		OSHA	TWA 200 ppm (260 mg/m3)
	ACGIH	TWA: 200 ppmSTEL: 250 ppm Skin	
		NIOSH	TWA 200 ppm (260 mg/m3) ST 250 ppm (325 mg/m3) [skin]
	Supplier	No Established Limit	

Carcinogen Data

CAS No.	Ingestion	Source	Value
0000050-00-0 Formaldehyde		OSHA	Select Carcinogen: Yes
	NTP		Known: Yes; Suspected: Yes
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory Not necessary where area is properly ventilated.

Eyes Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the

splash of liquids.

Skin Overalls which cover the body, arms and legs should be worn. Skin should not be exposed.

All parts of the body should be washed after contact. Wear PVC or rubber gloves.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

SDS Revision Date:

04/25/2014



9. Physical and chemical properties

Appearance clear scarlet Liquid

Odor Pungent

Odor threshold Not Measured

pH 8.0-9.0

Melting point / freezing point Not Measured

Initial boiling point and boiling range 202-206F (94-97C)

Flash Point 137-141F (58-61C)
Evaporation rate (Ether = 1)
Less than Bu Acetate

Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: 7%

Upper Explosive Limit: 73%

Vapor pressure (Pa)Not MeasuredVapor DensityGreater than AirSpecific Gravity1.070-1.080Solubility in WaterComplete

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Decomposition temperature

Viscosity (cSt)

Not Measured

Not Measured

Not Measured

VOC % 98

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur

10.2. Chemical stability

Stable under the recommended storage and handling conditions prescribed. At higher temperatures, product may form formic acid and methanol.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid heat and open flame. Exposure to cold may cause precipitation of the polymer, will redissolve upon gentle heating.

SDS Revision Date:

04/25/2014



10.5. Incompatible materials

Avoid contact with strong oxidizers, strong alkalies, strong mineral acids, phenol and urea.

10.6. Hazardous decomposition products

May form formaldehyde gas, carbon oxides, hydrogen, formic acid and various hydrocarbons. Incomplete combustion may also produce irritating smoke and toxic and/or irritating gases or fumes.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Formaldehyde - (50-00-0)	800.00, Rat - Category: 4	270.00, Rabbit - Category: 3	0.578, Rat - Category: 2	No data available	168.00, Rat - Category: NA
Methanol - (67-56-1)	143.00, Human - Category: 3	No data available	No data available	No data available	64,000.00, Rat - Category: NA

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed.
Acute Toxicity (skin)	3	Toxic in contact with skin.
Acute Toxicity (inhalation)	2	Fatal if inhaled.
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)		Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	2	Suspected of causing genetic defects.
Carcinogenicity	1B	May cause cancer.

SDS Revision Date:

04/25/2014



Reproductive Toxicity		Not Applicable
Specific target organ systemic toxicity (single exposure)	2	May cause damage to organs.
Specific target organ systemic Toxicity (repeated exposure)		Not Applicable
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Formaldehyde - (50-00-0)	1.41, Oncorhynchus mykiss	5.80, Daphnia pulex	0.788 (96 hr), Ulva pertusa
Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.



SDS Revision Date: 04/25/2014

14. Transport information

14.1. UN number UN1198

14.2. UN proper shipping name Formaldehyde solutions, flammable

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

DOT Proper Shipping UN1198, Formaldehyde IMDG Proper Formaldehyde solutions, flammable, 3, Shipping Name solutions, flammable

Ш

DOT Hazard Class 3 IMDG Hazard Class 3

DOT Label 3, 8 **Sub Class** Not Applicable

UN / NA Number UN1198

DOT Packing Group ||| IMDG Packing Group |||

CERCLA/DOT RQ 48 gal. / 400 lbs.

14.4. Packing group

14.5. Environmental hazards

IMDG Marine Pollutant: Yes (Formaldehyde)

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D1A E

US EPA Tier II Hazards Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): Yes

SDS Revision Date: 04/25/2014

EPCRA 311/312 Chemicals and RQs (lbs):

Formaldehyde (100.00)

Methanol (5,000.00)

EPCRA 302 Extremely Hazardous:

Formaldehyde

EPCRA 313 Toxic Chemicals:

Formaldehyde

Methanol

Proposition 65 - Carcinogens (>0.0%):

Formaldehyde

Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Formaldehyde

Methanol

Penn RTK Substances (>1%):

Formaldehyde

Methanol



SDS Revision Date: 04/25/2014

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.

This is the first revision of this SDS format, changes from previous revision not applicable.

This Safety data Sheet was prepared using information provided by/obtained from the Dodge Chemical Company Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company, Inc. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company, Inc.

End of Document