

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupation Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY

STATIC KILL (120320)

*Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.*

Section I

D.O.T. Hazard Class: CONSUMER COMMODITY ORM-D

Manufactured For:

Beaver Research Company

Emergency Telephone Number

1-800-255-3924 (Chem-Tel)

Address (Number, Street, City, State, and ZIP Code)

3700 E. Kilgore Road, Portage, MI 49002

Telephone Number For Information

269-382-0133

HMIS RATINGS:

0-Minimal 3-Serious

1-Slight 4-Extreme

2-Moderate

Health: 1

Fire: 3

Reactivity: 0

Personal Protection: B

Date Prepared

03/25/03

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical
Identity; Common Name(s))

CAS No.

PEL

TWA
TLV

Other Limits
Recommended

%
(optional)

Isoparaffinic Hydrocarbon

64741-66-8

400ppm

400ppm

40-60

Isopropyl Alcohol

67-63-0

400ppm

400ppm

05-10

Liquified Petroleum Gas

68476-85-7

1000ppm

1000ppm

40-60

Section III - Physical/Chemical Characteristics

Boiling Point

~140°F

Specific Gravity (H₂O = 1)@75°F

0.735

Vapor Pressure of can (psig @ 70°F)

50

Melting Point

N/A

Vapor Density (AIR = 1)

>1

Evaporation Rate
(Butyl Acetate = 1)

N/A

Solubility in Water

pH

N/A

Slight

Total VOC

95%

Appearance and Odor

Clear liquid, solvent odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

30°F (T.O.C.)

Flammable Limits

Extremely Flammable Spray

LEL

N/A

UEL

N/A

Extinguishing Media

Foam, CO₂, Dry Media

Special Fire Fighting Procedures

Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards

Exposure to temperature above 120°F may cause bursting.

Section V - Reactivity Data

Stability

Unstable

Conditions to
Avoid

N/A

Stable

X

Incompatibility (Materials to Avoid)

Avoid contact with strong oxidizing agents.

Hazardous Decomposition or Byproducts

Carbon Dioxide, Carbon Monoxide

Hazardous

May Occur

Conditions to
Avoid

None

Polymerization

Will Not Occur

X

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes
Health Hazards (Acute and Chronic)			
Eyes: May cause slight irritation but does not injure eye tissue.			
Skin: Frequent or prolonged contact may cause irritation.			
Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.			
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis. Minimal toxicity.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No
Signs and Symptoms of Exposure			
See above "Health Hazards".			
Medical Conditions Generally Aggravated by Exposure			
N/A			
Emergency and First Aid Procedure			
Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.			
Skin: Wash with soap and water. If irritation persists seek medical attention.			
Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.			
Ingestion: Do not induce vomiting. Seek medical attention immediately.			

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled	
Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.	
Waste Disposal Method	
Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.	
Precautions to be Taken in Handling and Storage	
KEEP OUT OF REACH OF CHILDREN. For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F.	
Other Precautions	
N/A	

Section VIII - Control Measures

Respiratory Protection (Specify Type)				
None needed for proper use in accordance with label directions.				
Ventilation	Local Exhaust	Yes	Special	N/A
	Mechanical(General)	N/A	Other	N/A
Protective Gloves			Eye Protection	
None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.			None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.	
Other Protective Clothing or Equipment				
N/A				
Work/Hygienic Practices				
N/A				

The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.