U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

		3110 0		ng (25 Ci 11 1515, 15	10, 1917)						
SECTION I											
MANUFACTURER"	S NAME				EMERGENCY TELEPHON	E NO.					
White Che	mical Internationa	il, I	nc.	(713) 240-3626							
760 Indus	Street City. State and 71P Costrial Rd. Sugar Li	and,	Texas	77478							
Surfactant	CHEMICAL NAME AND SYNONYMS MIXTURE OF TRADE NAME AND SYNONYMS Surfactants water softening agents										
CHEMICAL FAMILY Detergent			Propietary Blend								
Parameter and the state of the											
SECTION II - HAZARDOUS INGREDIENTS											
PAINTS, PRESER	RVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND	METALLIC COATINGS	%	TLV (Units)				
PIGMENTS	Not Applicable			BASE METAL Not	Applicable						
CATALYST	Not Applicable	_		1	Applicable	ļ					
VEHICLE	Not Applicable		·		S Not Applicable						
SOLVENTS	Not Applicable			FILLER METAL PLUS COATING OR C	ORE FLUX NOT App.						
DITIVES	Not Applicable			OTHERS							
OTHERS											
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES											
				**							
				<u> </u>		1					
						-					
						-					
29	SEC	TION	V III - P	HYSICAL DATA							
BOILING POINT (°F.)			13°F	SPECIFIC GRAVITY (H2O=1)			1.04				
VAPOR PRESSURE	(mm Hg.)			PERCENT, VOLATILE BY VOLUME (%)	E gg						
VAPOR DENSITY (A	NR=1)			EVAPORATION RAT							
SOLUBILITY IN WA	TER	Sol	uble								
APPEARANCE AND ODOR Light Blue, Mild											
SECTION IV - FIRE AND EXPLOSION HAZARD DATA											
FLASH POINT (Metr	None		,	FLAMMABLE LIM	ITS Lel		Uel				
Not Applicable											
Not Applicable Not Applicable Not Applicable											
UNUSUAL FIRE AN	D EXPLOSION HAZARDS	- N	Tone								
			one								

		S	ECTION	v	- HEA	ALTH HAZAF.C	DATA	
THRESTOLD LIMIT	Ŧ V2		tablish			300 132		
EFFECTS OF OVE	REXPO	JRE						
cause irrit	 ation	of the ev	appiic	atı	on ca	in result in i	ngestion of product which may	
T EMPRIENCY AND	FIRST	AID BOOKED!	IDEC					
Remove fro	om sl	cin by was	shing th	nor	ough]	y with water	. Should eve contact occur,	
irritation o	igniv	with clea	an wate	er f	or at	least 15 min	utes. Consult a physician if	
1111tation 0	ccur	S. 				<u> </u>		
390			SECTIO	NI N	// 5			
STABILITY	1		SECTIO	CTION VI - PEACTIVITY DATA				
	UNSTABLE			CONDITIONS TO AVOID				
INCOMPATABILITY	STA		X					
		•						
HAZARDOUS DECO	IZCAWC	TION PRODUC	CTS		<u> </u>			
HAZARDOUS		MAY OCCUR				CONDITIONS TO	AVOID	
POLYMERIZATION		WILL NOT O	CCUR		X			
			<u> </u>			<u> </u>	-	
	70715			81				
		SECTI	IIV NO	- S	PILL	OR LEAK PRO	CEDURES	
STEPS TO BE TAKE	NINC							
T31 1								
Flush with	ı wat	er.	-		•			
WASTE DISPOSAL N	METHO	<u> </u>	·			٠,		
		None						
						·		
-								
•		SECTIONIN	(111 CD	1501	AL D	207507		
RESPIRATORY PRO	TECTIO	N /S-orie to	111 - SP	EUI	AL PI	ROTECTION IN	FORMATION	
RESPIRATORY PRO fresh air su	ply ·	<u> specijy iyp</u> r <u>hen usi</u> n	g spra:	raj Vaj	pprov	ed respirat etor in an en	closed area	
VENTILATION	pply when using spray applicator						SPECIAL	
	MECHANICAL (General)						OTHER	
Rubber gloves						EYE PROTECTION		
OTHER PROTECTIVE EQUIPMENT Chemical goggles								
		SEC	CTION I	X -	SPEC	IAL PRECAUT	IONS	
PRECAUTIONS TO BE	E TAKE							
				110		None		
THER PRECAUTION	15							
								

PAGE (2)