

Page 1 of 6 **WP-008**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/31/2013

.1	Product Name:		DENIO	ALELUD AS	-0	IDENTII					
				ON FLUID OF	<u> </u>						
2	Chemical Name:	Hydrau	lic Oils								
3	Synonyms:	NA .		0=0							
4	Trade Names:	-	nsion Fluid								
5	Product Use:		otive Lubric	ant							
6 7	Distributor's Name: Distributor's Address:		pac, Inc.	t N 0 A O A	500 LIOA						
8	Emergency Phone:			eet, Newark, CA 94		250) 200	2500 (0	ONITO (•	
				1 (800) 535-505		352) 323-	3500 (C	ONIRA	ACT 84261	1)	
9	Business Phone / Fax:	+1 (510	J) 608-5525	5 / +1 (510) 742-926	2						
			2	HAZARDS I	DENT	FICATION	ON				
1	Hazard Identification:	This nr		ssified as a hazard				ierous do	nds accordin	na to	
		DANGI ALLER Hazard cause a Precau SWALI induce should soap a P321 - contan	ER! MAY CGIC SKIN I Statement an allergic s stionary Sta LOWED: In vomiting, not be allo ind water. – For spec inated clo	riteria of [NOHSC: 1 BE FATAL IF SWA REACTION. <u>s</u> (H): H304 – May kin reaction. tements (P): P280 mediately call a P P261 - Avoid brea wed out of the work P333+P313 – If sk cific treatment – se thing before reuse to licenses treatme	be fatal in the property of th	f swallowed protective g ENTER or t/sprays. P 302+P352 - n or rash oc 1 4 of this 5 - Store	and enter loves/eye doctor/ph 272 - Co - IF ON S curs: Ge Safety D locked u	ers airway e protectio ysician. ontaminate KIN: Wa t medical oata Shee ep. P50	ys. H317 – I on. P301+310 P301 - Do I ded work clot ash with plen advice/atten et. P363 V	May 0: IF NOT thing ty of ition. Vash	
2	Effects of Exposure:	Eyes: Skin: Ingesti	m Th <u>on</u> : If ef	nis product can cau ists. nis product can caus swallowed, no sign fect. If aspirated into o significant advers	se mild, tra ificant adv the lung	ansient skin verse health s, liquid can	irritation veffects a cause se	with short- ire anticip vere lung	-term exposu pated. Ingesti damage or c	ire. ion can ca death.	ause a laxativ
		Illiaac		oduct. Aspiration of							posure to trii
3	Symptoms of Overexposure:		 								
4	Acute Health Effects:	Modera	te irritation	to eves. Moderate	irritation to	o skin near a	affected a	reas.			
5	Chronic Health Effects:	Moderate irritation to eyes. Moderate irritation to skin near affected areas. Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.									
6	Target Organs:		•	ratory tract, skin.							
_	·	, ,		· · · · · · · · · · · · · · · · · · ·							
		3. C	OMPOS	SITION & INC	REDI	ENT INF	ORM	ATION	I		
		T 3. 3	1						LIMITS IN AIR (1	mg/m³)	
						ACGIH		OHSC	OSH		
					1		1 -	opm	ppr	m	
						ppm			pp.	",	
	IICAL NAME(S)	CAS No	RTECS NA	EINECS NO	0/_		ES-	ES- ES-			OTHER
	ICAL NAME(S) ROLEUM OILS MIXTURE	CAS No.	RTECS No	o. EINECS No.	% 60-100	TLV STEL	ES- TWA S		K PEL STEL	L IDLH	OTHER

NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2010 format.



7.2

7.3

Storage & Handling:

Special Precautions:

SAFETY DATA SHEET

Page 2 of 6

WP-008 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.0 SDS Revision Date: 12/31/2013 4. FIRST AID MEASURES 4 1 First Aid: DO NOT INDUCE VOMITING. Contact Infotrac +1 (800) 535-5053 or the nearest Poison Control Ingestion: Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 Eyes: minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists Skin: and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned. Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial Inhalation: respiration. Seek immediate medical attention. 4.2 Medical Conditions Aggravated by Persons with pre-existing central nervous system (CNS) HEALTH Exposure: disease, neurological conditions, skin disorders, chronic **FLAMMABILITY** 1 respiratory diseases, or impaired liver or kidney function should PHYSICAL HAZARDS 0 avoid exposure. PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers. Avoid all ignition sources such as sparks, heat and open flames. Product or residue can ignite explosively. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO₂, and NOx), smoke, hydrocarbons and their derivatives Extinguishing Methods: 5.2 Water, Foam, CO₂, Dry Chemical, low velocity water fog, Halon (if permitted), 5.3 Firefighting Procedures: As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Treat as hot oil. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon, and/or nitrogen, hydrocarbons and/or derivatives. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective 6.1 Spills Equipment (PPE). Use safety glasses or safety goggles and face shield, use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a noncombustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal Large Spills: Keep incompatible materials (e.g., oxidizers, strong acids, alkalis) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. . Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters. 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Immediately clean-up and decontaminate any spills or residues.

substances (see Section 10). Protect containers from physical damage.

Empty containers may retain hazardous product residues.

Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Store in closed containers. Avoid temperatures above 40°C (120°F). Keep away from incompatible



10.2

10.3

10.4

10.5

Hazardous Decomposition Products:

Hazardous Polymerization:

Incompatible Substances:

Conditions to Avoid:

SAFETY DATA SHEET

Page 3 of 6 **WP-008**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.0 SDS Revision Date: 12/31/2013 **EXPOSURE CONTROLS & PERSONAL PROTECTION** 8.1 Ventilation & Engineering Controls: Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eve-wash station) 8.2 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.3 Eye Protection: Avoid eye contact. Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU) 8.4 Hand Protection: Wear protective, chemical-resistant gloves (e.g., neoprene, nitrile) when using or handling this product. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. 8.5 Body Protection: Not required under normal conditions of use. A chemical resistant apron and/or protective clothing are recommended when handling or using large quantities (e.g., > 5 gallons (18.9 L)) of this product. Protective working garments should meet EU Standard EN 344 or equivalent. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Viscous green liquid 9.2 Odor Mild petroleum odor 9.3 Odor Threshold: NA 9.4 NA 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling Range: ≥ 250 °C (≥ 482 °F) ≥ 110 °C (≥ 230 °F) Flashpoint 9.8 Upper/Lower Flammability Limits: NA 9.9 Vapor Pressure: NA Vapor Density: 9.10 NA 9.11 Relative Density: NA 9.12 Solubility: Immiscible 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature NA Viscosity 9 16 NA 9 17 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stability This product is stable under normal storage and use conditions.

Oxides of carbon (CO, CO₂), sulfur (SO_x), and nitrogen (NO_x)

Open flames, high heat and direct sunlight.

Strong oxidizing agents, acids or alkalis.

Will not occur



Page 4 of 6 **WP-008**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.0 SDS Revision Date: 12/31/2013 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry: Inhalation: NO Absorption: YES Ingestion: YES 11 2 Toxicity Data: Based on animal testing from similar materials & products, the acute toxicity of this product is expected to be: Distillates, Petroleum, Solvent-Refined, Heavy Paraffinic - LD50 (oral, rat) > 5000 mg/kg; LD50 (dermal, rabbit) > 2000 mg/kg; Distillates, Petroleum, Hydrotreated, Heavy Paraffinic - LD₅₀ (oral, rat) > 5000 mg/kg; LD₅₀ (dermal, rabbit) > 2000 mg/kg. 11.3 Acute Toxicity: See section 2.4. Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. 11.4 Chronic Toxicity: See section 2.5 11.5 Suspected Carcinogen: This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. Dimethyl sulfoxide (DMSO), if present at all, is in a concentration of less than 1.0 %. Reproductive Toxicity: 11.6 This product is not reported to cause reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenicity effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 2.3 11.8 Biological Exposure Indices: NA Physician Recommendations: The viscosity range of the product(s) represented by this MSDS is between 100 and 400 SUS at 100°F. Accordingly, upon ingestion there is a moderate risk of aspiration. Careful gastric lavage or emesis may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl. Effects on Plants & Animals: 12.2 An environmental fate analysis has not been conducted on this specific product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products. 12.3 Effects on Aquatic Life: Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway can result in a loss of marine life or create an anaerobic environment. This material contains phosphorus which is a controlled element for disposal in effluent waters in most sections of North America. Phosphorus is known to enhance the formation of algae. Severe algae growth can reduce oxygen content in the water possibly below levels necessary to support marine life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal, state, provincial and local regulations. 13.2 Special Considerations: Used oil may be recyclable. Contact the federal, state or provincial environmental authority to determine suitability for recycling and or proper disposal requirements. If the material is unsuitable for recycling or reclamation, enclosed-controlled incineration is recommended unless otherwise prohibited by local statute. European Waste Catalog: 13 01 10 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGT, ADR and the 49 CFR (GND): NOT REGULATED 14.2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): NOT REGULATED 14.4 TDGR (Canadian GND): **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** SCT (MEXICO): 14.6 **NOT REGULATED** ADGR (AUS): 14.7 **NOT REGULATED**



Page 5 of 6 **WP-008**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/31/2013

Prepa	ared to USHA, ACC, ANSI, NUHSO	, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.0 SDS Revision Date: 12/31/2013
		15. REGULATORY INFORMATION
15.1	SARA Reporting Requirements:	This product does not contain any components subject to Section 313 reporting requirements.
15.1	SARA Threshold Planning Quantity:	NA
15.2	TSCA Inventory Status:	
15.4	CERCLA Reportable Quantity (RQ):	All components of this product are listed in the TSCA Inventory or are exempt. NA
15.5	Other Federal Requirements:	
15.6	Other Canadian Regulations:	NA This graduat has been placed as a second as the beauty at the Controlled Products
15.0	Other Canadian Regulations.	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects).
15.7	State Regulatory Information:	No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. Irritant (Xi). Risk Phrases (R): R36/37/38-65-66 – Irritating to eyes, respiratory system and skin. Harmful – may cause lung damage if swallowed. Repeated exposure my cause skin dryness or cracking. Safety Phrases (S): S(2)-23-24-62 - Keep out of the reach of children. Do not breathe mists/vapors/spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label where possible.
16.1	Other Information:	16. OTHER INFORMATION DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. May cause an allergic skin reaction.
10.1	Otto moments.	Wear protective gloves/eye protection. If swallowed, immediately call a Poison Center or doctor/physician. Avoid breathing mist/sprays. If skin irritation or rash occurs: Get medical advice/attention. KEEP OUT OF REACH OF CHILDREN .
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Worldpac's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
16.4	Prepared for:	Worldpac, Inc. 37137 Hickory Street Newark, CA 94560 USA Tel: +1 (510) 608-5525 Fax: +1 (510) 742-9262 http://www.worldpac.com
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, OR 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com



Page 6 of 6 **WP-008**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/31/2013

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists	
TLV Threshold Limit Value		
OSHA U.S. Occupational Safety and Health Administration		
PEL Permissible Exposure Limit		
IDLH Immediately Dangerous to Life and Health		

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α		
В		
С		
D		
Е		
F		





Splash Goggles



Full Face Respirator

Synthetic Apron



Dust & Vapor Half-Mask Respirator







Dust Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR No Results	
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:				
Autoignition Temperature Minimum temperature required to initiate combustion in air with no source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source			

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ох	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{lo} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	PA U.S. Environmental Protection Agency	
DSL	Canadian Domestic Substance List	
NDSL	Canadian Non-Domestic Substance List	
PSL	Canadian Priority Substances List	
TSCA U.S. Toxic Substance Control Act		
EU	European Union (European Union Directive 67/548/EEC)	
WGK	Wassergefährdungsklassen (German Water Hazard Class)	

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)		\odot	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

1		M	*		9	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

•				\Diamond			\Diamond		*
	GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
	Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment