MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION

PRODUCT NAME: Synthetic Seal

PRODUCT TYPE:Vehicle Polishing Compound

SECTION	II –	INGREE	DIENTS
---------	------	--------	--------

INGREDIENT	C.A.S. NUMBER	PEL
Water	7732-18-5	No limits established
Odorless Mineral Spirits	64741-65-7	100 ppm TLV
Polydimethylsiloxane	63148-62-9	No limits established
Carnauba Wax	8015-86-9	No limits established
Organophilic Clay	71011-27-3	No limits established

SECTION III - PHYSICAL DATA

APPEARANCE: Light green cream, spearmint scented.

VAPOR PRESSURE: .0005 PSIA@ 68 VAPOR DENSITY (AIR=1): Greater than 1.

F

SPECIFIC GRAVITY: 0.99 pH: 6.5-7.5

BOILING POINT: 210 degrees F. **SOLUBILITY IN WATER:** Dispersible.

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT:	>180 degrees F.
	Water fog or fine spray. Carbon dioxide, Dry chemical
or Alcohol resistant foam.	
SPECIAL FIRE FIGHTING PROCED	URES:Firefighters working in areas
	be equipped with an approved, fully enclosed SCBA.
UNUSUAL FIRE AND EXPLOSION F	HAZARDS:None known.

SECTION V – REACTIVITY DATA

STABILITY:	Stable under normal conditions.
HAZARDOUS POLYMERIZATION:	This product not known to polymerize.
INCOMPATIBILITY:	Do not mix with other chemicals.
HAZARDOUS BYPRODUCTS	Carbon monoxide, carbon dioxide.

SECTION VI - HEALTH DATA

CHON VI - REALTH DATA
Inhalation, skin absorption, or ingestion.
Not listed by IARC, NTP or OSHA.
TED:May aggravate pre-existing dermatitis.
Not likely to be inhaled in hazardous amounts. Avoid
in adequate ventilation in the work area.
Swallowing even small amounts may be harmful.
vomiting and central nervous system depression.
May cause severe eye irritation.
This product may cause irritation if not removed from
cause central nervous system depression.

SECTION VII - FIRST AID

BREATHING (INHALATION):lf victim shows signs of discomfort or irritation, remove
to fresh air. If symptoms persist, get immediate medical attention.
SWALLOWING (INGESTION):DO NOT INDUCE VOMITING! Drink a large quantity of
water or milk. Do not attempt to give liquids to an unconscious person. Get immediate medical
attention!
EYES:Flush eyes with a large quantity of fresh water for at
least 15 minutes. If irritation persists, consult a physician.
SKIN (DERMAL):Flush from skin and clothing with large amounts of fresh
water. If irritation persists, consult physician. Wash contaminated clothing before wearing.
SECTION VIII - EMPLOYEE PROTECTION
RESPIRATORY PROTECTION: Not usually needed. Vapors not normally harmful.
PROTECTIVE CLOTHING:Nitrile or PVC gloves, and chemical splash goggles.
ADDITIONAL MEASURES:Do not place this product in an unmarked container!
Keep away from children! Spilled material is slippery. ATTENTION: Empty containers retain
vapor and product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder,
drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of
ignition. Do not reuse empty container.
SECTION IX – SPILL AND DISPOSAL DATA
SPILL: Dike to prevent spillage into streams or sewer systems.
Consult local, state and federal authorities.
WASTE DISPOSAL:As recommended by local, state and federal authorities
HANDLING & STORAGE PRECAUTIONS:Store in a cool, well ventilated
area. Avoid overheating or freezing.
SECTION X - OTHER REGULATORY INFORMATION
PROPER SHIPPING NAME: Not D.O.T. NFPA HEALTH: 1
regulated in these container sizes. NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 0
NFPA OTHER: None
SECTION XI – PRECAUTIONARY STATEMENTS