# SAFETY DATA SHEET

### SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name:

Henry Schein Tartar and Stain Remover

Product Code: MSDS Manufacturer Number: 100-4263 G069

Other means of identification:

Synonyms:

Sulfamic Acid Solution

Recommended use of the chemical and restrictions on use:

Product Use/Restriction:

Tartar and stain removing ultrasonic solution.

Chemical manufacturer address and telephone number:

Manufacturer Name:

Henry Schein, Inc.

Address:

135 Duryea Road Melville, New York 11747

USA

General Phone Number:

1-800-472-4346

Emergency phone number:

Emergency Phone Number:

Chemtrec @ 1-800-424-9300

# SECTION 2 : HAZARD(S) IDENTIFICATION

# Classification of the chemical in accordance with A61910.1200(d)(f):

GHS Pictograms:



Signal Word:

DANGER.

GHS Class:

Serious Eye Damage. Category 1. Skin corrosion, Category 1.

Hazard Statements:

H318 - Causes serious eye damage. H314 - Causes severe skin burns and eye damage.

Precautionary Statements:

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do not induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

preating.
P305+P331+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P321 - Specific treatment (see ... on this label).
P363 - Wash contaminated dothing before reuse.

P405 - Store locked up.
P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

# Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure:

Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye:

Corrosive. Will cause eye burns and permanent tissue damage.

Inhalation:

Skin:

Severely irritating; may cause permanent skin damage. May cause severe respiratory system irritation.

Ingestion:

Harmful if swallowed. Corrosive to the gastrointestinal tract.

Chronic Health Effects:

Prolonged skin contact causes burns.

Signs/Symptoms:

Repeated or prolonged inhalation may cause toxic effects.

Depending on solution concentration, material may be corrosive to skin, mucous membranes and eyes. Vapors may cause respiratory irritation.

Target Organs:

Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions:

May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

# SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

**Chemical Name** 

CAS#

Ingredient Percent

EC Num

5 - 10 by weight

Notes:

The remaining components of this product are non-hazardous or are in a small enough quantity as to not meet regulatory thresholds for disclosure.

# SECTION 4: FIRST AID MEASURES

#### Description of necessary measures:

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact:

Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes.

Get medical attention if irritation develops or persists.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

# SECTION 5: FIRE FIGHTING MEASURES

### Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media:

Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.

# Special protective equipment and precautions for fire-fighters:

Protective Equipment:

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

#### **NFPA Ratings:**

NFPA Health:

NFPA Flammability:

NFPA Reactivity:

# SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures:

Personnel Precautions:

Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in section 8.

Environmental precautions:

**Environmental Precautions:** 

Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and deaning up:

Methods for containment:

Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by

covering, diking or other means. Provide ventilation.

Methods for cleanup:

Clean up spills immediately observing precautions in the protective equipment section. Provide

### SECTION 7: HANDLING and STORAGE

# Precautions for safe handling:

Handling:

Corrosive. Use proper personal protective equipment as listed in section 8. Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Wash hands thoroughly after handling.

Hygiene Practices:

Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

# Conditions for safe storage, including any incompatibilities:

Storage:

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use. Keep only in the original, comosive resistant container and store locked up.

### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES

Henry Schein Tartar and Stain Remover Revision:: 5/1/2015

Product Code: G069

Guideline ACGIH: Exposure limits are not established Guideline OSHA: Exposure limits are not established

Appropriate engineering controls:

Use appropriate engineering control such as process enclosures, local exhaust Engineering Controls:

use appropriate engineering control such as process encousities, rocal exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Individual protection measures:

Eye/Face Protection:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or dothing. Skin Protection Description:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide

adequate protection.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Other Protective:

PPE Pictograms:

Respiratory Protection:





# SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liquid. Color: Clear Odor: Sweet,

Odor Threshold: Not determined. Boiling Point: 214°F (101°C) Melting Point: Not determined.

Specific Gravity: 1.09 (Ref: water = 1).

Solubility: Very soluble. Vapor Density: Not determined. Vapor Pressure: Not determined.

Percent Volatile: 86%

Evaporation Rate: Not determined. pH: 0.3 - 0.7

Viscosity: Not determined. Coefficient of Water/Oil Not determined.

Distribution:

Flammability: Not determined. Flash Point: 210 °F (99°C)

Flash Point Method: Tag Closed Cup (T.C.C).

Lower Flammable/Explosive Limit: Not determined. Upper Flammable/Explosive Limit: Not determined. Not determined. Auto Ignition Temperature: Oxidizing Properties: Not determined. VOC Content: Not determined.

# SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Will not occur.

Conditions To Avoid:

Conditions to Avoid: Avoid contact with incompatible materials.

Incompatible Materials:

Henry Schein Tartar and Stain Remover Revision:: 5/1/2015

Product Code: G069

Strong acids,

# SECTION 11: TOXICOLOGICAL INFORMATION

#### TOXICOLOGICAL INFORMATION:

#### Sulfamic Acid 99.8% Technical Grade:

Eye: Administration into the eye - Rabbit Standard Draize test: 20 mg [Moderate]

Administration into the eye - Rabbit Standard Draize test: 250 ug/24H [Severe] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 3160 mg/kg [Details of toxic effects not reported other

than lethal dose value] (RTECS)

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

#### SECTION 13: DISPOSAL CONSIDERATIONS

#### Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous

waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

# SECTION 14: TRANSPORT INFORMATION

UN number: 3262

UN proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s

Transport hazard dass(es): 8
Packing group: II

Notes:

The data provided in this section is for information only. Please apply the appropriate regulations to

properly classify your shipment.

# SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

# Sulfamic Acid 99.8% Technical Grade :

TSCA Inventory Status: Listed
Canada DSL: Listed

# SECTION 16: ADDITIONAL INFORMATION

HMIS Fire Hazard: 3
HMIS Fire Hazard: 1

HMIS Reactivity:

HMIS Personal Protection:
Other Information:

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). The customer is responsible for determining the appropriate PPE to be used for the task.

the task. The National Fire Protection Association (NFPA) rating system is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. NFPA hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. NFPA hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. The NFPA system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Henry Schein Tartar and Stain Remover Revision:: 5/1/2015



HMIS	
Health Hazard	3
Fire Hazard	
Reactivity	2
Personal Protection	х

SDS Revision Date:

May 01, 2015

MSDS Revision Notes:

Supercedes MSDS 7/30/2014

MSDS Author:

Regulatory department

Disclaimer:

We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of the product are not within our control it is the user's obligation to determine the conditions of safe use of the product,

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

Henry Schein Tartar and Stain Remover Revision:: 5/1/2015 Product Code: G069