# MATERIAL SAFETY DATA SHEET

# TEMPFIL PASTE PRODUCTS

Inlay / Onlay

### 1 - IDENTIFICATION

**Manufacturer:** Kerr Corporation

Address: 1717 West Collins Avenue
City, State, Zip: Orange, CA 92867-5422
Telephone: 1-800-KERR-123

**Emergency:** Chemtrec 1-800-424-9300

**Date Prepared:** June 6, 2005

# 2 - COMPOSITION INFORMATION

### **Hazardous Ingredients**

Uncured Diacrylate Ester Monomers

CAS # PEL TLV %
N/A N/A 35-45

## **Other Ingredients**

Non-hazardous inert mineral fillers, non-hazardous activators and stabilizers.

### 3 - PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point: N/D** 

Specific Gravity ( $H_20 = 1$ ):  $\sim 2$ Vapor Pressure (mm Hg): N/D

Melting Point: N/D

Vapor Density (AIR = 1): N/D Solubility in Water: Insoluble

Appearance and Odor: Colored paste with fruity ester-like odor.

### 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/D

Flammable Limits: LEL: N/A UEL: N/D

**Extinguishing Media:** Chemical foam, CO<sub>2</sub>, dry chemical **Special Fire Fighting Procedures:** Wear self contained breathing

apparatus.

**Unusual Fire and Explosion Hazards:** Heat can cause polymerization

with rapid release of energy.

### 5 - REACTIVITY DATA

Stability: Stable if stored as directed.

Incompatibility (Material to Avoid): Reducing and oxidizing agents,

peroxides and amines.

Hazardous Decomposition Products: Oxides of carbon

Hazardous Polymerization: May occur

Conditions to Avoid: Heat, light, aging and sources of contamination.

# 6 - HEALTH HAZARD DATA

### **Routes of Entry:**

**Skin:** Prolonged or repeated exposure to uncured material may cause irritation or skin rash especially in sensitive individuals.

**Eyes:** May cause irritation and damage if not removed promptly. **Inhalation:** Prolonged or excessive inhalation may cause respiratory

tract irritation.

**Ingestion:** Uncured material may be harmful if swallowed.

Carcinogenicity - NTP: No

IARC Monographs: No OSHA Regulated Carcinogen: No

## 7 - EMERGENCY FIRST AID PROCEDURES

Skin: Wash thoroughly with soap and water.

**Eyes:** Flush with water for 15 minutes including under eyelids. **Inhalation:** Remove to fresh air. Get medical attention if discomfort

persists.

**Ingestion:** Rinse mouth out with water. Do not induce vomiting. Seek

medical attention.

# 8 - PRECAUTIONS FOR SAFE HANDLING & USE

**Steps to be taken in case material is released or spilled:** Absorb spills with inert material. Keep spilled material out of sewers.

**Waste Disposal Method:** Unpolymerized (uncured) material may be RCRA hazardous waste. Incinerate uncured material in accordance with all federal, state and local regulations.

**Precautions to be taken in handling and storing:** Store in a cool, dry place away from heat light and ignition.

#### 9 - CONTROL MEASURES

**Respiratory Protection (Specify Type):** Avoid prolonged or excessive breathing of vapors of uncured material.

VENTILATION:

Local Exhaust: Good general ventilation should be sufficient to control airborne levels of vapors released by uncured material.

Mechanical (General): Good general ventilation recommended.

Protective Gloves: Protective gloves recommended when contacting

uncured material.

Eye Protection: Safety glasses recommended

Other Protective Clothing or Equipment: N/A

**Work/Hygiene Practices:** Handle in accordance with good personal hygiene and safety practices. These practices include avoiding

unnecessary exposure to uncured material.

### 10 - TRANSPORTATION INFORMATION

Not DOT Regulated

# 11 - SPECIAL INFORMATION

#### HMIS(Hazardous Material Identification System) Rating:

H2 F1 R2 PPE-Gloves and safety glasses. Hazard information relates only to uncured material.

[HMIS Index: 4 - Severe Hazard; 3 -Serious Hazard;

2 - Moderate Hazard; 1 - Slight Hazard; 0 - Minimum Hazard]

Note: Hazard information contained on this MSDS form relates only to material in its uncured state. Thorough biocompatibility and toxicity testing of the cured material and its extracts have demonstrated that the material is non-toxic.

Note: This MSDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product. The information in this MSDS is, to the best of our knowledge, believed to be accurate.