



# MATERIAL SAFETY DATA SHEET PRODUCTS

CODE NO. 003-T

ORIGINAL ISSUE DATE: 1-7-86 REVISED:

## I. IDENTIFICATION


INFORMATION & EMERGENCY TELEPHONE NUMBER  
(313) 755-1900PRODUCT NAME:  
TITANIUM ALLOY (6 Al, 6 V, 2 Sn)

### NEPA HAZARD RATING

4 = Extreme  
3 = High  
2 = Moderate  
1 = Slight  
0 = Insignificant

Flammability

Reactivity



### DISTRIBUTOR:

TITANIUM & ALLOYS CORP.  
21870 Hoover Road  
Warren, Michigan 48089

COMMON NAME:

TITANIUM 6-6-2

## II. INGREDIENTS AND RECOMMENDED OCCUPATIONAL EXPOSURE LIMITS

NOTE: Products under normal conditions do not present an inhalation, ingestion or contact health hazard. However, operations, such as, burning, welding, sawing, brazing, grinding, and possibly machining, etc., which results in elevating the temperature of the product to or above its melting point or results in the generation of airborne particulates, may present health hazards.

| BASE METAL, ALLOYING ELEMENTS | % WEIGHT | EXPOSURE LIMITS      |                      | HAZARD DATA     |
|-------------------------------|----------|----------------------|----------------------|-----------------|
|                               |          | OSHA PEL             | ACGIH TLV            |                 |
| TITANIUM                      | 86.0%    | 20 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> | See Section VI. |
| ALUMINUM                      | 6.0      | 20 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> |                 |
| VANADIUM                      | 6.0      | NS                   | .5 mg/m <sup>3</sup> |                 |
| TIN                           | 2.0      | 2 mg/m <sup>3</sup>  | 2 mg/m <sup>3</sup>  |                 |

NOTE: All commercial metals contain small amounts of various elements in addition to those that are specified. These small quantities, frequently referred to as "trace" or "residual" elements, generally originate in the raw materials, primarily scrap, utilized in the production.

## III. PHYSICAL DATA

MELTING POINT: 1560 - 1840°C @ 1 atmosphere.

APPEARANCE AND ODOR: Gray metallic solid; no odor.

## IV. FIRE AND EXPLOSION HAZARD DATA

This product does not burn. However, grinding or polishing this product in the absence of oxygen, such as under water, can result in a finely divided waste which is ignitable.

## V. REACTIVITY DATA

This is a stable material at room temperature under normal storage and handling conditions.



VI. HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

TITANIUM: There is no evidence of a health hazard from inhalation of titanium dioxide in concentrations not exceeding 10 mg/m<sup>3</sup>. The toxicity of titanium dioxide has been found to be relatively inert. Skin contact with titanium dusts may cause physical abrasion. Eye contact with pure material has shown particulate irritation. A NCI bioassay of titanium dioxide, administered in the diet of rats and mice, was reported to be negative (NCI-CC-TR-97, 1979). ALUMINUM: Aluminum dust/fines and fumes are a low health risk by inhalation, and should be treated as a nuisance dust (Ref. ACGIH). VANADIUM: Exposure to high concentrations of Vanadium dust and fumes can cause respiratory irritation, skin pallor, greenish-black tongue, chest pain, cough, dyspnea, palpitation, lung changes. TIN: No systemic effects have been reported from industrial exposure to tin.

| MAJOR EXPOSURE HAZARD                          |                                      |
|--|--------------------------------------|
| <input checked="" type="checkbox"/> INHALATION | <input type="checkbox"/> EYE CONTACT |
| <input type="checkbox"/> SKIN CONTACT          | <input type="checkbox"/> INGESTION   |

EMERGENCY AND FIRST AID PROCEDURES:

For overexposure to airborne fumes and particulates generated during various milling operations, remove exposed person to fresh air. If breathing is difficult or has stopped, administer artificial respiration or oxygen as indicated. Seek medical attention promptly.

VII. SPILL OR LEAK PROCEDURES

N/A

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY: Respirator recommended for all grinding, cutting, etc. Consult local supplier for selection of appropriate NIOSH/MSHA approved respirator.

SKIN: Protective clothing and gloves may be required for certain handling operations.

EYE: Safety glasses should be worn.

VENTILATION: Adequate general and/or local exhaust ventilation should be provided as necessary.

OTHER PROTECTIVE EQUIPMENT:

None Required.

IX. SPECIAL PRECAUTIONS

If ignitable waste is generated, special precautions and firefighting procedures should be followed:

- 1.) Keep work areas free of the waste.
- 2.) Store wet and keep away from heat and open flame - maintain humidity above 50% to prevent an electrostatic build-up.
- 3.) No smoking in area.
- 4.) Use non-sparking metal equipment.
- 5.) Extinguishing media: dry chemical powders, salts or inert gas. Do not use water or liquid: explosion hazard could result.