

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
 TRANSEPTIC® CLEANSING SOLUTION

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name	Emergency Telephone Number
PARKER LABORATORIES, INC.	Chemtrec (800) 262-8200
Address (Number, Street, City, State and ZIP Code)	Telephone Number for Information
286 ELDRIDGE ROAD	(973) 276-9500
	Date Prepared
FAIRFIELD, NJ 07004	SEPTEMBER 2006
	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
ISOPROPYL ALCOHOL	400 ppm	400 ppm	500 ppm (TLV/STEL)	~70

Section III – Physical/Chemical Characteristics

Boiling Point	180°F	Specific Gravity (H²O = 1)	0.88
Vapor Pressure (mm Hg.)	N/D	Melting Point	N/A
Vapor Density (AIR = 1)	N/D	Evaporation Rate (Butyl Acetate = 1)	N/D
Solubility in Water	SOLUBLE		
Appearance and Odor	A CLEAR, LIGHT BLUE LIQUID; ALCOHOLIC ODOR		

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) APPROX. 63°F – TCC	Flammable Limits	LEL 2	UEL 12
Extinguishing Media DRY CHEMICAL, FOAM OR CARBON DIOXIDE			
Special Fire Fighting Procedures FLAMMABLE, COOL FIRE – EXPOSED CONTAINERS WITH WATER			
Unusual Fire and Explosion Hazards VOLATILE LIQUID			

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid	IGNITION SOURCES (HEAT, SPARKS, FLAMES, STATIC ELECTRICITY)
	Stable	X		
Incompatibility (Materials to Avoid) CONCENTRATED NITRIC AND SULFURIC ACIDS, STRONG OXIDIZERS, HALOGENS				
Hazardous Decomposition or Byproducts BURNING MAY PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE				
Hazardous Polymerization	May Occur		Conditions to Avoid	NONE KNOWN
	Will Not Occur	X		

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation? YES	Skin? NO	Ingestion? YES
Health Hazards (<i>Acute and Chronic</i>)			
INHALATION: MILDLY IRRITATING. INGESTION: SLIGHTLY TOXIC.			
EYE CONTACT: SLIGHT IRRITATION.			
Carcinogenicity:	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
Signs and Symptoms of Exposure			
INHALATION: MILD IRRITATION OF EYES, NOSE, THROAT. INGESTION: LARGE QUANTITIES MAY CAUSE DROWSINESS AND LOSS OF CONSCIOUSNESS. EYES: IRRITATION.			
Medical Conditions Generally Aggravated by Exposure			
PRE-EXISTING EYE, SKIN, AND RESPIRATORY DISORDERS.			
Emergency and First Aid Procedures			
EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. INHALATION: REMOVE VICTIM FROM EXPOSURE. INGESTION: GIVE WATER TO DRINK; INDUCE VOMITING; CONTACT PHYSICIAN IMMEDIATELY.			

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled	
REMOVE ALL IGNITION SOURCES. FLUSH WITH WATER: SOAK UP WITH ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINER.	
Waste Disposal Method	
FOLLOW LOCAL, STATE, AND FEDERAL REGULATIONS.	
Precautions to Be Taken in Handling and Storing	
DO NOT STORE NEAR HEAT, SPARKS, OR FLAME.	

Other Precautions

Section VIII – Control Measures

Respiratory Protection (Specify Type)		N/A		
Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A
Protective Gloves		N/A	Eye Protection	N/A
Other Protective Clothing or Equipment		N/A		
Work/Hygienic Practices		NORMAL GOOD PERSONAL HYGIENE, AND GOOD HOUSEKEEPING PRACTICES		

Section IX – Transportation Information

Applicable DOT Regulations:		CFR 49 IMDG
Shipping Name:		ISOPROPYL ALCOHOL
Identification Number:		UN 1219
Reportable Quantity:		<u>DOMESTIC</u> 250 ML X 12 BOTTLES/ INNER BOX "ORM-D CONSUMER COMMODITY" ARROWS - LABELS UPRIGHT DIRECTION
LABELS:		
Reportable Quantity:		<u>STOWAGE</u> 250 ML X 12 BOTTLES/ INNER BOX "LTD – QTY" UN1219 ARROWS - LABELS UPRIGHT DIRECTION
LABELS:		