TRUE PRIME Version Number: 2

# SAFETY DATA SHEET

### SECTION 1. INDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: TRUE PRIME

Other Names:

Recommended Use: Solvent Alkyd Paint

Company Name: Resene Paints Limited 32-50 Vogel Street

Naenae Wellington NEW ZEALAND

Phone: (04) 577 0500 Fax: (04) 577 0600 P O Box 38242 Wellington Mail Centre

Emergency Telephone: 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

### SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Risk Phrases Safety Phrases

Substance Classification 3.1C 6.3B 9.1B

Hazard Statements Flammable liquid and vapour

Causes mild skin irritation

Toxic to aquatic life with long lasting effects

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients % CAS No TWA

Mineral Turps 30 - 60 Mixture None Establish

Barium metaborate < 10 13701-59-2 0.5 mg/m³ as B  $^{NZ OSH (WES) 2002}$ 

Methyl Ethyl Ketoxime < 1 96-29-7 36 mg/m³ OSHA CEL

Non-Hazardous material Not known None Establish

# SECTION 4. FIRST AID MEASURES

Eye: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed:

Skin IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF skin irritation occurs: Get medical advice/attention.

Inhaled

Aggravated medical conditions caused by exposure

**Chronic Health Effects** 

Advice to Doctor Treat symptomatically.

### SECTION 5. FIRE FIGHTING MEASURES

**Extinguisher** Foam, Carbon Dioxide, Dry Chemical

**Hazards from** 

combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

Hazchem Code Flash Point 250°C 0.4% 6.0%

3[Y] 31°C

# SECTION 6. ACCIDENTAL RELEASE MEASURES

#### **Emergency Procedures**

Keep spectators away and avoid breathing dust or vapours 1 of 3

TRUE PRIME Resene Paints Limited

#### Methods and materials for containment and clean up

Minor Spills Clean up spills immediately.

Wear protective clothing and breathing apparatus.

Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Sweep up.

Place in separate container for disposal or recovery.

Major Spills Restrict access to area. No smoking or naked lights.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Clear area of personnel and move upwind.

Dike and contain spill with inert materials (eg. Sand).

Stop leak if safe to do so.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Collect recoverable product into labelled containers for recycling.

### SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

#### Conditions for safe storage including any incompatibilities

Storage Temperatures Min 1°C Max 40°C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure

standards for mixture Breathing Zone ppm Breathing Zone mg/m<sup>3</sup>

**Component Pigments** 

#### **Personal Protection**

**Eyes** Safety eyewear with splash guards or side shields to prevent eye contact is recommended when

using any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined

gauntlet recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

Respirator

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Coloured liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze Solubility Volatile by Weight

Hydrocarb n/a 3.3 kPa 4.3 145°C < -40°C Insoluble 35

# SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Material

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

TRUE PRIME Resene Paints Limited

#### TRUE PRIME

### SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Refer to individual raw materials

### SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment

No data available for this product

### SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineratio

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

### SECTION 14. FIRST AID MEASURES

UN Number 1263

UN Proper Paint related product

shipping

Subsidiary risk

Poison Schedule HAZCHEM Code 3[Y]

Packing Group: III Class 3 Flammable Liquid

#### Special precautions for user

### SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants (Flammable)

Approved Handler Not required

# SECTION 16. OTHER INFORMATION

Date of Preparation 10/06/2008

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commissio

TLV Time weighted averag
STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry numbe

TWA Threshold limit valu

Marine Pollutant Marine Pollutant

#### Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.

Page 3 of 3

TRUE PRIME Resene Paints Limited