Material Safety Data Sheet

EzNails Inc 11652 Monarch Street Garden Grove CA 92841 Ph.866.439.6255 **Product:**

UV/AIR TOP COAT

Date Prepared: 02/15/07

Prepared By:

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS - Chemical Name & Common Names (Hazardous Components 1% or greater, Carcinogens 0.1% or greater)	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Ethyl Acetate			400 ppm	
Cellulose Acetate Butyrate			NA	
Methyl Ethyl Ketone			300 ppm	
Isopropyl Alcohol				
n-Butyl Acetate			NA	
Urethane Acrylate Oligomer				
Photoinitiator				
	100			

SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point NA	Specific Gravity $(H_20 = 1)$ about 1	
Vapor Pressure (mm Hg and Temperature) NA	Melting Point N/A	
Vapor Density (Air = 1) >1	Evaporation Rate (Butyl Acetate = 1) NA	
Solubility in Water Not Soluble	Water Reactive No	
Appearance And Odor Pale, Slightly Viscous liquid, fruity odor		

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used -4°F (cc)	Auto-Ignition Temperature NA	Flammability Limits in Air % by Volume NA	LEL	UEL 2.2	
Extinguisher Media: Dry chemi	Extinguisher Media: Dry chemical, carbon dioxide, halogen, water spray, foam				
Special Fire Fighting Procedures: Water spray should be used to keep fire-exposed containers cool					
Unusual Fire and Explosion Hazards: Dangerous when exposed to heat or flame. Wear self-contained breathing apparatus.					
	<u>-</u>	-			

NA = not available

UV/AIR TOP COAT Page 2/2

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY	Conditions to Avoid: Excessive heat or flame.	
Incompatibility (Materials to Avoid): Oxidizing materials, acids, aliphatic amines		
Hazardous Decomposition Products: Thermal decomposition products may include toxic oxides of carbon		
HAZARDOUS	Conditions to Avoid:	
POLYMERIZATION ☐ May Occur	Not applicable	
⊠ν Will Not Occur		

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES	ν ⊠ Inhalation	v⊠ Ingestion	Carcinoge	□ NTP	□ OSHA
OF ENTRY	v Skin Absorption	□ Not Hazardous	n	□ IARC	□ Not Listed
			Listed In	Monograph	
HEALTH HAZARDS	Acute: Slight transient irritation of upper respiratory tract, dizziness				
	Chronic: Upper respiratory tract irritation, dizziness				
Signs and Symptoms of	Signs and Symptoms of Exposure: Headaches, dizziness, irritation of eyes and respiratory tract				
Medical Conditions Generally Aggravated by Exposure: Not known					
EMERGENCY FIRST AID PROCEDURES -					
Eye Contact: Immediately flush eyes with running water for 15 minutes					
Skin Contact: Wash with soap and water					
Inhalation: Remove to fresh air. Consult a physician					
Ingestion: Consult a physician					

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type): Avoid prolonged breathing of vapor				
Protective Gloves: Resistant gloves		Eye Protection: Safety/chemical goggles		
VENTILATION	ν⊠ Local Exhaust	v Mechanical (general)	☐ Special	
TO BE USED	☐ Other (specify)			
Other Protective Clothing and Equipment When handling large quantities, apron and rubber boots				
Hygienic Work Practices: Avoid contact with skin and eyes; work in well ventilated area				

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

Steps to be Taken if Material is Spilled Or Released:	Cover with absorbent material and place into tight container for later disposal.
Waste Disposal Methods:	Dispose in accordance with local, state, and federal regulations for the disposal of hazardous waste.
Precautions to be Taken in Handling and Storage:	Store away from acids, amines, oxidizing materials. Should be stored in containers which meet the bonding and grounding guidelines specified in NFPA77-1983.
Other Precautions and/or Special Hazards:	Store in cool dry place.

 $NA = not \ available$

NFPA Rating* Health 1 Flammability 3 Reactivity 0 Special HMIS Rating* Health Flammability Reactivity Personal Protection *optional