

Material Safety Data Sheet

Material Name: ULTRABOND ECO 85

ID: NDM0009

*** Section 1 - Chemical Product and Company Identification ***

Product Name: **ULTRABOND ECO 85**

Product Use: Flooring Adhesive

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive
Deerfield Beach, FL 33442
Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue
Laval, QC H7L 3J5
Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers: (USA) CHEMTREC 1-800-424-9300
(Canada) CANUTEC 1-613-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product has been evaluated using criteria specified in 29CFR 1910.1200 (Hazard Communication Standard).

This product contains trace levels (<0.03%) of fungicides.

Potential Health Effects: Eyes

Irritating to eyes.

Potential Health Effects: Skin

None identified.

Potential Health Effects: Ingestion

Acute ingestion may result in mild gastrointestinal distress.

Potential Health Effects: Inhalation

If inhaled, immediately remove the affected person to fresh air. Seek medical attention.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
1317-65-3	Limestone	15-40
1332-58-7	Kaolin	10-30
64742-52-5	Naphthenic oil	5-10

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Calcium carbonates.

Component Information/Information on Non-Hazardous Components

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical attention.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 85

ID: NDM0009

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

Product is not considered toxic in small amounts. If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

First Aid: Inhalation

Move person to non-contaminated air. Call a physician if symptoms develop or persist.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is combustible at high temperatures.

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container.

Evacuation Procedures

None necessary.

Special Procedures

Follow all Local, State, Federal and Provincial regulations for disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid contact with skin and eyes. Wash thoroughly after handling. Keep out of the reach of children.

Storage Procedures

Store at ambient temperature and atmospheric pressure. Store away from strong oxidizers.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Limestone (1317-65-3)

OSHA: 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)

Kaolin (1332-58-7)

ACGIH: 2 mg/m3 TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)

OSHA: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 85

ID: NDM0009

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed.

Personal Protective Equipment: General

Laundry contaminated clothing before reuse.

*** Section 9 - Physical & Chemical Properties ***

Appearance: Creamy Paste

Physical State: Paste

Vapor Pressure:

Boiling Point:

Solubility (H2O):

Evaporation Rate:

Octanol/H2O Coeff.:

Flash Point Method: Closed cup

Odor: Slight Hydrocarbon Odor

pH: 7-11

Vapor Density:

Melting Point:

Specific Gravity: 1.2- 1.5

VOC: 18g/liter

Flash Point: >200F

Upper Flammability Limit

(UFL):

Burning Rate:

Lower Flammability Limit

(LFL):

Auto Ignition:

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

This is a stable material.

Chemical Stability: Conditions to Avoid

Avoid strong oxidizing agents. Do not freeze.

Incompatibility

This product may react with strong oxidizing agents.

Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Petroleum distillates, hydrotreated heavy naphthenic (64742-52-5)

Inhalation LC50 Rat: 2.18 mg/L/4H; Oral LD50 Rat:>5000 mg/kg; Dermal LD50 Rabbit:>2000 mg/kg

Carcinogenicity

Component Carcinogenicity

Kaolin (1332-58-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Material Safety Data Sheet

Material Name: ULTRABOND ECO 85

ID: NDM0009

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Petroleum distillates, hydrotreated heavy naphthenic (64742-52-5)

Test & Species

Conditions

96 Hr LC50 Pimephales promelas >5000 mg/L

48 Hr EC50 Daphnia magna >1000 mg/L

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Clean up and dispose of waste in accordance with all federal, state, and local environmental regulations.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes	Yes
Kaolin	1332-58-7	No	Yes	Yes	Yes	Yes	Yes

Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

WHMIS Classification: Not Regulated

Additional Regulatory Information

Material Safety Data Sheet

Material Name: ULTRABOND ECO 85

ID: NDM0009

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Limestone	1317-65-3	Yes	NDSL	EINECS
Kaolin	1332-58-7	Yes	DSL	EINECS
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	Yes	DSL	EINECS

*** Section 16 - Other Information ***

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

NA = Not available or Not Applicable. NFPA = National Fire Protection Association. HMIS = Hazardous Material Information System. CFR = Code of Federal Regulations. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888