

# SAFETY DATA SHEET.

Issuing date 13-Mar-2015 Revision Date 13-Mar-2015 Version 2.04

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name UNLIMITED SLIP AUTOMOTIVE & FLEET WHITE LITHIUM GREASE

Recommended use of the chemical

and restrictions on use

Product code DA7910

<u>Product Type</u> Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Lubricant.

Uses advised against No information available

Manufactured For:

Drummond, A Lawson Brand Lawson Products, Inc. 8770 W. Bryn Mawr Avenue-Suite 900 Chicago, IL 60631-3515 773-304-5050

Emergency telephone number

Emergency telephone 888-426-4851

# 2. HAZARDS IDENTIFICATION

#### Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

## **Emergency Overview**

# **DANGER**

## **Hazard Statements**

Causes skin irritation

May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance opaque Physical state Aerosol Odor Solvent

# **Precautionary Statements - Prevention**

Wash hands thoroughly after handling

Wear protective gloves

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

# **Precautionary Statements - Response**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

# **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Store in a well-ventilated place

Keep container tightly closed.

Do not expose to temperatures exceeding 122°F (50°C)

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

None

## Other information

Toxic to aquatic life with long lasting effects

0.00002% of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Titanium Dioxide is bound in the polymer matix .

Chemical Name	CAS-No	Weight %*
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	40-50
HEPTANE	64742-49-0	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
LITHIUM 12HYDROXYOCTADECANOATE	7620-77-1	1-10
ACETONE	67-64-1	1-10
TITANIUM DIOXIDE	13463-67-7	0.1-1.0

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# First aid measures for different exposure routes

**General advice** Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek

immediate medical attention/advice.

**Skin contact** Wash off immediately with soap and plenty of water. If skin irritation persists, call a

physician.

**Inhalation** Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial

respiration. If breathing has stopped, contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

## Most important symptoms/effects, acute and delayed

Main Symptoms Causes eye irritation. Inhalation causing Central Nervous System effects. ingestion causing

lung damage.

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

## Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire. Keep product and empty container away from heat and sources of ignition.

#### **Explosion Data**

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Environmental precautions** 

**Environmental precautions** Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventiliation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such

as electric motors and batteries. Do not spray on hot surfaces.

## Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible products** Store away from strong oxidizers and acids.

Aerosol Level 3

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEPTANE	TLV: 400 ppm	TWA: 500 ppm	-
64742-49-0	STEL: 500 ppm		

PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m³
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

**Engineering Measures**Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Odor

provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Physical and chemical properties

Physical state Aerosol
Appearance opaque

Color beige Odor Threshold No information available

Color Deige Odor Threshold No information available

Property Values Remarks • Methods

pH No information available
Melting/freezing point No information available
Boiling point/boiling range
Flash Point -96.4 °C / -141 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limits in Air

upper flammability limit

No information available

Solvent

#### DA7910 UNLIMITED SLIP AUTOMOTIVE & FLEET WHITE LITHIUM GREASE

Revision Date 13-Mar-2015

Not applicable

Iower flammability limitNo information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.759

Water solubility Practically insoluble
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available

Decomposition temperatureNo information availableViscosityNo information availableExplosive propertiesNo information available

**Other information** 

**VOC Content(%)** 49.86

# 10. STABILITY AND REACTIVITY

## Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

Store away from strong oxidizers and acids.

## **Hazardous Decomposition Products**

Carbon oxides. Fumes. Hydrocarbons.

# 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known information

**Inhalation** Exposure to high vapour concentrations may cause nervous systems effects such as

headache, nausea, and dizziness.

**Eye contact** May cause irritation.

**Skin contact** Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung

damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEPTANE	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
64742-49-0			
ACETONE	-	20,000 mg/kg (Rabbit)	= 50100 mg/m <sup>3</sup> (Rat) 8 h
67-64-1			
TITANIUM DIOXIDE	> 10000 mg/kg (Rat)	-	-
13463-67-7			

## Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizzienss, tiredness, nausea, and

vomiting.May cause mild irritation.Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause

serious lung damage which may be fatal.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Eye damage/irritation Irritating to eyes.

No information available. Sensitization **Germ Cell Mutagenicity** No information available.

This product contains titanium dioxide which is classified as an IARC 2B carcinogen based Carcinogenicity on laboratory studies where animals were exposed to titanium dioxide dust. This is not a relevant route of exposure for this product since it is a moist solid material with little to no chance of producing dust . No inhalation exposure will occur during the handling or use of

this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE 13463-67-7	-	2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity Specific target organ systemic

toxicity (single exposure) Specific target organ systemic

toxicity (repeated exposure)

**Chronic toxicity** 

The ingredients are not reproductive hazards.

may cause drowsiness and dizziness.

No information available.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

**Target Organ Effects** 

Central nervous system, Eyes, Lungs, Respiratory system, Skin.

May be fatal if swallowed and enters airways. **Aspiration hazard** 

## Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0.00002% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 8674 mg/kg 10975 mg/kg **ATEmix (dermal)** ATEmix (inhalation-dust/mist) 5076 mg/l ATEmix (inhalation-vapor) 87 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	<del>-</del>	-	-	-

ACETONE	-	4.74 - 6.33 mL/L LC50	-	10294 - 17704 mg/L EC50
67-64-1		Oncorhynchus mykiss 96h		Daphnia magna 48h Static
		6210 - 8120 mg/L LC50		12600 - 12700 mg/L EC50
		Pimephales promelas 96h		Daphnia magna 48h
		static 8300 mg/L LC50		
		Lepomis macrochirus 96h		

# Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
ACETONE 67-64-1	-0.24

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations.

**Contaminated packaging** Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

Or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

# 15. REGULATORY INFORMATION

# **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
NAPHTHENIC OIL, SEVERLY HYDROT	Х	X	X	X	Х	Х	X	Х
HEPTANE	Χ	X	X	X	X	X	X	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
LITHIUM 12HYDROXYOCTADE CANOATE	Х	X	X	Х	Х	Х	Х	X

#### DA7910 UNLIMITED SLIP AUTOMOTIVE & FLEET WHITE LITHIUM GREASE

Revision Date 13-Mar-2015

ACETONE	X	X	X	X	X	X	X	X
TITANIUM DIOXIDE	Χ	X	Х	Χ	Х	X	X	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## **U.S. Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

# SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard Yes
Reactive Hazard no

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

## **U.S. State Regulations**

# **California Proposition 65**

No warning required.

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
TITANIUM DIOXIDE 13463-67-7	Х	X	X

## EPA Pesticide Registration Number Not applicable

# Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

# **16. OTHER INFORMATION**

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

Prepared By Regulatory Affairs Issuing date 13-Mar-2015 Revision Date 13-Mar-2015

Revision Note

No information available

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**