



55-9442-1 ✓

Product Name: UNOCAL GUARDOL MOTOR OIL 15W/40
 PRODUCT CODE NO: 0365QXX54

ISSUE DATE: 6/ 5/85

PAGE 1 OF 4

<p>MANUFACTURER:</p> <p>UNOCAL REFINING & MARKETING DIVISION UNION OIL COMPANY OF CALIFORNIA 1201 W. 5TH STREET LOS ANGELES, CALIFORNIA 90017</p> <p>CONTACT FOR FURTHER INFORMATION: MSDS COORDINATOR (213) 977-7589</p>	<p>Transportation Emergencies: Call CHEMTREC (800) 424-9300 Cont. U.S. (202) 483-7616 (Collect) from Alaska & Hawaii</p> <p>Health Emergencies: CALL LOS ANGELES POISON INFORMATION CENTER (24 hrs.) (213) 664-2121</p>
--	--

PRODUCT IDENTIFICATION

PRODUCT NAME: UNOCAL GUARDOL MOTOR OIL 15W/40

SYNONYMS: UNION GUARDOL MOTOR OIL 15W/40

GENERIC NAME: CRANKCASE OIL

CHEMICAL FAMILY: PETROLEUM HYDROCARBON

DOT PROPER SHIPPING NAME: NOT APPLICABLE

ID NUMBER: NONE

SECTION I - INGREDIENTS	TLV	UNITS	AGENCY	TYPE
OIL MIST, IF GENERATED	5.00	MG/M3	OSHA	FULL TERM TWA

THE IDENTITIES OF INGREDIENTS THAT ARE TRADE SECRETS ARE EXCLUDED FROM THIS LIST.

SECTION II - EMERGENCY AND FIRST AID PROCEDURES *****EMERGENCY*****
 Have physician call LOS ANGELES POISON INFORMATION CENTER (24 hrs.) (213) 664-2121

EYE CONTACT:

FOR DIRECT CONTACT, FLUSH THE AFFECTED EYE(S) WITH CLEAN WATER. IF IRRITATION OR REDNESS DEVELOPS, SEEK MEDICAL ATTENTION.

SKIN CONTACT:

DO NOT USE GASOLINES, THINNERS OR SOLVENTS TO REMOVE PRODUCT FROM SKIN. WIPE MATERIAL FROM SKIN AND REMOVE CONTAMINATED CLOTHING. CLEANSE AFFECTED AREA(S) THOROUGHLY BY WASHING WITH SOAP AND WATER AND, IF NECESSARY, A WATERLESS SKIN CLEANSER. IF IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION (BREATHING):

IF IRRITATION OF NOSE OR THROAT DEVELOPS, MOVE AWAY FROM SOURCE OF EXPOSURE AND INTO FRESH AIR. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING OR IF BREATHING DIFFICULTIES DEVELOP, ARTIFICIAL RESPIRATION OR OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SEEK IMMEDIATE MEDICAL ATTENTION.

INGESTION (SWALLOWING):

IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2 TO 3 CUPS OF MILK OR WATER TO DRINK. SEEK MEDICAL ATTENTION. TO PHYSICIAN: EMESIS OR LAYAGE IS NOT RECOMMENDED FOR INGESTIONS OF MINUTE QUANTITIES OR TASTES OF MOST HYDROCARBONS. MEDICAL OPINION IS DIVIDED FOR LARGER INGESTIONS. EMESIS OR LAYAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM PRODUCTS WHICH HAVE A HIGH ORAL TOXICITY. GASTRIC LAYAGE WITH A CUFFED ENDOTRACHEAL TUBE IS RECOMMENDED BY SOME PHYSICIANS TO PREVENT ASPIRATION.

SECTION III - POTENTIAL ADVERSE HEALTH EFFECTS

EYE CONTACT:

THIS MATERIAL MAY CAUSE EYE IRRITATION. DIRECT CONTACT MAY CAUSE BURNING, TEARING AND REDNESS.

SKIN CONTACT:

THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DERMATITIS.

INHALATION (BREATHING):

EXPOSURE TO MISTS, OR PROLONGED OR REPEATED EXPOSURE TO FUMES OR VAPORS THAT MAY BE GENERATED WHEN THIS MATERIAL IS HEATED, MAY CAUSE IRRITATION OF NOSE AND THROAT.

INGESTION (SWALLOWING):

ACCIDENTAL INGESTION OF THIS MATERIAL MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

COMMENTS:

USED MOTOR OIL: FOLLOWING REPEATED SKIN APPLICATIONS, ANIMAL STUDIES HAVE SHOWN THAT USED MOTOR/CRANKCASE OILS HAVE CAUSED AN INCREASED INCIDENCE OF SKIN CANCER IN MICE. IT IS THEREFORE RECOMMENDED THAT PROLONGED OR REPEATED CONTACT WITH MOTOR/CRANKCASE OILS BE AVOIDED.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION:

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE IN MAINTAINING AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

RESPIRATORY PROTECTION:

IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED EXPOSURE LIMITS, A SUITABLE FILTER-TYPE RESPIRATOR SHOULD BE WORN. (SEE SECTION I.)

PROTECTIVE GLOVES:

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN WORK AREA FOR FLUSHING EYES AND SKIN. BARRIER CREAMS THAT ARE SPECIFIC FOR OIL-BASED MATERIALS ARE RECOMMENDED WHEN GLOVES ARE IMPRACTICAL.

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH ANY SOURCE OF HEAT OR FLAME.

SECTION V - REACTIVITY DATA

INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS SUCH AS CHLORINE, PERMANGANATES AND DICHROMATES.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD MAJOR AMOUNTS OF OXIDES OF CARBON AND MINOR AMOUNTS OF OXIDES OF SULFUR AND NITROGEN.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

SECTION VI - SPILL OR LEAK PROCEDURES

HIGHWAY OR RAILWAY SPILLS
Call CHEMTREC (800) 424-8300 Cont. U.S.
(Collect) (202) 483-7616 from Alaska & Hawaii

PRECAUTIONS IN CASE OF RELEASE OR SPILL:

COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS. ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBANT. CONTACT FIRE AUTHORITIES AND APPROPRIATE STATE/LOCAL AGENCIES. IF SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS ZONE, OR ADJOINING SHORELINES, NOTIFY COAST GUARD NATIONAL RESPONSE CENTER (PHONE NUMBER 800-424-8802).

WASTE DISPOSAL METHOD:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION V). AVOID GENERATING OIL MISTS WHILE HANDLING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. FOR USED MOTOR OIL: LAUNDRER SATURATED CLOTHING BEFORE WEARING AND DISCARD OIL-SOAKED SHOES AND UNWASHABLE CLOTHING.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

HAZARD RANKING

NFPA HAZARD CLASS	HEALTH HAZARD: FLAMMABILITY: REACTIVITY: OTHER:	0 = LEAST 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME	DOT FLAMMABILITY CLASSIFICATION NOT REGULATED	<u>FLASH POINT</u> 419, COC F 215 C
-------------------	--	--	--	---

EXTINGUISHING MEDIA:

EXTINGUISH WITH DRY CHEMICAL, CO2, WATER SPRAY, FOAM, SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

FIRE & EXPLOSION HAZARDS:

THIS MATERIAL WILL BURN, BUT WILL NOT IGNITE READILY.

FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK.

SECTION IX - PHYSICAL DATA

<u>APPROX. BOILING RANGE</u>	<u>VAPOR DENSITY</u>	<u>EVAPORATION RATE</u>	<u>% VOLATILE</u>
ABOVE 600 F (316) C	HEAVIER THAN AIR	SLOWER THAN ETHER	NEGLECTIBLE
<u>% SOLUBILITY IN WATER</u>	<u>SPECIFIC GRAVITY</u>	<u>APPEARANCE</u>	
NEGLECTIBLE	D.89	CLEAR, BROWN LIQUID	

ODOR

CHARACTERISTIC

SECTION X - PRECAUTIONARY LABEL

CAUTION! USED MOTOR OIL IS A POSSIBLE SKIN CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID MAKING OR BREATHING OIL MIST. USE ADEQUATE VENTILATION. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING.

SECTION XI - DOCUMENTARY INFORMATION

ISSUE DATE: 6/ 5/85 PREV. DATE: 7/25/84 PRODUCT CODE NO. D3650XX54

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.