## MATERIAL SAFETY DATA SHEET

Simoniz USA Inc.	REVISION DATE:DATE PRINTED:	
Bolton, Connecticut 06043 (860) 646-0172	PRODUCT NUMBER:CONTROL NUMBER:	

#### **SECTION I - IDENTIFICATION**

# PRODUCT NAME: Urethane Fortified Premier

PRODUCT TYPE:.....Liquid Acrylic Floor Finish

#### **SECTION II - HAZARDOUS INGREDIENTS**

CAS NUMBER

PEL

PERCENT

Water	7732-18-5	No limits established	Not
Acrylate Copolymer Diethylene Glycol Methyl Ether Tributoxy Ethyl Phosphate Acrylate Copolymer	63744-68-3 111-77-3 78-51-3 65405-63-2	No limits established No limits established 0.5mg/m3 TWA No limits established	Listed

#### **SECTION III - PHYSICAL DATA**

APPEARANCE: White opaque liquid. No significant odor.

HAZARDOUS INGREDIENT

BOILING POINT: 210 degrees F. VAPOR PRESSURE: N/A VAPOR DENSITY: Greater than 1. SPECIFIC GRAVITY: 1.02

PH: 8.0-9.0 SOLUBILITY IN WATER: Completely soluble.

### **SECTION IV - FIRE AND EXPLOSION DATA**

FLASHPOINT:This product is non-flammable.		
EXTINGUISHING MEDIA:This product is non-flammable. Use extinguishing media		
suitable for materials already burning.		
SPECIAL FIRE FIGHTING PROCEDURES: Firefighters working in areas		
where this product is present should be equipped with an approved, fully enclosed SCBA.		
UNUSUAL FIRE AND EXPLOSION HAZARDS:None known.		
SECTION V - REACTIVITY DATA		
STABILITY:Stable under normal conditions.		
HAZARDOUS POLYMERIZATION: This product not known to polymerize.		
INCOMPATIBILITY:Do not mix with other chemicals.		
HAZARDOUS BYPRODUCTS:Carbon monoxide, carbon dioxide.		
SECTION VI - HEALTH DATA		
ROUTE(S) OF ENTRY:Ingestion. Not likely to be inhaled in dangerous amounts.		
LISTED CARCINOGEN:Not listed by IARC, NTP or OSHA.		
MEDICAL CONDITION AGGRAVATED:		
INHALATION:Not likely to be inhaled in hazardous amounts. Maintain		
adequate ventilation in the work area.		
INGESTION:This material can cause irritation to the stomach and		
esophagus if ingested.		
EYES:May cause eye irritation.		
SKIN (DERMAL):Not likely to irritate. Prolonged exposure to undiluted		
product may cause irritation.		

#### **SECTION VII FIRST AID**

CECTION VIII INC				
BREATHING (INHALATION): If victim shows si	gns of discomfort or irritation, remove			
to fresh air. If symptoms persist, get immediate medical atte	ention.			
SWALLOWING (INGESTION):DO NOT INDUC	E VOMITING! Drink a large quantity			
of water or milk. Do not attempt to give liquids to an uncon	scious person. Get immediate medical			
attention!	_			
EYES:Flush eyes with a	large quantity of fresh water for at			
least 15 minutes. If irritation persists, consult a physician.				
SKIN (DERMAL):Flush from skin and clothing with large amounts of free				
water. If irritation persists, consult physician. Wash contaminated clothing before wearing.				
SECTION VIII EMPLOYEE F				
RESPIRATORY PROTECTION:Not usually neede				
PROTECTIVE CLOTHING:Special protection				
protection if product is likely to splash.				
ADDITIONAL MEASURES:	product in an unmarked container.			
Avoid eye contact. Spilled material is slippery.				
The state of the s				
SECTION IX - SPILL AND DIS	SPOSAL DATA			
SPILL:Dike to prevent spillage into streams or sewer systems.				
Consult local, state and federal authorities.	·			
WASTE DISPOSAL: As recommended by local, state and federal authorities.				
HANDLING & STORAGE PRECAUTIONS	Store in a cool, well ventilated			
area. Avoid overheating or freezing.				
SECTION X -OTHER REGULATO	RY INFORMATION			
PROPER SHIPPING NAME: Not D.O.T. regulated.	NFPA HEALTH: 1			
CONSTITUENT:	NFPA FLAMMABILITY: 0			
HAZARD CLASS AND LABEL:	NFPA REACTIVITY: 0			
ID NUMBER:	NFPA OTHER: None			
PACKING GROUP:				

#### **SECTION XI - PRECAUTIONARY STATEMENTS**