

# UTILITY 25 CPF=25<sup>A</sup>

## **ARTERIAL FLUID**

UTILITY 25 is a formaldehyde arterial fluid for general purpose use. UTILITY 25 is suitable for use in all normal cases if appropriate accessory fluids are used. UTILITY 25 is not recommended for use in difficult or advanced decomposition cases.

|   |                     | CELL             | UTILITY 25 <sup>8</sup> |                                   |           | DI-SAN⁵                | HUMITONE <sup>6</sup>        |
|---|---------------------|------------------|-------------------------|-----------------------------------|-----------|------------------------|------------------------------|
| PH-A¹   | DI-SAN <sup>2</sup> | CONDI-<br>TIONER | MODERATE<br>FIRMNESS    | DEFINITE <sup>3</sup><br>FIRMNESS | HUMITONE⁴ | ADD FOR EXTRA FIRMNESS | ADD TO RESTORE MOISTURE CON- |
| 3-4   | 1-2                 | 8-12             | 8                       | 10-12                             | 4-6       | 1-3                    | 4-8                          |
| $\rightarrow$ MIX IN THIS ORDER $\rightarrow$ $\rightarrow$ |                     |                  |                         |                                   |           |                        |                              |

#### **Notes:**

- A A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
- 1 For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water -reduce amount to 2-3 ozs.)
- 2 For sanitizing action in solution and improved fluid action in all non-glutaraldehyde based fluids.
- 3 These are recommended amounts for normal cases. Additional amounts of fluid will be needed for cases with higher aldehyde demand such as cancer, renal and liver diseases with their complications, institutional cases and other wasting diseases, delayed em- balming cases, edema and bodies subjected to extensive drug therapy.
- 4 Humectant to control aldehyde action and prevent dehydration during embalming. Use in all non-lanolin based fluids. Do not use in cases of moisture retention (edema, etc.).
- 5 For increased aldehyde action of fluid with improved rigidity and preservation. (Increases preservative factor of fluid without inducing dehydration or other unwanted effects.)
- 6 For maximum rehydration of tissues. Restores moisture in cases of dehydration or emaciation. Use in last 1 to 1-1/2 gallons of solution with intermittent or restricted drainage.

BEFORE USING, READ MATERIAL SAFETY DATA SHEET. FOR PROFESSIONAL EMBALMING USE ONLY.

## MATERIAL SAFETY DATA SHEET

THE CHAMPION COMPANY

400 Harrison Street Springfield, Ohio 45505

EMERGENCY TELEPHONE NO. (937) 324-5681

CHEMTREC: (800) 424-9300 (Spill, Leak, Fire, Exposure or Accident)

**HAZARD RATING** 

Health 2 2 Fire

Reactivity 0 Special 0

#### I. PRODUCT INFORMATION

General Type: Trade Name:

**Embalming Fluid Utility 25 Arterial** 

### II. HAZARDOUS INGREDIENTS

MATERIAL (CAS) Formaldehyde (50-00-0)

% 24.5

**OSHA PEL** TWA/STEL (15) .75ppm/2ppm

**ACGIH TLV** TWA/STEL (15) .3ppm (ceiling)

Possible Carcinogen: NTP, IARC

Methanol (67-56-1)

4

200ppm/NONE

200ppm/250ppm

## III. PHYSICAL DATA

**Boiling Point** Specific Gravity 195°+ 1.08 1

4

Freezing Point Vapor Pressure Solubility in Water

N/A UNKNOWN **COMPLETE** 

Vapor Density **Percent Volatiles** 

**Evaporation Rate** (Butyl Acetate = 1)

Appearance and Odor

Pinkish, creamy liquid with pungent odor.

## IV. FIRE AND EXPLOSION HAZARD DATA

Flash Point

Flammable Limits In Air

Extinguishing Media

Special Fire Fighting **Procedures** 

Unusual Fire and Explosion Hazard

195° F (COC) Combustible Liquid

Lower 6.7 Upper 72

Foam, Dry Chemical, Carbon Dioxide, Water Spray

Wear self-contained breathing apparatus, cool container with water

1

spray. -----

#### V. HEALTH HAZARD DATA

Threshold Limit Value

See Part II

Effects of Overexposure

If swallowed may cause burns, nausea, vomiting, diarrhea, blindness or death. Skin contact may cause burns, dermatitis or serious skin injury. Eye contact may cause burns, inflammation, eye injury or blindness. Inhalation may cause burning of throat and lungs, difficult breathing and collapse, liver damage, nerve damage or blindness. Can be absorbed through skin.

**Emergency and First Aid** 

**Procedures** 

Contact physician immediately. If swallowed give milk or water and induce vomiting by sticking finger down throat and get medical attention. unconscious - give nothing. If eye or skin contact - flush with water for 15 minutes. Remove contaminated clothing, get medical attention. If inhaled remove to fresh air, give artificial respiration if not breathing, get medical attention.

#### VI. REACTIVITY DATA

Stability

Conditions to Avoid Incompatibilities

Hazardous Decomposition Products

Hazardous Decomposition Fi

Hazardous Polymerization

Product is stable

Sparks, heat and open flames

Strong acids and alkalis

At high temperatures may release carbon monoxide or carbon dioxide

Will not occur

## VII. SPILL OR LEAK PROCEDURES

If Material is Spilled Neutralize with sodium sulfite solution and flush to sewer with large

quantity of water - if allowed. Mop up with dry, non-reactive

absorbent and dispose of as solid waste as allowed.

Waste Disposal Method Flush to chemical sewer, incinerate, dispose in sanitary landfill - if

allowed or flush to waste treatment system - if allowed.

## VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection Unnecessary if area is adequately ventilated - use organic vapor mask

if necessary.

Local Ventilation Preferred

Mechanical VentilationAcceptable if necessarySpecial VentilationNot normally requiredOther VentilationNot normally required

Protective Gloves Impervious vinyl or rubber type
Eye Protection Coverall goggles or full face shield

Other Protective Equipment Safety shower, eye wash and full protective clothing is required.

#### IX. SPECIAL PRECAUTIONS

Maintain adequate ventilation and engineering controls to insure exposure levels below OSHA limits. Avoid prolonged inhalation or contact with skin or eyes.

Keep bottles tightly capped. Keep away from heat and flames. Store in cool, dry, well-ventilated area.

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

Utility 25 Arterial Date August 1, 2010