SAFETY DATA SHEET

1. Identification

Product identifier H2O SUPER YELLOW

Other means of identification

Product Code VST-630-18

Recommended use Automotive Refinish Toner

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Pro-Spray Automotive Finishes Limited

Address Unit H, Normandy Lane, Stratton Business Park

Biggleswade, Bedfordshire SG18 8QB United Kingdom

United Kingdom

Telephone General Information +44 (0) 1767 314320

Website prosprayfinishes.com
E-mail colour@pro-spray.co.uk

Emergency phone number Office hours only +44 (0) 1767 314320

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, inhalationCategory 3Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2ASensitization, skinCategory 1Environmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Causes skin irritation. May cause an allergic skin reaction. Causes serious

eye irritation. Toxic if inhaled. Harmful to aquatic life. Harmful to aquatic life with long lasting

Category 3

effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing mist or

vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the

environment. Wear protective gloves/eye protection/face protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Supplemental information

None known.

37.17% of the mixture consists of component(s) of unknown acute inhalation toxicity. 43.62% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 43.62% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
C.I. Pigment Yellow 184		14059-33-7	10 to <20
2-Butoxyethanol		111-76-2	5 to <10
2-methyl-4-isothiazolin-3-one		2682-20-4	0.1 to <1
CIT/MIT		55965-84-9	0.1 to <1
Zinc Phosphate		7779-90-0	0.1 to <1
Other components below reportable lev	rels		70 to <80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance.

Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a POISON CENTER or doctor/physician. Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment, Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants	(29	CFR 1	1910 1000	١
OO. OOHA Table 2-1 Limits for All Containinants	123	01 11	1310.1000	,

Components	Type	Value		
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3		
·		50 ppm		
US. ACGIH Threshold Limit Valu	es			
Components	Туре	Value		
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm		
US. NIOSH: Pocket Guide to Che	emical Hazards			
Components	Туре	Value	Form	
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3		
·		5 ppm		
C.I. Pigment Yellow 184 (CAS 14059-33-7)	Ceiling	0.05 mg/m3	Dust.	

Biological limit values

ACGIH Biological Exposure Indices					
Components	Value	Determinant	Specimen	Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

VST-630-18 Version #: 01 Issue date: 04-11-2015

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Material name: H2O SUPER YELLOW

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColorYellow

Odor Slight. Solvent.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

212 °F (100 °C) estimated

Flash point 143.0 °F (61.7 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.12 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 460.4 °F (238 °C) estimated

Decomposition temperature Not available.

Not available. **Viscosity**

Other information

Density 9.76 lbs/gal

Combustible IIIA estimated Flammability class

Percent volatile 62.1 % estimated

1.17 Specific gravity

VOC 0.8 lbs/gal Material

> 2.2 lbs/gal Coating 93 g/l Material 268 g/l Coating

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Toxic if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Toxic if inhaled. May cause an allergic skin reaction.

Components	Species	Test Results

2-Butoxyethanol (CAS 111-76-2)

Acute Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

> Rat 450 ppm, 4 Hours

Oral

LD50 Guinea pig 1.2 g/kg

> Mouse 1.2 g/kg Rabbit 0.32 g/kg Rat 560 mg/kg

Skin corrosion/irritation Causes skin irritation.

Material name: H2O SUPER YELLOW

^{*} Estimates for product may be based on additional component data not shown.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
2-Butoxyethanol (C	AS 111-76-2)		
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Zinc Phosphate (CA	AS 7779-90-0)		
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.09 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Material name: H2O SUPER YELLOW

VST-630-18 Version #: 01 Issue date: 04-11-2015

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-methyl-4-isothiazolin-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2) Listed. Zinc Phosphate (CAS 7779-90-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
C.I. Pigment Yellow 184	14059-33-7	10 to <20	
2-Butoxyethanol	111-76-2	5 to <10	
Zinc Phosphate	7779-90-0	0.1 to <1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

2-Butoxyethanol (CAS 111-76-2)

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

VST-630-18 Version #: 01 Issue date: 04-11-2015

Material name: H2O SUPER YELLOW

SDS US

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)

C.I. Pigment Yellow 184 (CAS 14059-33-7)

Zinc Phosphate (CAS 7779-90-0)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)

C.I. Pigment Yellow 184 (CAS 14059-33-7)

Zinc Phosphate (CAS 7779-90-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date 04-11-2015

Version # 01

HMIS® ratings Health: 3

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 2 Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Material name: H2O SUPER YELLOW SDS US

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).