



Valspar® Brilliant Metals Spray Paint

No. 66009 – Series

GENERAL DESCRIPTION

Metallic paint adds a polished and sleek finish to surfaces for a decorative flair.

PRODUCT FEATURES

- Brilliant-metal effects
- Flawless spray
- No drip

RECOMMENDED USES

Ideal for wood, metal and more.

COMPOSITION

Net Weight: 11 oz (312 g) solvent based

AVAILABLE COLORS

- Brilliant Gold (66009)
- Brilliant Silver (66010)

SURFACE PREPARATION AND APPLICATION

USE WITH ADEQUATE VENTILATION. Clean and dry surface. Remove dirt, grease, etc. Remove gloss from shiny surfaces. Prime bare metal.

Use outdoors or in a well-ventilated area when temperature is 65–90 °F (18–32 °C). Cover nearby area to protect from spray mist. Shake well for at least 1 minute, listening for rattle of mixing ball. Shake frequently during application. Hold can 8–10 inches from surface. Move can back and forth, releasing button after each stroke. Overlap each stroke. Two (2) thin coats are recommended. Recoat anytime. Dry to touch in 15 minutes.

DO NOT insert pins or other sharp objects into valve opening of can. To prevent clogging after use, turn can upside down and press spray head for 3 seconds.

PRODUCT SPECIFICATIONS

MIR: 1.90 Max

Practical Coverage: varies depending on surface porosity

Dry Time @ 77 °F and 50% Relative Humidity

Recoat: Anytime

Dry to Touch: 15 minutes

Application Temperature: 65–90 °F

CAUTIONS

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL.

66009 Contains: Acetone, Isobutyl Acetate and Petroleum Distillates.

66010 Contains: Cyclohexane, Ethyl 3-Ethoxypropionate and Stoddard Solvent.

All: DANGER! May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F (49 °C). Replace cap after each use. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. NOTICE: Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal.

66010: WARNING: This product contains a chemical known to the State of California to cause cancer.

All: FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.* In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention;* for skin, wash thoroughly with soap and water.

* Call poison control center, hospital emergency room, or physician immediately.

KEEP OUT OF THE REACH OF CHILDREN

EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732

60009: UCA 1.2

66010: UCA 5.2

Manufacturer and Seller make no warranty, expressed or implied, other than replacement of product; the cost of labor for the application of any paint is the customer's responsibility.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

8725 W. Higgins Rd., Chicago, IL 60631

866.222.8714

valsparpaint.com

Revised: 1/5/16

Version: 66009C