PRODUCT NAME: Cuccio Colour Veneer- Color Gel - Tel-Aviv Me All About It January 02, 2014

This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: Cuccio Colour Veneer- Color Gel- Tel-Aviv Me All About It

Product Use: Nail Gel Polish

Manufacturer's Name : Star Nail International, Inc. Chemical Family : UV Gels

Address: 29120 Avenue Paine Proprietary Mix City, State, Zip: Valencia, CA 91355 CAS# N/A

Preparation Date: 01/02/2014

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information may be based on findings from related or similar materials.

- · May be slightly toxic.
- . May cause moderate skin injury (reddening & swelling).

· May cause eye irritation.

FLAMMABLE

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: No specific information is available for this product. Although, this product opposes only slight irritation concern

with all routes of entry.

Eyes: No specific information available. Contains materials that are essentially nonirritating, but contact may cause

slight transient irritation.

Skin: No specific information available. Contains materials that may cause moderate skin injury (reddening and

swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not

occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that may be practically nontoxic. Inhalation No specific information available. Low volatility makes vapor inhalation unlikely.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in

animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OS	% HA
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	50-65
2-Hydroxyethyl Methacryl	ate 868-77-9	212-782-2	НЕМА	N/E	N/E	Not Listed	5-10





MSDS PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Tel-Aviv Me All About It January 02. 2014

Safety Phrases - S2, S7, S16, S24/25, S26

Safety Phrases: S2, S25

Safety Phrases:

Hydroxypropyl Methacrylate	27813-02-1 2	48-666-3	Hydroxypropyl methacrylate	N/E	N/E	Not Listed	5-10
Polyethylene Glycol 400 Dimethacrylate	25852-47-5	N/E	PEG-9 Dimethacrylate	N/E	N/E	Not Listed	1-7
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400ppm	400ppm	Not Listed	0-3
n-Butyl Acetate	123-86-4	204-658-1	Butyl Acetate	150ppm	150ppm	Not Listed	0-3
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400ppm	400ppm	no/no/no	0-3
Hydroxycyclohexyl Phenyl Ketone	947-19-3	213-426-9	Hydroxycyclohexy phenyl ketone	·l N/E	N/E	Not Listed	1-2
TPO	75980-60-8	278-355-8	Trimethylbenzoyl diphenylphosphine oxide	N/E	N/E	Not Listed	0-1
May Contain the following	lowing: Please s	ee Section 16 for	additional compounds				
N/E - None Established N/R - Not Reviewed	N/DA - No Da		* See section 16				
Polyurethane Acrylate Oligomer 2-Hydroxyethyl Methacrylate: Hydroxypropyl Methacrylate: Polyethylene Glycol 400 Dimethacrylate:	Hazard Symbo Hazard Symbo Hazard Symbo Hazard Symbo	ols – Xi Risk Ph ol: Xi Risk Ph	rases – R36/38, R43 S rases: R36/37/38, R43 S	afety Phrases: S14, S3 afety Phrases: S2, S26 afety Phrases: S26, S3 afety Phrases – S26, S	6, S28 6/37		

Hazard Symbol:

SECTION 4: FIRST AID MEASURES

See Section 16 for Risk and Safety Phrase Key

Isopropyl Alcohol:

n-Butyl Acetate:

Ethyl Acetate:

TPO:

First Aid for Eye: Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention

Hazard Symbol – F, Xi Risk Phrases – R11, R36, R37

Hazard Symbol: N/E Risk Phrases: R10, R66, R67

Risk Phrases: R99

Immediately.

First Aid for Skin: Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing

Hazard Symbol – F, Xi Risk Phrases – R11, R36, R66, R67 Safety Phrases – S2, S16, S26, S33

has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion: If appreciable quantities are swallowed, seek medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point	Flammable Limit	Auto Ignition Temperature
(°F/°C)	(vol%)	(vol%)

PRODUCT NAME: Cuccio Colour Veneer- Color Gel - Tel-Aviv Me All About It January 02, 2014

Method:

Extinguishing Media:

Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Instructions:

Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion

exists.

Unusual Hazards:

High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in Explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control

fires since frothing can occur.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Release

Procedures:

Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detregent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

SECTION 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential.

Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheating of product, this will also diminishing the quality of the product. Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above

Storage:

the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times. **Explosion Hazard:** High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

Personal Protective Equipment

General: To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a

hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole

body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection: Wear chemical splash goggles.

PRODUCT NAME: Cuccio Colour Veneer- Color Gel - Tel-Aviv Me All About It January 02, 2014

Skin Protection: Wear impervious gloves (Neoprene).

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN

149.

.....

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appe	earance	Odor & Odor	Odor & Odor Threshhold		Specific Gravity	Viscosity	% Volatile
	slight violet, s liquid	characteristic acrylate odor		N/A	(H2O=1): 1.15	(at 77°F/25°C) 1500-6000cP	By Volume: < 0.5
Boiling Point/Freezi ng Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C : < 0.01	No Data	No Data	No data	Insoluble

Flash Point	Flammable Limit	Auto Ignition Temperature
(°F/°C)	(vol%)	(vol%)

SECTION 10: STABILITY AND REACTIVITY

Stability

Normally Stable:

Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: evolution of heat and increased pressure that could result in carbon monoxide, carbon dioxide.

Hazardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Conditions to Avoid:

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation – Skin	Irritation-Eye
				No information
No information available	No information available	No information available	No information available	available

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

SECTION 12: ECOLOGICAL INFORMATION

PRODUCT NAME: Cuccio Colour Veneer- Color Gel - Tel-Aviv Me All About It January 02, 2014

Ecotoxicological Information

Acute Toxicity to fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability		N/DA	
Chemical Oxygen Demand		N/DA	

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil

SECTION 13: DISPOSAL CONSIDERATIONS

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

SECTION 14: TRANSPORTATION INFORMATION

DOT (49 CFR 172)		
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (Isopr Acetate), 3, PGIII	opyl Alcohol, n-Butyl
Identification Number:	UN1993	
Marine Pollutant:	No	
Special Provisions:	T8,T31	
Emergency Response Guidebook (ERG) #:	128	
IATA (DGR):		
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (Isopr Acetate), 3, PG II	opyl Alcohol, n-Butyl
Class or Division:	3	
UN or ID Number:	UN1993	
Packaging Instructions:		
Emergency Response Guidance (ICAO)#:		
IMO (IMDG):		
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (Isopr Acetate), 3, PGIII	opyl Alcohol, n-Butyl
Class or Division:	3.2	
UN or ID Number:	UN1993	
Special Provisions & Stowage/Segregation:	None	
Emergency Schedule (EmS)#:		
Other Information:	Flash point 49°C	

.....

US Federal	Regulations
------------	-------------

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act: · NONE This product contains no ODS's This product contains the following chemicals listed under the U. S. Clean Water Act Priority Pollutant and Hazardous Substance List:
Clean Water Act: Priority Pollutant	· Butyl Acetate, CAS# 123-86-4
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are:
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): • Ethyl Acetate CAS# 141-78-6, RCRA Code U112
SARA Title III: Section 302 (TPQ)	This product contains the following chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ. Ethyl Acetate CAS# 141-78-6, RQ(lbs.): 5000 Butyl Acetate, CAS# 123-86-4, RQ (Lbs): 5000
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: Immediate (acute) health hazard Delayed (chronic) health hazard Reactive hazard
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: · Isopropyl Alcohol, CAS# 67-63-0
TSCA Section 8(b): Inventory: TSCA Significant New Use Rule:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA pre-manufacture notification requirements. None of the chemicals listed have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-
California No Significant Risk Rule:	86-4 NONE

	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
MA Right-to-Know Law:	
	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
NJ Right-to-Know Law:	
PA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
FL Right-to-Know	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4
MN Right-to-Know	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4

	Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B
	Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS = n/da
	2-Hydroxyethyl methacrylate CAS# 868-77-9 is on the DSL List. WHMIS = n/da
	Isopropyl Alcohol CAS #67-63-0 is on the DSL list. WHMIS = B2, D2B
CDSL: Canadian Inventory	Butyl Acetate CAS #123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B
(on Canadian Transitional List)	Ethyl Acetate CAS# 141-78-6 is on the DSL List. WHMIS = n/da

Labeling according to EC directives – 1999/45/EC

PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Tel-Aviv Me All About It January 02, 2014

European Community:

Gel Polish:



- · RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact.
- · SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 16: ADDITIONAL REGULATORY INFORMATION

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol: Xi – Irritants

F – Flammable

Risk Phrases:

R10 - Flammable; R11 - Highly Flammable; R36 - Irritating to eyes; R43 - May cause sensitization by skin contact; R66 - Repeated exposure may cause skin dryness and cracking; R67 – Vapors may cause drowsiness and dizziness, R36/37/38 - Irritating to eyes, respiratory system and skin; R36/38 - Irritating to eyes and skin

S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; ; S7 Keep container tightly closed; S16 Keep away from sources of ignition – No smoking; S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way; S36 Wear suitable protective clothing; S36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container

Hazard Rating System:

NFPA: Health (2) Flammabilty (2) Reactivity (1)



HMIS: Health (2) Flammability (2) Reactivity (1)

MAY CONTAIN THE FOLLOWING CHEMICALS:

Chemical Identity	CAS Numbers	EINECS #	INCI Name	Exposure	Limits	Carcinogen	%	
				OSHA	ACGIH			
				TWA/STEI	TWA/STEI	IADC/NITD/OSHA		

MSDS
PRODUCT NAME: Cuccio Colour Veneer- Color Gel – Tel-Aviv Me All About It January 02, 2014

Titanium Dioxide	13463-67-7	236-675-5	Titanium 15 r Dioxide/CI77891	mg/m3	10mg/m3	3/no/no	0-2
Yellow Iron Oxide	51274-00-1	257-098-5	Iron Oxides/CI77492	N/E	N/E	Not Listed	0-2
Red Iron Oxide	1309-37-1	215-168-2	Iron Oxide/CI77491	N/E*	N/E	Not Listed	0-2
D&C Red 7	5281-04-9	226-109-5	Red 7/CI15850	N/E	N/E	Not Listed	0-2
Synthetic Red Iron Oxide (maroon)	1309-37-1	N/E	Iron Oxides/CI77491	N/E	N/E	Not Listed	0-2
D&C Orange No. 4	633-96-5	211-199-0	Orange 4/CI15510	N/E	N/E	Not Listed	0-2
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-2
Mica	12001-26-2	310-127-6	Mica	N/E	3mg/m3	Not Listed	0-2
FD&C Yellow #5	1934-21-0	217-699-5	Yellow 5/CI19140	N/DA	N/DA	N/DA	0-2
D&C Red #6	5858-81-1	227-497-9	Red 6/CI15850	N/DA	N/DA	N/DA	0-2
D&C Red #34	6417-83-0	229-142-3	Red 34/CI15880	N/DA	N/DA	N/DA	0-2
Cosmetic Iron Blue	14038-43-8	237-875-5	Ferric Ferrocyanide/CI775	N/DA 510	N/DA	N/DA	0-2
D&C Yellow #10	8004-92-0	N/DA	Yellow 10/CI47005/E104	N/DA	N/DA	N/DA	0-2
Ultramarine Blue	57455-37-5	N/DA	Ultramarines/CI7700)7 N/DA	N/DA	N/DA	0-2
Manganese Violet	10101-66-3	233-257-4	Manganese Violet/CI77742	N/DA	A N/DA	A N/DA	0-2
FD&C Blue #1	3844-45-9	223-339-8	Blue 1/CI42090	N	E N	/E Not List	ed 0-2
D&C Black #2	1333-86-4	215-609-9	Carbon Black/C177266	3.5mg/m3 0.1 mg PAH's/m3 carbon black in presence of polycyclic aromatic hydrocarbon (PAHs)		H's/m3 4/Possib bon black Select presence of Carcino ycyclic matic rocarbon	
N/E - None Established N/A-Not Applicable	N/DA–No Data Ava N/R - Not Reviewe						

DISCLAIMER: This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

PRODUCT NAME: Cuccio Colour Veneer- Color Gel - Tel-Aviv Me All About It January 02, 2014

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. Star Nail International assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

SECTION 17: OTHER INFORMATION

HAZARDOUS MATERIAL INDENTIFICATION SYSTEM (HMIS) RATING:

HEALTH: 2
FLAMMABILITY: 2
REACTIVITY: 1

PERSONAL PROTECTION EQUIPMENT: Gloves and Safety Glasses

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

HEALTH: 2
FLAMMABILITY: 2
REACTIVITY: 1

ABBREVIATIONS:

NA NE	Not Applicable Not Established	ND	Not [Determined
pm	Part per million		G	Gallon

art per million L Milligram Liter mg Gram Mole gm mol Kilogram Micro kg u Pa Pascals р Pico

LCLethal ConcentrationLDLethal DoseTCToxic ConcentrationTDToxic Dose

BOD Biological Oxygen Demand COD Chemical Oxygen Demand

TLm Threshold Limit

DOC Dissolved Organic Carbon

H Hours M Months D Days Y Years

W Weeks

ACGIH American Conference of Governmental Industrial Hygenist

CPR Controlled Product's Regulation
DSL Canadian Domestic Substances List

NDSL Canadian Non-Domestic Substance List IARC International Agency for Research for Cancer

NOEL No Observed Effect Level

NOAEL No Observed Adverse Effect Level OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit
TLV Threshold Limit Value