SAFETY DATA SHEET



Date of issue/Date of revision 18 October 2016 Version 3

Section 1. Identification	
Product name	: WATERBASE CEDAR COARSE (J.)
Product code	: CP-6488 (F1)
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Industrial applications.
Use of the substance/ mixture	: Coating. Paints. Painting-related materials.
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)
Technical Dhane Number	1, 200, 441, 0605, (2:00, cm to E:00, cm EST)

Technical Phone Number : 1-800-441-9695 (8:00 am to 5:00 pm EST)

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 58.6%
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	

Product name WATERBASE CEDAR COARSE (J.)

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.
Response	: IF exposed or concerned: Get medical attention. Photosensitive agents : In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Product name	1	WATERBASE CEDAR COARSE (J.)

Ingredient name	%	CAS number
zinc oxide	≥5.0 - ≤10 ≥1.0 - ≤5.0 <1.0	1317-65-3 1314-13-2 119-61-9

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
	United States Page: 2/12

Date of issue 18 October 2016 Version 3

Product name WATERBASE CEDAR COARSE (J.)

Section 4. First aid measures

	In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Most important symptoms/	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides

Product name WATERBASE CEDAR COARSE (J.)

Section 5. Fire-fighting measures

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	1	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	ive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions Methods and materials for co	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
methous and materials for co	trainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated

Section 7. Handling and storage

Precautions for safe hand	ling
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

United States

Page: 4/12

Product name WATERBASE CEDAR COARSE (J.)

Section 7. Handling and storage

Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
∠ímestone	OSHA PEL (United States, 2/2013).
	TWA: 5 mg/m ³ 8 hours. Form: Respirable
	fraction
	TWA: 15 mg/m ³ 8 hours. Form: Total dust
zinc oxide	OSHA PEL (United States, 2/2013).
	TWA: 5 mg/m ³ 8 hours. Form: Fume
	TWA: 5 mg/m ³ 8 hours. Form: Respirable
	fraction
	TWA: 15 mg/m ³ 8 hours. Form: Total dust
	ACGIH TLV (United States, 3/2015).
	STEL: 10 mg/m ³ 15 minutes. Form:
	Respirable fraction
	TWA: 2 mg/m ³ 8 hours. Form: Respirable
	fraction
benzophenone	None.
	Key to abbreviations

A	= Acceptable Maximum Peak	S	= Potential skin absorption
ACGIH	 American Conference of Governmental Industrial Hygienists. 	SR	 Respiratory sensitization
С	= Ceiling Limit	SS	 Skin sensitization
F	= Fume	STEL	 Short term Exposure limit values
IPEL	 Internal Permissible Exposure Limit 	TD	= Total dust
OSHA	 Occupational Safety and Health Administration. 	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		

Consult local authorities for acceptable exposure limits.

Product name WATERBASE CEDAR COARSE (J.)

Section 8. Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	1	Safety glasses with side shields.
Hand protection		Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves		polyethylene
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Product name WATERBASE CEDAR COARSE (J.)

Section 9. Physical and chemical properties

Appearance

Physical state:Liquid.Color:Not available.Odor:Not available.Odor threshold:Not available.pH:Not available.Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:0.35 (butyl acetate = 1)Vapor density:Not available.Relative density:1.34Density (Ibs / gal):1.118Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity::SatisfieldViscosity::Satisfield% Solid. (w/w)::53% (v/v), 38.59% (w/w)% Solid. (w/w):::% Solid. (w/w)::% Solid. (w/w)			
Odor: Not available.Odor threshold: Not available.Odor threshold: Not available.PH: Not available.Boiling point: >37.78°C (>100°F)Flash point: Closed cup: >93.33°C (>200°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not available.(flammable) limits: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Physical state	1	Liquid.
Odor threshold:Not available.pH:Not available.Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.4 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.34Density (lbs / gal):11.18Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity::Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:::Valitity::Solubility:::::::::::::::::::::::::::::::::::::::	Color	1	Not available.
pH:Not available.Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.4 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.34Density (lbs / gal):11.18Solubility:Insoluble in the following materials: cold water.Partition coefficient: n-octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:53% (v/v), 38.59% (w/w)	Odor	1	Not available.
Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.4 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.34Density (lbs / gal):11.18Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:53% (v/v), 38.59% (w/w)	Odor threshold	1	Not available.
Boiling point: >37.78°C (>100°F)Flash point: Closed cup: >93.33°C (>200°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	рН	4	Not available.
Flash point: Closed cup: >93.33°C (>200°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Melting point	4	Not available.
Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not available.(flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Boiling point	4	>37.78°C (>100°F)
Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Flash point	1	Closed cup: >93.33°C (>200°F)
Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Auto-ignition temperature	1	Not available.
Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Decomposition temperature	1	Not available.
(flammable) limitsEvaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Flammability (solid, gas)	1	Not available.
Vapor pressure: 2.3 kPa (17.4 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)		1	Not available.
Vapor density: Not available.Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Evaporation rate	1	0.35 (butyl acetate = 1)
Relative density: 1.34Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Vapor pressure	1	2.3 kPa (17.4 mm Hg) [room temperature]
Density (lbs / gal): 11.18Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Vapor density	1	Not available.
Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Relative density	1	1.34
Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 53% (v/v), 38.59% (w/w)	Density(lbs / gal)	:	11.18
octanol/water Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt) Volatility 53% (v/v), 38.59% (w/w)	Solubility	1	Insoluble in the following materials: cold water.
Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt) Volatility : 53% (v/v), 38.59% (w/w)	Partition coefficient: n-	1	Not available.
Volatility : 53% (v/v), 38.59% (w/w)	octanol/water		
	Viscosity	4	Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
% Solid. (w/w) : 61.41	Volatility	4	53% (v/v), 38.59% (w/w)
	% Solid. (w/w)	4	61.41

Section 10. Stability and reactivity

	United States Page: 7/12
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Product name WATERBASE CEDAR COARSE (J.)

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result		Sp	oecies	Dose	Exposure
penzophenone	LD50 Derr LD50 Oral	-	Ra Ra	abbit at	3.535 g/kg >10 g/kg	-
Conclusion/Summary	: There are	e no data a	available on the n	nixture itself	f.	
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There are	e no data a	available on the n	nixture itself	f.	
Eyes	: There are	e no data a	vailable on the r	nixture itsel	f.	
Respiratory	: There are	e no data a	vailable on the n	nixture itself	f.	
<u>Sensitization</u>						
Conclusion/Summary						
Skin	: There are	e no data a	vailable on the r	nixture itself	f.	
Respiratory	: There are	e no data a	vailable on the n	nixture itself	f.	
<u>Mutagenicity</u>						
Conclusion/Summary	: There are	e no data a	vailable on the n	nixture itsel	f.	
Carcinogenicity						
Conclusion/Summary	: There are	e no data a	vailable on the r	nixture itself	f.	
Classification						
Product/ingredient name	OSHA	IARC	NTP			
penzophenone	-	2B	-			
Carcinogen Classification	n code:					
IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + Not listed/not regi	e a human card	cinogen; Reas	sonably anticipated	l to be a huma	an carcinogen	
Reproductive toxicity						
Conclusion/Summary	: There are	no data av	vailable on the m	ixture itself.		
<u>Feratogenicity</u>						
Conclusion/Summary	: There are	no data av	vailable on the m	ixture itself.		
Specific target organ toxicity	<u>/ (single exp</u>	<u>oosure)</u>				
<u>specific larger organ toxicity</u>						
Not available.						
	<u>/ (repeated (</u>	exposure)				

Target organs

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes.

Category 2

Aspiration hazard

United States	Page: 8/12
---------------	------------

Product name WATERBASE CEDAR COARSE (J.)

Section 11. Toxicological information

Not available.

Information on the likely routes of exposure

Potential acute health effect	ts
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	toms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	ects
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Not available.	

Product name WATERBASE CEDAR COARSE (J.)

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
zínc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - Daphnia magna - Neonate	72 hours 48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzophenone	3.18	12.02	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

Product name WATERBASE CEDAR COARSE (J.)

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	hazard	Sudden release of pressure			Delayed (chronic) health hazard
b enzophenone	Yes.	No.	No.	No.	Yes.

<u>SARA 313</u>

Chemical name

Supplier notification

: zinc oxide

<u>CAS number</u> 1314-13-2 Concentration 1 - 5

United States Page: 11/12

Product name WATERBASE CEDAR COARSE (J.)

Section 15. Regulatory information

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 1 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Ass	ociation (U.S.A.)			
Health : 1 Flammability : 1 Instability : 0				
Date of previous issue	: 4/26/2016			
Organization that prepared the MSDS	: EHS			
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations 			

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.