

95 SECTION I
PRODUCT IDENTIFICATION



MATERIAL SAFETY DATA SHEET

WESTERN AUTOMOTIVE FINISHES
101 PROSPECT AVE. N.W.
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
DATE OF PREPARATION
1 - FEB - 95

INFORMATION TELEPHONE NO.
(216) 566-2902

©1995, Western Automotive Finishes

WES-THANE™ Acrylic Urethane Mixing Colors W7800/W1

SECTION II														
CAS No.	HAZARDOUS INGREDIENT (percent by weight)	ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mmHg)	W7800 Bright White	W7801 Black	W7802 Medium Metallic	W7803 Bright Yellow	W7804 Medium Yellow	W7805 Earthy Yellow	W7806 Yellow	W7807 Violet	W7808 Orange
54742-47-9	Mineral Spirits	100	100	PPM	2.0			2						
95-63-6 §	1,2,4-Trimethylbenzene	25	25	PPM	2.0		1	1				1	1	
78-93-3 §	Methyl Ethyl Ketone	200	200	PPM	70.0			1						
123-86-4	n-Butyl Acetate	<300> 150	<300> 150	PPM	10.0	23	47	50	26	29	34	39	43	21
112-07-2 §	2-Butoxyethyl Acetate	<200> 50	<200> 50	PPM	1.0		2	1	1	1	1	2	2	1
108-65-6	1-Methoxy-2-Propanol Acetate	Not Established				5	9		6	7	8	10	9	5
13463-67-7	Titanium Dioxide	10	10(5)	Mg/M3 as Dust (Resp. Fraction)		47								
1333-86-4	Carbon Black	3.5	3.5	Mg/M3 as Dust			3							
1344-37-2	Lead Chromate	0.05	0.05	Mg/M3					41	34				
12656-85-8	Molybdate Orange	0.05	0.05	Mg/M3										
§ Lead compound (% Lead)														51
§ Chromium compound (% Chromium)									41(25.0)	34(23.1)				51(23.3)
Weight per Gallon (lbs.)									41(4.6)	34(4.9)				51(5.6)
VOC - Total Volatile Organic Compounds (lbs./gal.)						12.6	8.17	6.23	12.3	11.4	10.0	8.76	8.35	14.2
VOC - Less Water and exempt Solvents (lbs./gal.)						3.97	5.10	4.89	4.48	4.64	4.66	4.79	4.84	4.20
Photochemically Reactive						3.97	5.10	4.89	4.48	4.64	4.66	4.79	4.84	4.20
Flash Point (°F)						No	No	No	No	No	No	No	No	No
DOT Storage Category						72	72	72	72	72	72	72	72	72
HMIS (NFPA) Rating (health - flammability - reactivity)						1B	1B	1B	1B	1B	1B	1B	1B	1B
PAINT-SAFE® Personal Protection						2.3.0	2.3.0	2.3.1	2.3.0	2.3.0	2.3.0	2.3.0	2.3.0	2.3.0
						J3	J0	J3	J3	J3	J3	J3	J3	J3

AA 100 AA

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.

Section VIII -- PROTECTION INFORMATION

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flames. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to the contents may not be immediately apparent. Some containers may not be immediately apparent.

Rebreathing products may cause a health hazard. SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible explosion or explosion when exposed to extreme heat.

OSHA PEL 15 mg./m3 (total)

Recommendations for proper use: Ventilation, skin protection and respiratory system. May cause nervous system depression.

Exposure to Lead may result in unconsciousness and possibly death. Certain Mixing Colors contain Lead (see TABLE and PRODUCT LABEL). Acute occupational exposure to Lead is uncommon, but results in effects and symptoms similar to chronic exposure to Lead.

FOR SCIENCE BY TELETYPE SIGNALING SYSTEM

None generally recognized.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If on SKIN: Remove contaminated clothing and shoes. Flush skin with large amounts of water for 15 minutes. Get medical attention.

CHROMIUM PIGMENT PIGMENTS

Certain Mixing Colors contain Lead and/or Chromiumates (See TABLE and PRODUCT LABEL). Chronic overexposure to Lead may result in damage to the blood-forming, nervous, urinary, and reproductive systems (including embryotoxic effects). Symptoms include abdominal discomfort or pain, constipation, loss of appetite, metallic taste, nausea, anisomnia, nervous

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, blood-forming, and reproductive systems.

Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

Section X — OTHER REGULATORY INFORMATION

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of chemicals or other additives to this product may substantially alter the composition and hazards of the products. Since conditions of use are outside our control, we make no warranties express or implied, and assume no liability in connection with any use of this information.

IV-40 to IV-43