



METHYLSILANE

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	METHYLSILANE
Product Code(s)	G-447
UN-No	UN3161
Recommended Use	Compressed gas.
Synonyms	Monomethylsilane, Monosilylmethane, Silylmethane
Supplier Address*	Linde Gas North America LLC - Linde Merchant Production Inc. - Linde LLC 575 Mountain Ave. Murray Hill, NJ 07974 Phone: 908-464-8100 www.lindeus.com Linde Gas Puerto Rico, Inc. Las Palmas Village Road No. 869, Street No. 7 Catano, Puerto Rico 00962 Phone: 787-641-7445 www.pr.lindegas.com Linde Canada Limited 5860 Chedworth Way Mississauga, Ontario L5R 0A2 Phone: 905-501-1700 www.lindecana.com * May include subsidiaries or affiliate companies/divisions. For additional product information contact your local customer service.
Chemical Emergency Phone Number	Chemtrec: 1-800-424-9300 for US/ 703-527-3887 outside US

2. HAZARDS IDENTIFICATION

DANGER!		
Emergency Overview		
Extremely flammable liquid and vapor May form explosive mixtures with air Irritating to eyes, respiratory system and skin Contents under pressure Keep at temperatures below 52°C / 125°F		
Appearance Colorless	Physical State Compressed gas.	Odor Mild repulsive

OSHA Regulatory Status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
-------------------------------	---

Potential Health Effects

Principle Routes of Exposure	Inhalation. Eye contact. Skin contact.
Acute Toxicity	
Inhalation	Inhalation effects of methylsilane are unknown. Toxic effects are expected to be similar to effects caused by silane. Exposure to silane may cause headache and nausea.
Eyes	Contact may form silicic acid causing irritation. Contact with rapidly expanding gas near the point of release may cause frostbite. Ignited gas can cause thermal burns.
Skin	Contact may form silicic acid causing irritation. Contact with rapidly expanding gas near the point of release may cause frostbite. Ignited gas can cause thermal burns.
Skin Absorption Hazard	No known hazard in contact with skin.
Ingestion	Not an expected route of exposure.
Chronic Effects	None known.
Aggravated Medical Conditions	Skin disorders. Respiratory disorders. Pre-existing eye disorders.
Environmental Hazard	See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Volume %	Chemical Formula
Methyl Silane	992-94-9	>99	CH ₃ SiH ₃

4. FIRST AID MEASURES

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation persists.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Inhalation	PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF INHALATION OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Conscious inhalation victims should be assisted to an uncontaminated area and inhale fresh air. If breathing is difficult, administer oxygen. Unconscious persons should be moved to an uncontaminated area and, as necessary, given artificial resuscitation and supplemental oxygen. Treatment should be symptomatic and supportive.
Ingestion	None under normal use. Get medical attention if symptoms occur.
Notes to Physician	Methylsilane reacts with air to produce silicon oxide. Irrigate burns to the extent determined by a physician as necessary to remove silicon dioxide.
Protection of First-aiders	Remove all sources of ignition.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Extremely flammable liquefied gas. May be spontaneously flammable in air. Containers may explode when heated.
----------------------	---

Suitable Extinguishing Media Carbon dioxide (CO₂). Foam. Dry powder. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Unsuitable Extinguishing Media Do not use halogenated extinguishing agents or foam.

Hazardous Combustion Products Silicon dioxide. Hydrogen gas.

Explosion Data

Sensitivity to Mechanical Impact None

Sensitivity to Static Discharge Yes

Specific Hazards Arising from the Chemical Will form explosive mixtures with air. Reaction with water may release methane. Continue to cool fire exposed cylinders until flames are extinguished. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists.

Protective Equipment and Precautions for Firefighters If possible, stop the flow of gas. Do not extinguish the fire until supply is shut off as otherwise an explosive-ignition may occur. If the fire is extinguished and the flow of gas continues, use increased ventilation to prevent build-up of explosive atmosphere. Ventilation fans must be explosion proof. Use non-sparking tools to close container valves.

Isolate spill or leak area for at least 100 meters (330 feet) in all directions. Vapors from liquefied gas are initially heavier than air and spread along ground. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.). Vapors may travel to source of ignition and flash back. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn.

Use water spray to cool surrounding containers. Be cautious of a Boiling Liquid Evaporating Vapor Explosion, BLEVE, if flame is impinging on surrounding containers.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Use personal protective equipment. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Releases of methylsilane into air can produce silicon dioxide. This white powder may remain suspended in air for some time if produced from a release.

Environmental Precautions Prevent spreading of vapors through sewers, ventilation systems and confined areas.

Methods for Containment Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is in container or container valve, contact the appropriate emergency telephone number in Section 1 or call your closest Linde location.

Methods for Cleaning Up Return cylinder to Linde or an authorized distributor.

7. HANDLING AND STORAGE

Handling

Handle in sealed, purged system. Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof. Remove all sources of ignition. Use only in ventilated areas. "NO SMOKING" signs should be posted in storage and use areas.

Materials may accumulated behind outlet plug. Wear appropriate protective equipmet and face outlet away when removing plug and connecting cylinder.

Never attempt to lift a cylinder by its valve protection cap. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Use equipment rated for cylinder pressure. Use backflow preventive device in piping.

Use an adjustable strap wrench to remove over-tight or rusted caps. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing leak to occur. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

Storage

Outside or detached storage is preferred. Protect from physical damage. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Keep at temperatures below 52°C / 125°F. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, pamphlet CGA-P1, Safe Handling of Compressed Gases in Containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Engineering Measures

Explosion proof ventilation systems. Eyewash stations. Showers.

Ventilation

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Face-shield. Tightly fitting safety goggles.

Skin and Body Protection

Work gloves and safety shoes are recommended when handling cylinders. Wear fire/flame resistant/retardant clothing.

Respiratory Protection

General Use

No special protective equipment required.

Emergency Use

Use positive pressure airline respirator with escape cylinder or self contained breathing apparatus for oxygen-deficient atmospheres (<19.5%).

Hygiene Measures

Wear suitable gloves and eye/face protection. Automated systems are recommended to continuously monitor for release of methylsilane. Automatic flow shutdown and alarms to alert personnel following releases.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colorless.	Odor	Mild repulsive.
Odor Threshold	No information available.	Physical State	Compressed gas
Flash Point	No information available.	Autoignition Temperature	No information available.
Decomposition Temperature	No information available.	Boiling Point/Range	-57.5°C / -71.5°F
Freezing Point	-156.1°C / -248.8°F	Molecular Weight	46.14
Water Solubility	No information available	Evaporation Rate	No information available
Vapor Pressure	1425 kPa @ 20°C	Vapor Density	0.628 @ -58°C / -71°F (liquid)
VOC Content (%)	Not applicable.	Flammability Limits in Air	
		Upper	Not applicable
		Lower	Not applicable

10. STABILITY AND REACTIVITY

Stability	Stable.
Incompatible Products	Oxidizing agents. Halogens.
Conditions to Avoid	Heat, flames and sparks.
Hazardous Decomposition Products	Hydrogen gas. Silicon dioxide. Methane.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

LD50 Oral:	No information available.
LD50 Dermal:	No information available.
LC50 Inhalation:	>5000 ppm/1 hr (ISO, CGA P-20)
Repeated Dose Toxicity	No information available.

Chronic Toxicity

Chronic Toxicity	None known.
Carcinogenicity	Contains no ingredient listed as a carcinogen.

Irritation	No information available.
Sensitization	No information available.
Reproductive Toxicity	No information available.
Developmental Toxicity	No information available.
Synergistic Materials	None known.

Target Organ Effects None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Ozone depletion potential; ODP; (R-11 = 1): Does not contain ozone depleting chemical (40 CFR Part 82).

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Linde for proper disposal.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name	Liquefied gas, flammable, n.o.s.
Hazard Class	2.1
Subsidiary Class	None
UN-No	UN3161
Description	UN3161,Liquefied gas, flammable, n.o.s.(Methyl Silane),2.1
Emergency Response Guide Number	115

TDG

Proper Shipping Name	Liquefied gas, flammable, n.o.s.
Hazard Class	2.1
UN-No	UN3161
Description	UN3161,LIQUEFIED GAS, FLAMMABLE, N.O.S.(Methyl Silane),2.1

MEX

Proper Shipping Name	Liquefied gas, flammable, n.o.s.
Hazard Class	2.1
UN-No	UN3161
Description	UN3161, Liquefied gas, flammable, n.o.s.(Methyl Silane),2.1

IATA

UN-No	UN3161
Proper Shipping Name	Liquefied gas, flammable, n.o.s.
Hazard Class	2.1
ERG Code	10L
Description	UN3161,Liquefied gas, flammable, n.o.s.(Methyl Silane),2.1
Maximum Quantity for Passenger	Forbidden
Maximum Quantity for Cargo Only	150 kg
Limited Quantity	No information available.

IMDG/IMO

Proper Shipping Name	Liquefied gas, flammable, n.o.s.
Hazard Class	2.1
UN-No	UN3161
EmS No.	F-D, S-U
Description	UN3161, Liquefied gas, flammable, n.o.s.(Methyl Silane),2.1

ADR

Proper Shipping Name	Liquefied gas, flammable, n.o.s.
Hazard Class	2.1
UN-No	UN3161
Classification Code	2F
Description	UN3161, Liquefied gas, flammable, n.o.s.(Methyl Silane),2.1

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL	Does not Comply
NDSL	Complies
EINECS/ELINCS	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	Yes

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Risk and Process Safety Management Programs

This material, as supplied, does not contain any regulated substances with specified thresholds under 40 CFR Part 68.
This product does not contain any substances regulated as Highly Hazardous Chemicals pursuant to the 29 CFR Part 1910.110.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA/SARA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated by state right-to-know regulations.

International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases

B1 Flammable gas

D2B Toxic materials



16. OTHER INFORMATION

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	05-Mar-2010
Revision Date	02-Sep-2010
Revision Number	1
Revision Note	(M)SDS sections updated. 1.

<u>NFPA</u>	Health Hazard 1	Flammability 4	Stability 2	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 0	Flammability 4	Physical Hazard 2	Personal Protection -

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition.

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Linde LLC, Linde Merchant Production, Inc. or Linde Gas North America LLC (or any of their affiliates and subsidiaries) and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet