

NITROGEN DIOXIDE Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name NITROGEN DIOXIDE

Product Code(s) G-61

UN-Number UN1067

Recommended Use Compressed gas.

Synonyms Nitrogen Oxide; Nitrogen Peroxide

Supplier Address* Linde Gas North America LLC - Linde Merchant Production Inc. - Linde LLC

575 Mountain Ave. Murray Hill, NJ 07974 Phone: 908-464-8100 www.lindeus.com

Linde Gas Puerto Rico, Inc. Las Palmas Village

Road No. 869, Street No. 7 Catano, Puerto Rico 00962 Phone: 787-641-7445 www.pr.lindegas.com

Linde Canada Limited 5860 Chedworth Way Mississauga, Ontario L5R 0A2 Phone: 905-501-1700 www.lindecanada.com

* May include subsidiaries or affiliate companies/divisions.

For additional product information contact your local customer service.

Chemical Emergency Phone Number Chemtrec: 1-800-424-9300 for US/703-527-3887 outside US

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Oxidizer Fatal if inhaled

The product causes burns of eyes, skin and mucous membranes Accelerates combustion and increases risk of fire Contents under pressure

Keep at temperatures below 52°C / 125°F

Appearance Reddish-brown in air

Physical State Compressed gas.

Odor Acrid

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

Potential Health Effects

Principle Routes of Exposure Eye contact. Skin contact. Inhalation.

Acute Toxicity

Inhalation Fatal if inhaled. Inhalation of corrosive fumes/gases may cause coughing, choking, headache,

dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate.

Eyes Gas can cause irritation. Contact with liquid causes severe corrosive action.

Skin Gas can cause irritation. Contact with liquid causes severe corrosive action.

Skin Absorption Hazard No known hazard in contact with skin.

Ingestion Not an expected route of exposure. Ingestion causes burns of the upper digestive and respiratory

tract.

Chronic Effects No known effect based on information supplied

Aggravated Medical Conditions Skin disorders. Pre-existing eye disorders. Respiratory disorders.

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No		Chemical Formula
Nitrogen dioxide	10102-44-0	>99	NO ₂

4. FIRST AID MEASURES

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact Immediate medical attention is required. In case of contact with substance, immediately flush eyes

with running water for at least 30 minutes. Remove contact lenses, if present, after the first 5

minutes, then continue rinsing.

Skin Contact Immediate medical attention is required. Wash off immediately with soap and plenty of water for at

least 15 minutes while removing all contaminated clothing and shoes.

Inhalation PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF INHALATION OVEREXPOSURE. RESCUE

PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Conscious inhalation victims should be assisted to an uncontaminated area and inhale fresh air. If breathing is difficult, administer oxygen. Unconscious persons should be moved to an uncontaminated area and,

as necessary, given artificial resuscitation and supplemental oxygen. Treatment should be symptomatic and supportive. Any physical exertion during this period should be discouraged as it may increase the severity of the pulmonary edema or chemical pneumonitis. Bed rest is indicated.

Ingestion None under normal use. Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties Oxidizer. May vigorously accelerate combustion.

Suitable Extinguishing Media Use water spray or fog; do not use straight streams. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS

LEAK CAN BE STOPPED.

Unsuitable Extinguishing Media Do not use halogenated extinguishing agents or foam.

Hazardous Combustion Products Nitric acid and nitrous acid.

Explosion Data

Sensitivity to Mechanical Impact None

Sensitivity to Static Discharge None

Specific Hazards Arising from the

Chemical

Explodes on contact with alcohols, hydrocarbons, organic materials and fuel. Will ignite combustible materials (wood, paper, oil, debris, etc.). Continue to cool fire exposed cylinders until flames are extinguished. Cylinders may rupture under extreme heat. Damaged cylinders should be

handled only by specialists.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Additional chemical protective clothing may be required to

protect from toxic decomposition products.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure

adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and

clothing.

Environmental Precautions Prevent spreading of vapors through sewers, ventilation systems and confined areas. Prevent

product from entering drains.

Methods for Containment Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is

in container or container valve, contact the appropriate emergency telephone number in Section 1

or call your closest Linde location.

Methods for Cleaning Up Return cylinder to Linde or an authorized distributor.

7. HANDLING AND STORAGE

Handling Anhydrous nitrogen dioxide is non-corrosive to most metals at normal temperatures. It does

corrode copper and its alloys. Teflon® is the preferred gasket material.

Use only in ventilated areas. Never attempt to lift a cylinder by its valve protection cap. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Use equipment rated for cylinder pressure. Use backflow preventive device in piping. Never insert an object (e.g. wrench, screwdriver, pry bar,etc.) into valve cap openings. Doing so may damage valve, causing leak to occur. "NO SMOKING" signs should be posted in storage and use areas.

Use an adjustable strap wrench to remove over-tight or rusted caps. Close valve after each use and when empty. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

Storage

Protect from physical damage. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Keep at temperatures below 52°C / 125°F. Full and empty cylinders should be segregrated. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, pamphlet CGA-P1, Safe Handling of Compressed Gases in Containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Nitrogen dioxide	STEL: 5 ppm	(vacated) STEL: 1 ppm	IDLH: 20 ppm
10102-44-0	TWA: 3 ppm	(vacated) STEL: 1.8 mg/m³	STEL: 1 ppm
		Ceiling: 5 ppm	STEL: 1.8 mg/m ³
		Ceiling: 9 mg/m³	_

Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir.,

1992).

Engineering Measures Showers. Eyewash stations. Ventilation systems. Exhaust gas should be vented to a gas treatment

system.

Ventilation Use ventilation adequate to keep exposures below recommended exposure limits.

Personal Protective Equipment

Eye/Face Protection Tightly fitting safety goggles. Face-shield.

Skin and Body Protection Appropriate protective and chemical resistant gloves, clothing and splash protection, or fully

encapsulating vapor protective clothing to prevent exposure. For materials of construction consult protective clothing manufacturer's specifications. Saranex @ is generally effective for >8 hour

exposures.

Respiratory Protection

General Use If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory

protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with

current local regulations.

Emergency Use Use positive pressure air line respirator or self-contained breathing apparatus for exposure over

exposure limits or emergency use. For exposures above IDLH, an additional escape bottle is

required.

Hygiene Measures Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after

handling the product. When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Keep away from food, drink and animal feeding stuffs.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Reddish-brown in air. Odor Acrid.

Odor Threshold No information available Physical State Compressed gas

Flash Point No information available. Autoignition Temperature No information available. Decomposition Temperature No information available. Boiling Point/Boiling Range 21.1 °C / 70 °F

Freezing Point -11.20 °C / 11.84 °F Molecular Weight 45.98

Water Solubility Decomposes Evaporation Rate No information available

Vapor Pressure 14.8 psia @ STP Vapor Density 2.83 (air = 1)

VOC Content (%) Not applicable. Flammability Limits in Air

Upper Not applicable Lower Not applicable

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible Products Strong oxidizing agents. Organic material. Combustible materials.

Conditions to Avoid Violent reaction with cyclohexane, fluorine, nitrobenzene, petroleum and toluene. Temperatures

above 160 °C / 320 °F.

Hazardous Decomposition Products nitric acid and nitrous acid.

Hazardous Polymerization Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

LD50 Oral: No information available.

LD50 Dermal: No information available.

LC50 Inhalation: Per CGA P-20: LC50: 115 ppm/1hr. (Rat)

Inhalation The vapor is highly toxic and hazardous because its ability to cause delayed chemical pneumonitis

and pulmonary edema. The absence of acute irritation limits its warning properties.

Repeated Dose Toxicity No information available.

Chronic Toxicity

Chronic Toxicity None known.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Irritation Concentrations of 10-20 ppm nitrogen dioxide are mildly irritating to the skin and eye.

Sensitization No information available.

No information available. Reproductive Toxicity

No information available. **Developmental Toxicity**

Synergistic Materials None known.

Target Organ Effects Eyes. Respiratory system. Skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Ozone depletion potential; ODP; (R-11 = 1): Does not contain ozone depleting chemical (40 CFR Part 82).

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container

PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP

IN PLACE to Linde for proper disposal.

Do not re-use empty containers. Contaminated Packaging

14. TRANSPORT INFORMATION

DOT

Proper shipping name Dinitrogen tetroxide

Hazard Class 2.3 **Subsidiary Class** 5.1, 8 **UN-Number** UN1067

Description UN1067, Dinitrogen tetroxide, 2.3, (5.1, 8)

Additional Description: "Toxic-Inhalation Hazard Zone A". If net weight of product is greater

than or equal to 10 lbs., the shipping description must also contain the letters "RQ".

Additional Marking Requirements: "Inhalation Hazard". If net weight of product is greater than or equal to

10 lbs., the container must also be marked with the letters "RQ".

Emergency Response Guide Number 124

TDG

Proper Shipping Name Dinitrogen tetroxide

Hazard Class 2.3 **Subsidiary Class** (5.1), (8)**UN-Number** UN1067

Description UN1067, DINITROGEN TETROXIDE, 2.3(5.1), (8)

MEX

Proper Shipping Name Dinitrogen tetroxide

Hazard Class 2.3
Subsidiary Class 5.1, 8
UN-Number UN1067

Description UN1067 Dinitrogen tetroxide,2.3

IATA

UN-Number UN1067

Proper Shipping Name Dinitrogen tetroxide

Hazard Class2.3Subsidiary Class5.1, 8ERG Code2PX

Description UN1067, Dinitrogen tetroxide, 2.3(5.1, 8)

Maximum Quantity for Passenger Forbidden
Maximum Quantity for Cargo Only Forbidden

Limited Quantity

No information available.

IMDG/IMO

Proper Shipping Name Dinitrogen tetroxide

Hazard Class2.3Subsidiary Class5.1, 8UN-NumberUN1067EmS No.F-C, S-W

Description UN1067, Dinitrogen tetroxide, 2.3 (5.1, 8)

ADR

Proper Shipping Name Dinitrogen tetroxide (Nitrogen dioxide)

Hazard Class2.3UN-NumberUN1067Classification Code2TOC

Description UN1067 Dinitrogen tetroxide (Nitrogen dioxide),2.3,

ADR/RID-Labels 5.1, 8

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Complies
EINECS/ELINCS Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous
	Quantities			Substances
Nitrogen dioxide	10 lb			Χ

Risk and Process Safety Management Programs

This material, as supplied, contains one or more regulated substances with specified thresholds under 40 CFR Part 68 or regulated as a highly hazardous chemical pursuant to the 29 CFR Part 1910.110 with specified thresholds:

Chemical Name	U.S CAA (Clean Air Act) -	U.S CAA (Clean Air Act) -	U.S OSHA - Process Safety
	Accidental Release Prevention	Accidental Release Prevention	Management - Highly
	- Toxic Substances	- Flammable Substances	Hazardous Chemicals
Nitrogen dioxide			250 lb

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA/SARA

This material, as supplied, contains one or more substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	TPQ
Nitrogen dioxide	10 lb	10 lb	100 lb TPQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Nitrogen dioxide	Х	Х	Х		Х

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Nitrogen dioxide		Mexico: TWA 3 ppm
		Mexico: TWA 6 mg/m ³
		Mexico: STEL 5 ppm
		Mexico: STEL 10 mg/m ³

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class
A Compressed gases
C Oxidizing materials
D1A Very toxic materials
E Corrosive material
D2B Toxic materials



Prepared By Product Stewardship

23 British American Blvd.

Latham, NY 12110 1-800-572-6501

Issuing Date 17-Mar-2010

Revision Date 27-Sep-2013

Revision Number 2

Revision Note Not applicable.

<u>NFPA</u>	Health Hazard 3	Flammability 0	Stability 0	Physical and Chemical Hazards OX
HMIS	Health Hazard 3	Flammability 0	Physical Hazard 1	Personal Protection -

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition.

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Linde LLC, Linde Merchant Production, Inc. or Linde Gas North America LLC (or any of their affiliates and subsidiaries) and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet