

3E Company3207 Grey Hawk Court, Suite 200
Carlsbad, CA 92010

U.S. Toll Free: 1-800-451-8346 or 1-760-602-8703

North America: 1-800-931-0537/Mexico 00-1-800-931-0537 or 1-760-602-8822

Fax: 1-760-602-8888

Email: msds@3ecompany.com

**Material Safety Data Sheet
Transmittal Form**

February 23, 2016

Request #: 296195

Processed By: rensmin

Recipient:

ISABELLE BIZUB

Email: ISABELLE.BIZUB@US.BOSCH.COM

Requester:

ISABELLE BIZUB

EMPLOYEE

Email: ISABELLE.BIZUB@US.BOSCH.COM

Thank you for using 3E's MSDS Paperless Compliance™ service. This service may eliminate the requirement to maintain MSDS on site. Below is a list of the MSDS you requested. Please verify that the MSDS sheet(s) enclosed/attached match what you have ordered.

The information contained in this facsimile transmission is intended only for the use of the individual or entity named above and is privileged and confidential. If you are not the intended recipient, please do not read, copy, use or disclose this communication to others. Any dissemination, distribution or copying of this information other than to the person or entity named above is strictly prohibited. If you have received this facsimile in error, you should shred this information.

3E COMPANY does not develop, prepare, or review the contents of any MSDS; the MSDS is prepared by the manufacturer. The statements, technical information and recommendations contained herein are transmitted without warranty or guarantee of any kind, expressed or implied, by 3E COMPANY. Furthermore, 3E COMPANY assumes no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.

PID/VID	Manufacturer ORDERED/Actual	Product Name ORDERED/Actual	UPC	Item
v7528030	/Robert Bosch Tool Corporation	80111 WORK OIL/Skil 80111 Lubricant		

END OF ORDER DETAIL - Request# 296195



3E Company is North American's leader in hazardous materials information management. 3E simplifies compliance for over 75,000 business locations worldwide. Services include: MSDS on Demand, 3E On-line, Government Disclosures, Hazmat Transportation Services, Emergency Response and Chemical Spill/Exposure Hotlines. For more information call **1-800-360-3220 or 1-760-602-8700 or visit us at www.3ecompany.com**



SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product Name: Skil 80111 Lubricant

Use of the product: Machine oil

Date of issue: 02/04/2015

Manufacturer/Distributor:
Robert Bosch Tool Corporation
1800 W. Central Road
Mt. Prospect, IL 60056

For More Information Call:
(Monday-Friday, 8:00 AM– 5:00 PM CST)
Bosch Customer Service
(877) 267-2499

In Case Of Emergency Call:
(24 Hours/Day, 7 Days/Week)
(877) 303-0891

SECTION 2: HAZARDS IDENTIFICATION

Hazard class and hazard category
Aspiration Hazard Category 1



Danger

Hazard statements

Health Hazard
H304 May be fatal if swallowed and enters airways

Precautionary statements

Prevention
P273 Avoid release to the environment.
Response
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.
Storage
P405 Store locked up.
Disposal
P501 Dispose of contents and container in accordance with local regulations.



SAFETY DATA SHEET

Appearance and Odor:	Amber. Black. Viscous liquid. Semi-solid at ambient temperature. Slight hydrocarbon.
Health Hazards:	Not classified as dangerous for supply or conveyance.
Safety Hazards:	Not classified as flammable but will burn.
Environmental Hazards:	Not classified as dangerous for the environment.
Health Hazards:	Not expected to be a health hazard when used under normal conditions.
Inhalation:	Under normal conditions of use, this is not expected to be a primary route of exposure.
Skin Contact:	Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Contact:	May cause slight irritation to eyes.
Ingestion:	Low toxicity if swallowed. Ingestion may result in nausea, vomiting and/or diarrhea.
Other Information:	Used oil may contain harmful impurities.
Signs and Symptoms:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.
Aggravated Medical Condition:	Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin.
Environmental Hazards:	Not classified as dangerous for the environment.
Additional Information:	Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.
Highly refined mineral oils and additives.

SECTION 4: FIRST AID MEASURES

General Information:	Not expected to be a health hazard when used under normal conditions.
Inhalation:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
Eye Contact:	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician:	Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Flash point:	Typical 323 °C / 613 °F (COC) > 218 °C / 424 °F (COC)
Upper / lower:	Typical 1-10 %(V)(based on mineral oil)
Flammability or Explosion limits	
Auto ignition temperature:	> 320 °C / 608 °F
Specific Hazards:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.



SAFETY DATA SHEET

Suitable Extinguishing: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only

Media

Unsuitable Extinguishing Media: Do not use water in a jet

Protective Equipment for when Firefighters: Proper protective equipment including breathing apparatus must be worn approaching a fire in a confined space.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective measures: Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Clean Up Methods: Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional Advice: Local authorities should be advised if significant spillages cannot be contained.

SECTION 7: HANDLING AND STORAGE

General Precautions: Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Handling: Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Storage: Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: 0 - 50 °C / 32 - 122 °F

Recommended Materials: For containers or container linings, use mild steel or high density polyethylene.

Unsuitable Materials: PVC.

Additional Information: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.



SAFETY DATA SHEET

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m ³	Notation
Oil mist, mineral	ACGIH	TWA(Mist.)		5 mg/m ³	
Oil mist, mineral	ACGIH	STEL (Mist.)		10mg/m ³	

Exposure Controls:

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Personal Protective Equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory Protection:

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapors [boiling point >65 °C (149 °F)].

Hand Protection:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye Protection:

Wear safety glasses or full face shield if splashes are likely to occur.

Protective Clothing: Monitoring Methods:

Skin protection not ordinarily required beyond standard issue work clothes. Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Environmental Exposure: Controls

Minimize release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation



SAFETY DATA SHEET

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance :	Amber. Black. Viscous liquid. Semi-solid at ambient temperature.
Odour :	Slight hydrocarbon.
pH :	Not applicable.
Initial Boiling Point and : Boiling Range	> 280 °C / 536 °F estimated value(s)
Pour point :	Typical -9 °C / 16 °F
Dropping point	Data not available
Flash point :	Typical 323 °C / 613 °F (COC) >218 °C / 424 °F (COC)
Upper/ lower Flammability : or Explosion limits	Typical 1-10 %(V) (based on mineral oil)
Auto-ignition temperature :	> 320 °C / 608 °F
Vapour pressure :	< 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Specific gravity :	Typical 0.929 at 15 °C / 59 °F Typical 0.995 at 15 °C / 59 °F
Density :	Typical 929 kg/m3 at 15 °C / 59 °F Typical 995 kg/m3 at 15 °C / 59 °F
Water solubility :	Negligible.
n-octanol/water partition : coefficient (log Pow)	> 6 (based on information on similar products)
Kinematic viscosity :	Typical 35.3 mm2/s at 100 °C / 212 °F
Vapour density (air=1) :	> 1 (estimated value(s))
Evaporation Rate:	Data not available

SECTION 10: STABILITY AND REACTIVITY

Stability :	Stable.
Conditions to Avoid :	Extremes of temperature and direct sunlight.
Materials to Avoid :	Strong oxidizing agents.
Hazardous Decomposition : Products	Hazardous decomposition products are not expected to form during normal storage.

SECTION 11: TOXICOLOGICAL INFORMATION

Basis for Assessment :	Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity :	Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity :	Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit
Acute Inhalation Toxicity :	Not considered to be an inhalation hazard under normal conditions of use.
Skin Irritation :	Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Irritation :	Expected to be slightly irritating.
Respiratory Irritation :	Inhalation of vapors or mists may cause irritation.
Sensitisation :	Not expected to be a skin sensitizer.
Repeated Dose Toxicity :	Not expected to be a hazard.
Mutagenicity :	Not considered a mutagenic hazard.
Carcinogenicity :	Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
Reproductive and Developmental Toxicity:	Not expected to be a hazard



SAFETY DATA SHEET

Additional Information : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity: Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically nontoxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

Mobility: Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

Persistence/degradability: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

Bioaccumulation: Contains components with the potential to bioaccumulate.

Other Adverse Effects: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical

SECTION 13: DISPOSAL CONSIDERATIONS

Material Disposal: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

Container Disposal: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation: Disposal should be in accordance with applicable regional, national, and local laws and regulations

SECTION 14: TRANSPORT INFORMATION

US Department of Transportation Classification (49CFR)

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.



SAFETY DATA SHEET

SECTION 15: REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Notification Status

EINECS

All components listed or polymer exempt.

TSCA

Not all components listed.

SARA Hazard Categories
(311/312):

No SARA 311/312 Hazards.

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

SECTION 16: OTHER INFORMATION

Although Robert Bosch Tool Corporation has attempted to provide current and accurate information herein, Robert Bosch Tool Corporation makes no representations regarding the accuracy or completeness of the information and assumes no liability for any loss, damage, injury of any kind which may result from or arise out of the use of or reliance on the information by any person.

It shall be the responsibility of the customer purchasing this product to ensure that all employees/users of this product are familiar with and trained in the handling, use and hazards associated with this product as contained herein. This responsibility shall also extend directly to the user.