

## Safety Data Sheet

### Xylene

Version 2.2

Revision Date: 10/07/2016

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name** : Xylene

#### Recommended use of the chemical and restrictions on use

**Recommended use** : Solvent.

#### Manufacturer or supplier's details

**Company** : Nexeo Solutions, LLC.  
**Address** : 3 Waterway Square Place Suite 1000  
The Woodlands, TX. 77380  
United States of America

#### Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC (1-800-424-9300)

**Additional Information:** : Responsible Party: Product Safety Group  
E-Mail: msds@nexeosolutions.com  
SDS Requests: 1-855-429-2661  
SDS Requests Fax: 1-281-500-2370  
Website: www.nexeosolutions.com

#### SECTION 2. HAZARDS IDENTIFICATION

##### GHS Classification

Flammable liquids : Category 3  
Acute toxicity (Inhalation) : Category 4  
Acute toxicity (Dermal) : Category 4  
Skin irritation : Category 2  
Eye irritation : Category 2A

##### GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 + H332 Harmful in contact with skin or if inhaled  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

**Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

## Safety Data Sheet

### Xylene

Version 2.2

Revision Date: 10/07/2016

CAS-No.	Chemical Name	Weight %
1330-20-7	Mixed xylenes	90 - 100
100-41-4	**Ethylbenzene	0 - 35
108-88-3	**Toluene	0 - 1
98-82-8	**Cumene	0 - 1

Any Concentration shown as a range is due to batch variation.

**Special Notes:** : Mixed Xylenes contains the isomers o-, m-, p- Xylene, and Ethylbenzene. Trace amounts of Toluene and Benzene may also be present as impurities., \*\* Other substances in the product which may present a health or environmental hazard.

#### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

**Safety Data Sheet**

**Xylene**

Version 2.2

Revision Date: 10/07/2016

- Hazardous combustion products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

regulations.

Conditions for safe storage : No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH		
		STEL	150 ppm	ACGIH		
		TWA	100 ppm 435 mg/m3	OSHA Z-1		
		TWA	100 ppm	ACGIH		
		STEL	150 ppm	ACGIH		
		100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL		
		ST	125 ppm 545 mg/m3	NIOSH REL		
		TWA	100 ppm 435 mg/m3	OSHA Z-1		
		TWA	100 ppm 435 mg/m3	OSHA P0		
		STEL	125 ppm 545 mg/m3	OSHA P0		
		108-88-3	**Toluene	TWA	20 ppm	ACGIH
				TWA	100 ppm 375 mg/m3	NIOSH REL
ST	150 ppm 560 mg/m3			NIOSH REL		
TWA	200 ppm			OSHA Z-2		
CEIL	300 ppm			OSHA Z-2		
Peak	500 ppm			OSHA Z-2		
TWA	100 ppm 375 mg/m3			OSHA P0		
STEL	150 ppm 560 mg/m3			OSHA P0		
98-82-8	**Cumene			TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL		
		TWA	50 ppm 245 mg/m3	OSHA Z-1		

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

		TWA	50 ppm 245 mg/m3	OSHA P0
--	--	-----	---------------------	---------

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : Clear, Colorless

Odour : Hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Freezing Point (Melting point/range) : -48 °C (-54 °F)

Boiling Point (Boiling point/boiling range) : 137 - 143 °C (279 - 289 °F)

Flash point : 27 °C (81 °F)

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

	Method: closed cup
Evaporation rate	: 0.76 - 0.8 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1 %(V)
Vapour pressure	: 6 - 7 mmHg @ 20 - 25 °C (68 - 77 °F)
Relative vapour density	: 3.7(Air = 1.0)
Relative density	: 0.862 - 0.872 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: 0.862 - 0.872 g/cm <sup>3</sup> @ 20 °C (68 °F)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 432 - 464 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: Calculated 0.618 - 0.753 mPa.s @ 20 °C (68 °F)
Viscosity, kinematic	: 0.717 - 0.864 mm <sup>2</sup> /s @ 20 °C (68 °F)

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Strong oxidizing agents

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

**Components:**

**1330-20-7:**

Acute inhalation toxicity : LC50 (Rat, male): 6700 ppm  
Exposure time: 4 h  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg  
Assessment: The component/mixture is moderately toxic after single contact with skin.

**Skin corrosion/irritation**

**Components:**

**1330-20-7:**

Species: Rabbit  
Exposure time: 24 h  
Result: Irritating to skin.

**Serious eye damage/eye irritation**

**Components:**

**1330-20-7:**

Species: Rabbit  
Result: Irritating to eyes.

**Carcinogenicity**

**IARC**

Group 2B: Possibly carcinogenic to humans

100-41-4 \*\*Ethylbenzene

98-82-8 \*\*Cumene

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**ACGIH**

Confirmed animal carcinogen with unknown relevance to humans

100-41-4 \*\*Ethylbenzene



**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

**Further information**

**Product:**

Remarks: Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

**Components:**

**108-88-3:**

Partition coefficient: n-  
octanol/water : log Pow: 2.73

**98-82-8:**

Partition coefficient: n-  
octanol/water : log Pow: 3.55 (23 °C)

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App. A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.  
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**DOT (Department of Transportation):**  
UN1307, XYLENES, 3, III

**IATA (International Air Transport Association):**  
UN1307, XYLENES, 3, III

**IMDG (International Maritime Dangerous Goods):**  
UN1307, XYLENES, 3, III, Flash Point:27 °C(81 °F)

**SECTION 15. REGULATORY INFORMATION**

**WHMIS Classification** : B2: Flammable liquid  
D2B: Toxic Material Causing Other Toxic Effects

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Mixed xylenes	1330-20-7	100	100
**Ethylbenzene	100-41-4	1000	2857

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Immediate (Acute) Health Hazard  
Fire Hazard

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

100-41-4 \*\*Ethylbenzene  
108-88-3 \*\*Toluene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7 Mixed xylenes  
100-41-4 \*\*Ethylbenzene  
108-88-3 \*\*Toluene

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

**Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene
108-88-3	**Toluene
71-43-2	**Benzene
91-20-3	**Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene
108-88-3	**Toluene
71-43-2	**Benzene
91-20-3	**Naphthalene

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

100-41-4	**Ethylbenzene
108-88-3	**Toluene

**US State Regulations**

**Massachusetts Right To Know**

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 35 %
71-43-2	**Benzene	0 - 0.02 %

**Pennsylvania Right To Know**

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 35 %
98-82-8	**Cumene	0 - 1 %
108-88-3	**Toluene	0 - 1 %
71-43-2	**Benzene	0 - 0.02 %

**New Jersey Right To Know**

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 35 %
108-88-3	**Toluene	0 - 1 %

**California Prop 65**

	WARNING! This product contains a chemical known to the State of California to cause cancer.
100-41-4	**Ethylbenzene
98-82-8	**Cumene
71-43-2	**Benzene
91-20-3	**Naphthalene
	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
108-88-3	**Toluene
71-43-2	**Benzene

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

**Safety Data Sheet**  
**Xylene**


Version 2.2

Revision Date: 10/07/2016

- AICS : On the inventory, or in compliance with the inventory
- NZIoC : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PHIL : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION**

**NFPA:**



**HMIS III:**

HEALTH	<b>2*</b>
FLAMMABILITY	<b>3</b>
PHYSICAL HAZARD	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) [MSDS@nexeosolutions.com](mailto:MSDS@nexeosolutions.com).

**Revision Date** : 10/07/2016

**Legacy SDS:** : R0004340, 100000006769

**Material number:**

16109065, 779350, 16063696, 102351, 776944, 763953, 710729, 710728, 708716, 707260, 706448, 638918, 568063, 554061, 554060, 554200, 508616, 508582, 508489, 70145, 70881, 70227, 70442, 53546, 70136, 87256, 53755, 103201, 85972, 103204, 86307, 102898, 69592, 70082, 85965, 54057, 70432, 86513, 102683, 102433, 86815, 103194, 508229, 508294, 508230, 39908, 22253, 22252, 22033, 22034, 20526, 20524, 16066675, 16061583, 16066710, 16084135, 16075696, 16056826, 16056828, 16056827, 16056829, 16056825, 16041807, 16040131, 16036781, 16017302, 16005979, 781040, 102986, 102359, 86304, 53758, 102348, 69917, 502710, 20530, 20529, 20528, 20525, 20523, 20522

**Safety Data Sheet**  
**Xylene**

Version 2.2

Revision Date: 10/07/2016

<b>Key or legend to abbreviations and acronyms used in the safety data sheet</b>			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%