MATERIAL SAFETY DATA SHEET

PRODUCT NAME: FOAM AWAY HEAVY DUTY BATHROOM CLEANER

PRODUCT CODE: Z92 (formerly 1646) PRODUCT CLASS: ACID CLEANER

RATINGS: 4-EXTREME 3 SFRIOUS 2-SIGNIFICANT 1-SLIGHT 0-MINIMUM

HMIS HAZARD RATING: HEALTH FLAMMARII ITY REACTIVITY PERSONAL PROTECTION

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CELLO PROFESSIONAL PRODUCTS ADDRESS: 1354 Old Post Road, Havre de Grace, MD 21078 EMERGENCY PHONE - INFOTRAC 24 HOURS: 800-535-5053

REVISED: 7/1/06

INFORMATION PHONE: 800-638-4850

SECTION II -	HAZARDOUS	INGREDIENTS/SARA	III INFORMATION

		VAPOR PRESSURE		WEIGHT
REPORTABLE COMPONENTS	CAS NUMBER	mm Hg	@ TEMP	PERCENT
HYDROXYACETIC ACID	79-14-1	N/A	N/A	6.30
DU PONT:AEL 10mg/m3 8&12HR TWA				
* PHOSPHORIC ACID	7664-38-2	8.2	25°C	4.25

ACGIH: TLV 1mg/cu.m OSHA: PEL 1mg cu.m; STEL 3mg/cu.m

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 121°F VAPOR DENSITY: Heavier than air **EVAPORATION RATE:** Slower than water APPEARANCE: Colorless liquid **pH:** 1.5 ± 0.5

SPECIFIC GRAVITY (H2O=1): 1.04 VAPOR PRESSURE: NE **SOLUBILITY IN WATER: Completely** ODOR: Cherry **VOLATILE**: 90.54%

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NONE FLASH METHOD: SETA FLASH

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: If involved in a fire use foam, CO2 or water fog.

SPECIAL FIREFIGHTING PROCEDURES: Spray water on cartons involved in fire to keep them from igniting. Wear self-contained breathing apparatus due to the possible toxic fumes from plastic

containers and or the vaporization of potentially harmful chemicals. (See section II)

UNUSUAL FIRE AND EXPLOSION HAZARDS: Area will become slippery if material is released.

SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Avoid product contact with soft metals such as aluminum, tin and zinc. INCOMPATIBILITY (MATERIALS TO AVOID): Alkaline materials, oxidizing agents, contact with metals HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Nitrogen, carbon dioxide, carbon monoxide HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: High concentrations are irritating to the eyes and respiratory tract. May cause headache, dizziness, nausea and vomiting.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Corrosive to skin, could cause blindness if gotten in eyes

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Absorption through skin may cause headache, nausea, dizziness, and vomiting

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Harmful if swallowed, may cause burns to the mouth and esophagus.

HEALTH HAZARDS (ACUTE AND CHRONIC): Contact with eyes can cause corneal damage. Extended overexposure can cause kidney/liver damage, dizziness, headaches, nausea, vomiting CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No NOT LISTED

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Pre-existing pulmonary, liver and/or kidney disorders may be aggravated by overexposure to this material **EMERGENCY AND FIRST AID PROCEDURES:**

IF IN EYES: Immediately flush with plenty of warm water for 15 minutes while keeping eyelids apart for maximum irrigation. If irritation persists contact physician.

IF ON SKIN: Wash off with large amounts of soap and water. If irritation persists contact a physician. Wash contaminated clothing before re-use.

IF INHALED: If victim complains of headache, dizziness or nausea, remove victim to fresh air. If breathing becomes difficult or condition persists, contact a physician.

IF INGESTED: Rinse mouth with water. Drink milk of magnesia or lime water. If these are not available drink large quantities of water. Do not induce vomiting. Seek immediate medical attention. Never give anything by mouth to an unconscious victim.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike area to contain material. Area may become slippery. Neutralize with lime or soda ash. Absorb product onto porous material such as sand, diatomaceous earth or commercial absorbent material. Shovel up into leak proof containers.

WASTE DISPOSAL METHOD: Consult local, state and or federal authorities for proper disposal.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near oxidizers, alkalies and base metals. Keep from excessive heat and keep from freezing. Do not store near consumables. Keep out of reach of children.

OTHER PRECAUTIONS: Read and follow all directions. Use in a manner consistent with product intent.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: NIOSH approved vapor respirator in the absence of proper environmental control

VENTILATION: Good ventilation is required. In the absence of good ventilation mechanical devices are recommended

PROTECTIVE GLOVES: Chemical resistant gloves recommended.

EYE PROTECTION: Safety splash goggles recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Solvent resistant clothing and boots are recommended

WORK/HYGIENIC PRACTICES: Wash hands after use and before eating, drinking, or smoking. Remove contaminated clothing and wash before reuse.

SECTION IX - REGULATORY INFORMATION

ALL INGREDIENTS OF THIS PRODUCT ARE LISTED ON THE US TOXIC SUBSTANCE CONTROL ACT (TSCA) INVENTORY.

This product is a DOT hazardous material. BILL of LADING (gallons): "Corrosive liquids, n.o.s. (contains Hydroxyacetic and phosphoric acids), 8, UN1760, II" BILL of LADING (quarts): "Consumer commodity, ORM-D (compound cleaning)"

The ingredients from Section II are subject to the following reporting requirements:

MA - The Massachusetts Hazardous Substance List NJ - The New Jersey Right-to-Know Hazardous Substance List PA - The Pennsylvania Hazardous Substance List

SECTION X - DISCLAIMER

^{*} Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. # Indicates hazardous chemical(s) subject to the reporting requirements of section 312 of Title III and of 40 CFR 370.