## MATERIAL SAFETY DATA SHEET

41750111

# **UNOCAL®**

Product Name: UNOCAL C-3 FLUID 10W Product Code No: 03990XX11

Page 1 of 7/10/8 Issue Date:

#### **MANUFACTURER:**

UNOCAL REFINING & MARKETING DIVISION UNION OIL COMPANY OF CALIFORNIA 1201 W. 5TH STREET LOS ANGELES, CALIFORNIA 90017

CONTACT FOR FURTHER INFORMATION: MSDS COORDINATOR (213) 977-7589 Transportation Emergencies: Call CHEMTREC (800) 424-9300 Cont. U.: (202) 483-7616 (Collect. from Alaska & Hawaii Health Emergencies: CALL LOS ANGELES POISON INFORMATION CENTER (24 hrs (213) 664-2121

#### PRODUCT IDENTIFICATION

PRODUCT NAME:

UNOCAL C-3 FLUID 10W

SYNONYMS:

UNION C-3 FLUID 10W

**GENERIC NAME:** 

TRANSMISSION OILS

CHEMICAL FAMILY: PETROLEUM HYDROCARBON

DOT PROPER

SHIPPING NAME:

NOT APPLICABLE

ID NUMBER:

NONE

SECTION I - INGREDIENTS

TLV UNITS **AGENCY** 

OIL MIST, IF GENERATED

5.00 MG/M3 OSHA

**FULL TERM TWA** 

TYPE

THE IDENTITIES OF INGREDIENTS THAT ARE TRADE SECRETS ARE EXCLUDED FROM THIS LIST.

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

\*\*\*EMERGENCY\*\*\*

Have physician call LOS ANGELES POISON INFORMATION CENTER (24 hrs.) (213) 664-2121

#### EYE CONTACT:

FOR DIRECT CONTACT, FLUSH THE AFFECTED EYE(S) WITH CLEAN WATER. IF IRRITATION OR REDNESS DEVELOPS, SEEK MEDICAL ATTENTION.

# **SKIN CONTACT:**

DO NOT USE GASOLINES, THINNERS OR SOLVENTS TO REMOVE PRODUCT FROM SKIN. WIPE MATERIAL FROM SKIN AND REMOVE CONTAMINATED CLOTHING. CLEANSE AFFECTED AREA(S) THOROUGHLY BY WASHING WITH SOAP AND WATER AND, IF NECESSARY, A WATERLESS SKIN CLEANSER. IF IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.

Page 2 of 4 Issue Date: 7/10/85

SECTION II - EMERGENCY AND FIRST AID PROCEDURES \*\*\*EMERGENCY\*\*\*

Have physician call LOS ANGELES POISON

INFORMATION CENTER (24 hrs.) (213) 664-21

## **INHALATION (BREATHING):**

IF IRRITATION OF NOSE OR THROAT DEVELOPS, MOVE AWAY FROM SOURCE OF EXPOSURE AND INTO FRESH AIR. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING OR IF BREATHING DIFFICULTIES DEVELOP, ARTIFICIAL RESPIRATION OR OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SEEK IMMEDIATE MEDICAL ATTENTION.

# INGESTION (SWALLOWING):

IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2 TO 3 CUPS OF MILK OR WATER TO DRINK. SEEK MEDICAL ATTENTION. TO PHYSICIAN: EMESIS OR LAVAGE IS NOT RECOMMENDED FOR INGESTIONS OF MINUTE QUANTITIES OR TASTES OF MOST HYDROCARBONS. MEDICAL OPINION IS DIVIDED FOR LARGER INGESTIONS. EMESIS OR LAVAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM PRODUCTS WHICH HAVE A HIGH ORAL TOXICITY. GASTRIC LAVAGE WITH A CUFFED ENDOTRACHEAL TUBE IS RECOMMENDED BY SOME PHYSICIANS TO PREVENT ASPIRATION.

# SECTION III - POTENTIAL ADVERSE HEALTH EFFECTS

#### EYE CONTACT:

THIS MATERIAL MAY CAUSE EYE IRRITATION. DIRECT CONTACT MAY CAUSE BURNING, TEARING AND REDNESS.

# SKIN CONTACT:

THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DERMATITIS.

#### <u>inhalation (Breathing):</u>

EXPOSURE TO MISTS, OR PROLONGED OR REPEATED EXPOSURE TO FUMES OR VAPORS THAT MAY BE GENERATED WHEN THIS MATERIAL IS HEATED, MAY CAUSE IRRITATION OF NOSE AND THROAT.

## INGESTION (SWALLOWING):

ACCIDENTAL INGESTION OF THIS MATERIAL MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

# SECTION IV - SPECIAL PROTECTION INFORMATION

#### VENTILATION:

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE IN MAINTAINING AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

# RESPIRATORY PROTECTION:

IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED EXPOSURE LIMITS, A SUITABLE FILTER-TYPE RESPIRATOR SHOULD BE WORN. (SEE SECTION I.)

## **PROTECTIVE GLOVES:**

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

## EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY IS RECOMMENDED.

Product Name: UNDCAL C-3 FLUID 10W

Product Code No: 03990XX11

Page 3 of Issue Date: 7/10

SECTION IV - SPECIAL PROTECTION INFORMATION

#### OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN WORK AREA FOR FLUSHING EYES AND SKIN. BARRIER CREAMS THAT ARE SPECIFIC FOR OIL-BASED MATERIALS ARE RECOMMENDED WHEN GLOVES ARE IMPRACTICAL.

SECTION V - REACTIVITY DATA

## STABILITY:

STABLE

# INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS. EXTENDED EXPOSURE TO HIGH TEMPERATURES MAY CAUSE DECOMPOSITION.

#### **HAZARDOUS DECOMPOSITION PRODUCTS:**

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

# **HAZARDOUS POLYMERIZATION:**

**WILL NOT OCCUR** 

SECTION VI - SPILL OR LEAK PROCEDURES

\*\*\*HIGHWAY OR RAILWAY SPILLS\*\*\*
Call CHEMTREC (800) 424-9300 Cont. U.S.
(Collect) (202) 483-7616 from Alaska & Haw

## PRECAUTIONS IN CASE OF RELEASE OR SPILL:

COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS. ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBANT. CONTACT FIRE AUTHORITIES AND APPROPRIATE STATE/LOCAL AGENCIES. IF SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS ZONE, OR ADJOINING SHORELINES, NOTIFY COAST GUARD NATIONAL RESPONSE CENTER (PHONE NUMBER 800-424-8802).

#### WASTE DISPOSAL METHOD:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

# HANDLING AND STORAGE PRECAUTIONS:

STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION V). AVOID GENERATING OIL MISTS WHILE HANDLING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR OIL-SOAKED CLOTHING OR SHOES.

# SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

NFPA HEALTH HAZARD: 0
HAZARD FLAMMABILITY: 1
CLASS REACTIVITY: 0
OTHER:

HAZARD RANKING
0 = LEAST
1 = SLIGHT
2 = MODERATE
3 = HIGH
4 = EXTREME

DOT FLAMMABILITY CLASSIFICATION

FLASH POI

NOT REGULATED

200 F 392 C Product Name: UNOCAL C-3 FLUID 10W Product Code No: 03990XX11

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

# **EXTINGUISHING MEDIA:**

EXTINGUISH WITH DRY CHEMICAL, CO2, WATER SPRAY, FOAM, SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

#### FIRE & EXPLOSION HAZARDS:

THIS MATERIAL WILL BURN, BUT WILL NOT IGNITE READILY.

#### FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK.

SECTION IX - PHYSICAL DATA

APPROX. BOILING RANGE

VAPOR DENSITY

EVAPORATION\_RATE

**X VOLATILE** 

ABOVE 600 F (316) C HEAVIER THAN AIR

SLOWER THAN ETHER

NEGLIGIBLE

X SOLUBILITY IN WATER

SPECIFIC GRAVITY

**APPEARANCE** 

**NEGLIGIBLE** 

0.88 - 0.89

CLEAR, RED LIQUID

ODOR

CHARACTERISTIC

ISSUE DATE: \_7/10/85

PRODUCT CODE NO. 03990XX11

PREV. DATE: \_\_\_\_\_

PREV. PROD. CODE NO. \_

MSDS NO:

PREV. MSDS NO: \_

## DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOMEVER, NO HARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER HARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.