

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Product Code: 11885993, 11886009

Intended Use of the Product

Lubricant

Name, Address, and Telephone of the Responsible Party

Company

West Marine
500 Westridge Drive
Watsonville, CA 95076
(831)728-2700

www.westmarine.com

Emergency Telephone Number

Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Eye Irrit. 2A H319

Carc. 1B H350

Asp. Tox. 1 H304

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H304 - May be fatal if swallowed and enters airways.
H319 - Causes serious eye irritation.
H350 - May cause cancer.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - IF SWALLOWED: Immediately call a poison center or doctor.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Contains trace amounts of benzene, a regulated human carcinogen. Benzene has the potential to cause anemia and other blood diseases, including leukemia, after repeated and prolonged exposure. Exposure to light hydrocarbons in the same boiling range as this product has been associated in animal studies with systemic toxicity. May release small amounts of hydrogen sulfide upon decomposition.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Distillates, petroleum, hydrotreated heavy paraffinic	(CAS No) 64742-54-7	60 - 100	Carc. 1B, H350 Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	(CAS No) 68037-01-4	3 - 7	Asp. Tox. 1, H304
Zinc, bis[O,O-bis(1,3-dimethylbutyl) phosphorodithioato-S,S']-, (T-4)-	(CAS No) 2215-35-2	0.5 - 1.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Butanedioic acid, (tetrapropenyl)-	(CAS No) 27859-58-1	0.1 - 0.7	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Phosphorodithioic acid, mixed O,O-bis(sec-butyl and isooctyl) esters, zinc salts	(CAS No) 113706-15-3	0.1 - 0.3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

* A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Small amounts of material which enter the mouth should be rinsed out until the taste is dissipated.

Most Important Symptoms and Effects Both Acute and Delayed

General: May cause cancer. Aspiration hazard. Causes serious eye irritation.

Inhalation: May cause irritation to the respiratory tract. In high concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.

Skin Contact: May cause mild skin irritation.

Eye Contact: Causes serious eye irritation. Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Ingestion: Ingestion is likely to be harmful or have adverse effects. The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

Chronic Symptoms: May cause cancer.

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Dry powder, alcohol-resistant foam, water in large amounts, carbon dioxide (CO₂)

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Unidentified organic compounds.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Handle in accordance with good industrial hygiene and safety practice.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Ventilate area. Stop leak if safe to do so. Eliminate ignition sources. Evacuate unnecessary personnel.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Precautions for Safe Handling: Avoid all unnecessary exposure. Do not handle until all safety precautions have been read and understood. Use appropriate personal protection equipment (PPE).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Reducing agents.

Specific End Use(s) Lubricant

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Consumer Exposure Controls: Do not eat, drink or smoke during use

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Light brown liquid
Odor	: Parrafinic
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: > 100 °C (212 °F)
Flash Point	: 222 °C (431.6 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 0.865
Solubility	: Not water soluble.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Reducing agents.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Hydrocarbons. Aldehydes. Hydrogen sulfide. Phosphorus oxides. Sulfur oxides. Zinc oxide. Oxides of calcium.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract. In high concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation. Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

Chronic Symptoms: May cause cancer.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LD50 Oral Rat	> 15 g/kg
Zinc, bis[O,O-bis(1,3-dimethylbutyl) phosphorodithioato-S,S'], (T-4)- (2215-35-2)	
LD50 Oral Rat	2000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Zinc, bis[O,O-bis(1,3-dimethylbutyl) phosphorodithioato-S,S'], (T-4)- (2215-35-2)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
EC50 Daphnia 1	4.0 - 6.0 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	25 - 50 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and Degradability

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40	
Persistence and Degradability	Not established.

Bioaccumulative Potential

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40	
Bioaccumulative Potential	Not established.

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Hazardous waste due to toxicity.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport

UN Proper Shipping Name Not regulated for transport

Transport Hazard Class(es)

Additional Information Not available

Transport by sea Not regulated for transport

Air transport Not regulated for transport

Marine Pollutant No

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Phosphorodithioic acid, mixed O,O-bis(sec-butyl and isooctyl) esters, zinc salts (113706-15-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Zinc, bis[O,O-bis(1,3-dimethylbutyl) phosphorodithioato-S,S']-, (T-4)- (2215-35-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Butanedioic acid, (tetrapropenyl)- (27859-58-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
1-Decene, homopolymer, hydrogenated (68037-01-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

State or local regulations	
California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity	
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Zinc, bis[O,O-bis(1,3-dimethylbutyl) phosphorodithioato-S,S']-, (T-4)- (2215-35-2)	
U.S. - Maine - Chemicals of High Concern	
U.S. - Minnesota - Chemicals of High Concern	
U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins	
Butanedioic acid, (tetrapropenyl)- (27859-58-1)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

1-Decene, homopolymer, hydrogenated (68037-01-4)


U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---



Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

Phosphorodithioic acid, mixed O,O-bis(sec-butyl and isooctyl) esters, zinc salts (113706-15-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Zinc, bis[O,O-bis(1,3-dimethylbutyl) phosphorodithioato-S,S']-, (T-4)- (2215-35-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Butanedioic acid, (tetrapropenyl)- (27859-58-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 07/30/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation: dust,mist)	Acute toxicity (inhalation: dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2

West Marine Premium 4 Stroke Outboard Oil Full Synthetic 10W40

Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H340	May cause genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Party Responsible for the Preparation of This Document

West Marine

Phone Number: (831)728-2700

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS