

SAFETY DATA SHEET

Issuing Date 30-June-2015

Revision Date 27-Oct-2015

Revision Number 6



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Through the Roof (cartridge grade)

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Caulking

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Sashco, Inc.

Supplier Address 10300 E. 107th Place
Brighton
CO
80601
US

Supplier Phone Number Phone:303-286-7271
Contact Phone303-286-7271

Supplier Email stunney@sashco.com

Emergency telephone number 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B



Carcinogenicity	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

GHS Label elements, including precautionary statements**Emergency Overview**

Signal word	Danger
Hazard Statements Causes skin irritation May cause genetic defects May cause cancer Suspected of damaging fertility or the unborn child May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Highly flammable liquid and vapor	
	
Appearance Clear	Physical state Paste Liquid
	Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see supplemental first aid instructions on this label)

Skin

If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

54.612% of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed

May be harmful in contact with skin

Harmful to aquatic life with long lasting effects

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Solvent naphtha (petroleum), light aliphatic	64742-89-8	15 - 40	*
Toluene	108-88-3	7 - 13	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact

Get medical attention if irritation develops and persists. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. Aspiration into lungs can produce severe lung damage. If breathing has stopped,



give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Some may be transported hot. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Uniform Fire Code

Flammable Liquid: I-B

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces. Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

Environmental precautions

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection	Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid	Odor	Solvent
Appearance	Viscous paste	Odor Threshold	No information available
Color	Clear		
<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	Not applicable	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	111 °C / 232 °F	None known	
Flash Point	9 C / 48 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	0.88	None known	
Water Solubility	Immiscible in water	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause irritation (based on components).

Skin contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Repeated exposure may cause skin dryness or cracking. Causes skin irritation (based on components).

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h

Information on toxicological effects



Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard. Contains a known or suspected reproductive toxin.

STOT - single exposure No information available.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure (STOT RE).

Chronic Toxicity Contains a known or suspected carcinogen. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected reproductive toxin. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects. Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects.

Target Organ Effects Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Reproductive System. Central Nervous System (CNS). Kidney. Liver. Gastrointestinal tract (GI).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

2,688.00 mg/kg

ATEmix (dermal)

3,608.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist)

52.80 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Solvent naphtha (petroleum), light aliphatic 64742-89-8	72h EC50: = 4700 mg/L (Pseudokirchneriella subcapitata)			
Toluene 108-88-3	96h EC50: > 433 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 12.5 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 15.22 - 19.05 mg/L (Pimephales promelas) 96h LC50: 5.89 - 7.81 mg/L (Oncorhynchus mykiss) 96h LC50: 14.1 - 17.16 mg/L (Oncorhynchus mykiss) 96h LC50: = 12.6 mg/L (Pimephales promelas) 96h LC50: = 5.8 mg/L (Oncorhynchus mykiss) 96h LC50: 11.0 - 15.0 mg/L (Lepomis macrochirus) 96h LC50: = 54 mg/L (Oryzias latipes) 96h LC50: = 28.2 mg/L (Poecilia reticulata) 96h LC50: 50.87 - 70.34 mg/L (Poecilia reticulata)	EC50 = 19.7 mg/L 30 min	48h EC50: 5.46 - 9.83 mg/L 48h EC50: = 11.5 mg/L

Persistence and Degradability

No information available.

Chemical Name	Log Pow
Toluene 108-88-3	2.65

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001 U220

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Toluene 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D

TDG

UN-No. UN1133
Proper Shipping Name ADHESIVES
Hazard Class 3
Packing Group III
Description UN1133, ADHESIVES, 3, III, MARINE POLLUTANT



MEX

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
Description	UN1133, ADHESIVES, 3, III

ICAO

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
Description	UN1133, ADHESIVES, 3, III

IATA

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
Description	UN1133, ADHESIVES, 3, III

IMDG/IMO

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
EmS-No.	F-E, S-D
Description	UN1133, ADHESIVES, 3, III, (9°C C.C.), MARINE POLLUTANT

RID

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
Classification code	F1
Description	UN1133, ADHESIVES, 3, III

ADR

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
Classification code	F1
Tunnel restriction code	(D/E)
Description	UN1133, ADHESIVES, 3, III

ADN

UN-No.	UN1133
Proper Shipping Name	ADHESIVES
Hazard Class	3
Packing Group	III
Classification code	F1
Special Provisions	640E
Description	UN1133, ADHESIVES, 3, III

Hazard Labels 3
 Limited Quantity 5 L
 Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	7 - 13	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Toluene 108-88-3	X	X	X	X	X

International Regulations



Mexico**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Toluene 108-88-3 (7 - 13)		Mexico: TWA 50 ppm Mexico: TWA 188 mg/m ³

*Mexico - Occupational Exposure Limits - Carcinogens***Canada****WHMIS Hazard Class**

B2 - Flammable liquid

D2A - Very toxic materials

D2B - Toxic materials

**16. OTHER INFORMATION**

NFPA	Health Hazards	2	Flammability	3	Instability	0	Physical and Chemical Hazards	-
HMIS	Health Hazards	2 *	Flammability	3	Physical Hazard	0	Personal Protection	X

Chronic Hazard Star Legend * = Chronic Health Hazard**Prepared By**

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date

27-Oct-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet